



GROWING TOGETHER

FLOTATION

AGRICULTURAL TIRES





A G R I C U L T U R A L T I R E S

FLC

At BKT, we develop tires for every application. That is why we have designed a broad and specific Flotation tire lineup for agricultural trailers. Suitable for combined usage on the road and in the fields, the name stands for the great plus provided by this flotation range, which results in minor impact on the terrain.

High load capacity along with lower inflation pressure makes sure that all soils are best preserved.

Every pattern has distinctive features making it suitable for specific applications.

Find out which tire is perfect for your needs.





OTATION



Radial

Radial tires have steel cords that are arranged running radially from bead to bead around the tire. Sidewall and tread have independent functional features providing more flexibility, great performance, durability, and fuel economy.



Bias

Bias tires have cord plies that are arranged running diagonally from bead to bead across the tire. Layers overlap forming a crisscross pattern. This design features extraordinary sidewall resistance and puncture resistance.



GROWING TOGETHER

AGRICULTURAL TIRES

FLO

TECHNOLOGIES



All Steel



Block Pattern



Extra Steel Belted



Heavy Duty



High Speed



Larger Footprint



Reinforced Bead



Reinforced Carcass



Rounded Shoulder Technology



Special Compound



Steel Belted



Strong Casing















VF Technology



OTATION

PERFORMANCE



FLOTATION TIRES



V-FLEXA



[p. 8]



RIDEMAX FL 699



[p. 9]



FL 633 PERFORMA



[p. 10]



RIDEMAX FL 690



[p. 11]



RIDEMAX FL 693 M



[p. 12]



FL 630 SUPER



[p. 15]



FL 630 ULTRA



[p. 17]



FL 635



[p. 18]



FL 637



[p. 19]



FL 639



[p. 20]



FL 695



[p. 21]



RIDEMAX FL 615



[p. 22]



FLOTATION 351



[p. 23]



FLOTATION 558



[p. 24]



FLOTATION 647



[p. 25]



FLOTATION 648



[p. 26]



FLOTATION 648 T



[p. 30]



FLOTATION TR 675



[p. 31]



FLOTATION TR 678



[p. 32]



FLOTATION RIB 774



[p. 33]



SR 234



[p. 34]



Radial



V-FLEXA

V-FLEXA is a radial tire specifically designed for agricultural trailers. It is a latest-generation flotation product featuring VF technology, which enables the transport of heavy loads both in the fields and on the road with an inflation pressure that is 30% less than that of a standard tire of the same size. Additional steel belts confer major resistance to the casing against impacts. Not only does V-FLEXA support heavy loads in full safety, it also avoids soil compaction thanks to perfect weight distribution. Moreover, V-FLEXA features great self-cleaning properties, durability as well as low rolling resistance.

Technologies



VF Technology



High Speed



Reinforced Bead



Extra Steel Belted

Performance



Reduced Soil Compaction



Traction



High Load Capacity



Durability



Low Rolling Resistance

	Tire size	LI/SS		RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	SRI (index)	Version	
		DW	FR	Rec.	Alt.							
Ø 22.5"	VF 560/60 R 22.5	166 D		AG 16.00	-	555	1250	550	3756	600	SB	
	Ø 26.5"	VF 600/55 R 26.5	167 D		AG 20.00	-	615	1342	580	3986	650	SB
		VF 600/65 R 26.5	172 D		AG 20.00	-	615	1453	628	4377	700	SB
		VF 650/55 R 26.5	171 D		AG 20.00	-	644	1389	591	4100	650	SB
	VF 710/50 R 26.5	176 D	176 D	AG 24.00	-	727	1383	600	4193	650	SB	
	VF 750/45 R 26.5	176 D	176 D	AG 24.00	-	755	1349	585	4095	650	SB	
	VF 800/45 R 26.5	179 D	179 D	AG 28.00	AG 24.00	805	1393	602	4213	675	SB	
Ø 30.5"	VF 710/50 R 30.5	178 D	178 D	AG 24.00	-	727	1485	654	4511	700	SB	
	VF 750/60 R 30.5	187 D	187 D	AG 24.00	-	780	1678	728	5085	800	SB	
	VF 750/60 R 30.5	187 D	187 D	AG 24.00	-	780	1678	728	5085	800	SB	
Ø 32"	VF 800/60 R 32 (VF 30.5 L R 32)	191 D	191 D	DW 27 B	DW 25 B	818	1799	785	5459	850	SB	



SB: Steel Belted



RIDEMAX FL 699

RADIAL TRANSPORT TIRES

RIDEMAX FL 699 is the perfect BKT tire for road applications with trailers and tank trucks. This All Steel tire stands out for its high mileage and durability. The reinforced bead ensures better stability even at high speeds. Even if this radial tire has been designed for a 90% on-the-road usage, i.e. for transport in farming applications, the new RIDEMAX FL 699 also provides excellent performance in the fields. The tire has been designed with a particular focus on load capacity to decrease the number of transport cycles. Good news also to farmers who know the sensation when a trailer seems to compromise driving: RIDEMAX FL 699 ensures an extraordinarily comfortable ride providing safety and driving control.

	Tire size	LI/SS	RIM		O.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	SRI (index)	Version
			Rec.	Alt.						
										
Ø 20.5"	24 R 20.5	176 F	18.00	-	590	1370	613	4165	-	STD
	525/65 R 20.5	173 F	16.00	-	518	1200	544	3678	-	STD

STD: Standard



Radial



Technologies



All Steel



High Speed



Reinforced Bead

Performance



High Mileage



Durability



High Load Capacity



Stability



Cut and Chip Resistance



Radial



FL 633 PERFORMA

The new All Steel radial tire FL 633 PERFORMA perfectly combines the needs of several agricultural applications with the growing demand for logistics in agriculture. Specifically designed for agro trucks, FL 633 PERFORMA is the innovative solution that enhances both tractor and truck performance features to meet the special needs of modern farming. Thanks to its very strong casing, exceptional load capacity and durability, FL 633 PERFORMA signs the "next level" of flotation tires being suitable for multiple activities in the fields and even for travel on highways reaching up to 100 km/h.

Technologies



High Speed



All Steel



Strong Casing

Performance



High Load Capacity



Durability



Self-Cleaning



Multi-Purpose Tires

	Tire size	LI/SS	RIM		O.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	SRI (index)	Version
			Rec.	Alt.						
Ø 22.5"	600/50 R 22.5	164 J	AG 20.00	-	590	1170	534	3559	-	STD

STD: Standard







RIDEMAX FL 690

RADIAL TRANSPORT TIRES

RIDEMAX FL 690 is a radial flotation and transport tire for tank trucks and trailers. The tire is suitable for 75% on-the-road applications. As a response to the increasing demand for high loads in modern agriculture, BKT has designed this steel-belted tire withstanding very heavy loads and increasing the farmer's productivity. The low rolling resistance contributes to better fuel economy.

	Tire size	LI/SS	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	SRI (index)	Version
			Rec.	Alt.						
										
Ø 26"	28 L R 26 (750/65 R 26)	176 A8/173 B	DW 25 B	DW 23 B	719	1590	695	4745	750	STD
Ø 32"	30.5 L R 32	184 A8/181 B	DH 27 B	DW 27 B	790	1800	806	5430	875	STD
	800/60 R 32	185 D	DH 27 B	DW 27 B	800	1800	817	5454	850	STD
	VF 900/65 R 32 (VF 35.5 L R 32)	197 D	DW 31 B	DW 30 ; TW 30	930	1986	838	5878	925	STD

STD: Standard



Radial



Technologies



Steel Belted



Reinforced Bead



High Speed



Block Pattern

Performance



Road Oriented



Durability



Fuel Economy



Radial



RIDEMAX FL 693 M

RADIAL TRANSPORT TIRES

RIDEMAX FL 693 M is the ideal radial tire for those who frequently travel on the road with trailers/tank trucks. Actually designed for 75% on-the-road use, RIDEMAX FL 693 M provides excellent road performance prioritizing both comfort and self-cleaning properties. The speed index classes D/E of the range stands for higher speeds when travelling on the road leading to significant time savings. The low rolling resistance contributes to less fuel consumption, while a reinforced bead and steel belts ensure enhanced durability.

Technologies



Steel Belted



Reinforced Bead



High Speed



Block Pattern

Performance



Road Oriented



Durability



Fuel Economy





Self-Cleaning

	Tire size	LI/SS	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	SRI (index)	Version
			Rec.	Alt.						
Ø 17"	425/55 R 17	129 D/ 140 A8	13.00	-	420	894	397	2704	425	STD
	500/50 R 17	149 D/ 146 E	16.00	-	503	932	424	2913	450	STD
	VF 500/50 R 17	156 D	16.00	-	503	932	422	2880	450	STD
Ø 17.5"	400/45 R 17.5	139 D	14.00	-	400	800	343	2357	390	STD
	VF 400/45 R 17.5	142 D	14.00	-	400	800	357	2448	390	STD
Ø 22.5"	500/45 R 22.5	146 D/ 143 E	AG 16.00	-	503	1022	455	3114	500	STD
	500/60 R 22.5	155 D/ 152 E	AG 16.00	15.00 ; 17.00	503	1172	531	3577	550	STD
	500/60 R 22.5	163 D	AG 16.00	15.00 ; 17.00	503	1172	544	3625	550	STD
	560/45 R 22.5	152 D/ 149 E	AG 16.00	-	543	1076	491	3306	525	STD
	560/45 R 22.5	160 D	AG 16.00	-	543	1076	491	3306	525	STD
	560/55 R 22.5	158 D/ 155 E	AG 16.00	17.00 ; 20.00	543	1180	533	3614	550	STD
	560/55 R 22.5	162 D	AG 16.00	17.00 ; 20.00	543	1180	533	3614	550	STD
	560/60 R 22.5	161 D/ 158 E	AG 16.00	16.00 ; 17.00 ; AG 20.00	543	1244	549	3767	600	STD
	560/60 R 22.5	165 D/ 162 E	AG 16.00	16.00 ; 17.00 ; AG 20.00	543	1244	552	3767	600	STD

STD: Standard



	Tire size	LI/SS	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	SRI (index)	Version
			Rec.	Alt.						
										
Ø 22.5"	560/60 R 22.5	169 D	AG 16.00	16.00 ; 17.00 ; AG 20.00	543	1244	552	3767	600	STD
	580/65 R 22.5	166 D/ 163 E	AG 18.00	AG 16.00 ; AG 17.00 ; AG 20.00	577	1326	572	4031	625	STD
	600/50 R 22.5	159 D/ 156 E	AG 20.00	-	611	1172	516	3574	550	STD
	650/50 R 22.5	163 D/ 160 E	AG 20.00	-	645	1222	535	3715	575	STD
	650/50 R 22.5	168 D	AG 20.00	-	645	1222	535	3715	575	STD
	710/35 R 22.5	157 D/ 154 E	AG 24.00	-	712	1070	482	3254	525	STD
	710/45 R 22.5	165 D	AG 24.00	-	706	1212	542	3658	575	STD
Ø 26.5"	600/55 R 26.5	165 D	AG 20.00	-	611	1333	586	4051	625	STD
	600/55 R 26.5	177 D	AG 20.00	-	611	1333	586	4077	625	HD
	650/55 R 26.5	169 D	AG 20.00	-	645	1389	620	4216	650	STD
	650/55 R 26.5	178 D	AG 20.00	-	645	1389	615	4250	650	HD
	710/50 R 26.5	170 D	AG 24.00	AG 20.00	727	1383	624	4217	650	STD
	710/50 R 26.5	179 D	AG 24.00	AG 20.00	727	1383	606	4217	650	HD
Ø 30.5"	600/60 R 30.5	169 D	AG 20.00	AG 18.00	605	1495	681	4495	725	STD

STD: Standard - HD: Heavy Duty





Radial



182



RIDEMAX FL 693 M

RADIAL TRANSPORT TIRES

RIDEMAX FL 693 M is the ideal radial tire for those who frequently travel on the road with trailers/tank trucks. Actually designed for 75% on-the-road use, RIDEMAX FL 693 M provides excellent road performance prioritizing both comfort and self-cleaning properties. The speed index classes D/E of the range stands for higher speeds when travelling on the road leading to significant time savings. The low rolling resistance contributes to less fuel consumption, while a reinforced bead and steel belts ensure enhanced durability.

Technologies



Steel Belted



Reinforced Bead



High Speed



Block Pattern

Performance



Road Oriented



Durability



Fuel Economy



Self-Cleaning

Ø 30.5"	Tire size	LI/SS	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	SRI (index)	Version
			Rec.	Alt.						
	600/60 R 30.5	173 D	AG 20.00	AG 18.00	605	1495	681	4495	725	STD
	650/65 R 30.5	176 D	AG 20.00	-	645	1623	734	4939	775	STD
	710/50 R 30.5	173 D	AG 24.00	AG 20.00	727	1485	676	4533	700	STD
	750/60 R 30.5	181 D	AG 24.00	-	754	1675	728	5092	800	STD
	850/50 R 30.5	182 D	AG 28.00	-	862	1625	719	4925	725	STD



STD: Standard





FL 630 SUPER

FL 630 SUPER is a flotation tire suitable for field and road applications with trailers, tankers and spreaders. Its resistant structure provides excellent traction and perfect grip even in bends and when maneuvering, while a reinforced bead and steel belts ensure enhanced durability.

	Tire size	LI/SS	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	SRI (index)	Version
			Rec.	Alt.						
										
Ø 22.5"	560/60 R 22.5	165 D	AG 16.00	17.00 ; 20.00	543	1244	549	3785	600	STD
	560/60 R 22.5	161 D	AG 16.00	17.00 ; 20.00	543	1244	549	3785	600	STD
	580/65 R 22.5	166 D	AG 18.00	AG 16.00 ; AG 17.00 ; AG 20.00	577	1326	594	4058	625	STD
	580/65 R 22.5	174 D	AG 18.00	AG 16.00 ; AG 17.00 ; AG 20.00	582	1326	594	4058	625	STD
	600/50 R 22.5	159 D	AG 20.00	-	611	1170	518	3533	550	STD
	600/55 R 22.5	162 D	AG 20.00	-	595	1232	560	3757	575	STD
Ø 26.5"	600/55 R 26.5	165 D	AG 20.00	-	611	1333	606	4078	625	SB
	600/55 R 26.5	177 D	AG 20.00	-	611	1333	604	4104	625	HD
	650/55 R 26.5	169 D	AG 20.00	-	645	1389	627	4258	650	STD
	650/55 R 26.5	178 D	AG 20.00	-	645	1389	628	4292	650	HD
	650/65 R 26.5	174 D	AG 20.00	-	645	1519	684	4653	725	STD
	710/50 R 26.5	170 D	AG 24.00	AG 20.00	727	1383	626	4237	650	STD
	750/45 R 26.5	170 D	AG 24.00	-	754	1349	606	4147	650	STD
	750/60 R 26.5	180 D	AG 24.00	-	754	1574	694	4800	725	STD

STD: Standard - HD: Heavy Duty - SB: Steel Belted



Radial



Technologies



Steel Belted



Reinforced Bead



High Speed

Performance



Durability



Field Protection



Excellent flotation



Self-Cleaning



Traction





Radial



182



FL 630 SUPER

FL 630 SUPER is a flotation tire suitable for field and road applications with trailers, tankers and spreaders. Its resistant structure provides excellent traction and perfect grip even in bends and when maneuvering, while a reinforced bead and steel belts ensure enhanced durability.

Technologies



Steel Belted



Reinforced Bead



High Speed

Performance



Durability



Field Protection



Excellent flotation



Self-Cleaning



Traction

	Tire size	LI/SS	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	SRI (index)	Version
			Rec.	Alt.						
Ø 30.5"	650/65 R 30.5	176 D	AG 20.00	-	645	1621	734	4976	775	STD
	710/50 R 30.5	173 D	AG 20.00	AG 24.00	686	1485	676	4550	700	SB
	750/60 R 30.5	181 D	AG 24.00	-	754	1675	746	5115	800	STD
	850/50 R 30.5	182 D	AG 28.00	-	860	1625	722	4895	775	STD



STD: Standard - SB: Steel Belted





FL 630 ULTRA

FL 630 ULTRA is suitable for trailers, tankers and spreaders. Thanks to its reinforced bead and the particular tread design, it is the ideal tire for multipurpose use on any kind of land or on the road. FL 630 ULTRA stands for extraordinarily reduced soil compaction.

	Tire size	LI/SS	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	SRI (index)	Version
			Rec.	Alt.						
										
Ø 22.5"	500/60 R 22.5	155 D/166 A8	AG 16.00	15.00 ; 16.00 ; 17.00	503	1172	521	3592	550	STD
	560/45 R 22.5	152 D/163 A8	AG 16.00	-	543	1076	490	3290	525	STD
	560/60 R 22.5	161 D/172 A8	AG 16.00	16.00 ; 17.00 ; AG 20.00	543	1244	535	3760	600	STD
	600/50 R 22.5	159 D/170 A8	AG 20.00	-	611	1172	518	3533	550	STD
	710/40 R 22.5	161 D/172 A8	AG 24.00	-	727	1140	514	3490	550	STD
Ø 26.5"	600/55 R 26.5	165 D/176 A8	AG 20.00	-	611	1333	579	4070	625	STD
	650/55 R 26.5	169 D/180 A8	AG 20.00	-	645	1389	600	4207	650	STD
	710/50 R 26.5	170 D/181 A8	AG 24.00	AG 20.00	727	1383	599	4208	650	STD
	800/45 R 26.5	174 D/184 A8	AG 28.00	AG 24.00	828	1393	618	4238	675	STD

STD: Standard



Radial



Technologies



Reinforced Bead

Performance



Reduced Soil Compaction



Radial



FL 635

FL 635 is a radial flotation tire suitable for both road and field usage. The special block pattern has been designed for hay baler applications. FL 635 ensures a great pressure distribution on the ground across the footprint and drastically reduces soil compaction to preserve the value of the crops. The tire ensures great self-cleaning properties, durability and traction along with excellent speed features.

Technologies



Reinforced Bead



High Speed

Performance



Reduced Soil Compaction



Traction



Self-Cleaning



Durability

	Tire size	LI/SS	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	SRI (index)	Version
			Rec.	Alt.						
Ø 22.5"	500/45 R 22.5	136 D	AG 16.00	-	490	1022	461	3086	500	STD
	620/40 R 22.5	154 D	AG 20.00	-	625	1068	470	3249	500	STD
	650/55 R 22.5	167 D	AG 20.00	-	645	1287	568	3901	600	STD
	710/40 R 22.5	161 D	AG 24.00	-	727	1140	510	3467	550	STD
	750/45 R 22.5	168 D	AG 24.00	-	754	1247	555	3810	600	STD



STD: Standard





FL 637

FL 637 is a radial flotation tire suitable for spreaders, trailers and tankers. The reinforced bead structure provides enhanced durability and higher load capacity. In addition to excellent flotation features leading to reduced soil compaction, this tire shows outstanding self-cleaning properties. The directional tread design ensures excellent traction and enabling speeds up to 70 km/h.

	Tire size	LI/SS	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	SRI (index)	Version
			Rec.	Alt.						
										
Ø 17"	520/50 R 17	151 D/148 E	16.00	-	516	952	414	2930	450	STD
Ø 22.5"	560/45 R 22.5	160 D	AG 16.00	-	544	1076	501	3324	525	STD

STD: Standard



Radial



E



160

Technologies



Reinforced Bead



High Speed

Performance



Reduced Soil Compaction



Traction



Self-Cleaning



Durability



Radial



FL 639

FL 639 is a field-oriented flotation radial tire also suitable for spreading applications. Its wide footprint area ensures low soil compaction resulting in increased crop productivity. The reinforced bead and the sidewall protection contribute to an extended tire life-cycle. FL 639 ensures extraordinary traction along with great self-cleaning properties.

Technologies



Reinforced Bead



High Speed

Performance



Reduced Soil Compaction



Traction



Self-Cleaning



Durability

	Tire size	LI/SS		RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	SRI (index)	Version
		DW	FR	Rec.	Alt.						
Ø 22.5"	560/45 R 22.5	152 D/163 A8		AG 16.00	-	543	1076	484	3303	525	STD
	600/50 R 22.5	159 D/170 A8		AG 20.00	-	611	1172	530	3540	550	STD
	600/50 R 22.5	156 B	168 B	AG 20.00	-	611	1172	521	3592	550	STD
	710/40 R 22.5	161 D/172 A8		AG 24.00	-	727	1140	503	3492	550	STD
	710/40 R 22.5	158 B	170 B	AG 24.00	-	727	1140	503	3492	550	STD
	800/40 R 22.5	168 D/178 A8		AG 28.00	-	828	1212	538	3642	575	STD
Ø 26.5"	850/40 R 26.5	173 D/184 A8		AG 28.00	-	860	1355	599	4122	650	STD


STD: Standard





FL 695

FL 695 has been specifically designed for trailers in construction and transport applications with a unique center block tread pattern. Thanks to its strong casing, FL 695 can carry heavy loads maintaining stability in all conditions and its deep tread ensures optimal self-cleaning during on and off-road applications. Multiple steel cord layers reinforce this pattern against punctures.

	Tire size	Type	LI/SS		RIM		Version	S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	SRI (index)	TREAD DEPTH (mm)
			DW	FR	Rec.	Alt.							
													
Ø 26.5"	600/55 R 26.5	TL	173 D		AG 20.00	-	SB	591	1335	620	4090	625	27
	650/55 R 26.5	TL	178 D		AG 20.00	AG 22.00	SB	630	1390	630	4242	675	27
Ø 30.5"	600/60 R 30.5	TL	179 D	179 D	AG 20.00	-	SB	611	1495	693	4586	725	27
	710/50 R 30.5	TL	177 D	177 D	AG 24.00	AG 20.00	SB	700	1490	691	4553	700	28

SB: Steel Belted



Radial



Technologies



Block Pattern



Steel Belted



Special Compound



Strong Casing

Performance



Self-Cleaning



High Load Capacity



Stability



High Puncture Resistance



Radial



190



RIDE MAX FL 615

RADIAL TRANSPORT TIRES

RIDE MAX FL 615 is a radial flotation tire suitable for non-driven wheels of trailers, tankers and spreaders. The steel belted structure offers high puncture resistant with increased durability and high load capacity. RIDE MAX FL 615 provides low rolling resistance on road with outstanding self-cleaning properties on the field. The rounded shoulder and wide footprint area ensure soil protection.

Technologies



Steel Belted



Rounded Shoulder Technology

Performance



Reduced Soil Compaction



Self-Cleaning



High Load Capacity



Ideal for grassland



Low Rolling Resistance

	Tire size	LI/SS	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	SRI (index)	Version
			Rec.	Alt.						
Ø 32"	800/65 R 32	185 D	DW 27 B	-	830	1853	834	5624	875	SB
	VF 800/65 R 32	190 D	DW 28 B	-	815	1850	811	5610	875	SB

SB: Steel Belted





FLOTATION 351

FLOTATION 351 is a bias flotation tire which best suits transport applications using trailers. Extra deep lugs provide outstanding traction and a longer tire life. FLOTATION 351 is the ideal tire on wet and moist surfaces ensuring high load capacity.

	Tire size	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS
		Rec.	Alt.								
Ø 20"	42 X 25.00 - 20	20.50 HF	20.50 VF	605	1110	508	3302	STD	12	TL	135 B
	42 X 25.00 - 20	20.50 HF	20.50 VF	605	1110	508	3302	STD	16	TL	139 B
	48 X 25.00 - 20	20.50 HF	20.50 VF	630	1270	559	3785	STD	10	TL	144 B
	48 X 31.00 - 20	26.00 HF	26.00 VF	775	1283	559	3886	STD	12	TL	148 B
Ø 25"	66 X 43.00 - 25	36.0 TH	-	1020	1750	782	5213	STD	6	TL	150 B
	66 X 43.00 - 25	36.0 TH	-	1020	1750	782	5213	STD	10	TL	160 B
	66 X 43.00 - 25	36.0 TH	-	1020	1750	782	5213	STD	16	TL	170 B

STD: Standard



Bias



HF-3



B



170

Performance



High Load Capacity



Durability



Traction



Bias



FLOTATION 558

FLOTATION 558 is a cross-ply flotation tire suitable for hay harvesters/balers, tankers and trailers both on and off the road. It is particularly recommended whenever traction is essential for good soil tillage in addition to high load capacity.

Performance



High Load Capacity



Durability



Traction

Tire size	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS		
	Rec.	Alt.								DW	FR	
Ø 22.5"	400/55 - 22.5	AG 11.75	12.25; 13.00; AG 13.00	405	1020	445	3084	STD	14	TL	138 A8/ 134 B	150 A8/ 146 B
	400/55 - 22.5	AG 11.75	12.25; 13.00; AG 13.00	405	1020	445	3084	STD	16	TL	140 A8/ 136 B	152 A8/ 148 B
	400/55 - 22.5	AG 11.75	12.25; 13.00; AG 13.00	405	1020	445	3084	AB HD	16	TL	140 A8/ 136 B	152 A8/ 148 B
	400/55 - 22.5	AG 11.75	12.25; 13.00; AG 13.00	405	1020	445	3084	STD	20	TL	144 A8/ 140 B	156 A8/ 152 B
	500/45 - 22.5	AG 16.00	-	500	1045	471	3167	STD	12	TL	136 A8/ 132 B	148 A8/ 144 B
	500/45 - 22.5	AG 16.00	-	500	1045	471	3167	STD	16	TL	142 A8/ 138 B	154 A8/ 150 B
	500/45 - 22.5	AG 16.00	-	500	1045	471	3167	AB HD	16	TL	142 A8/ 138 B	154 A8/ 150 B
	500/45 - 22.5	AG 16.00	-	500	1045	471	3167	STD	20	TL	146 A8/ 142 B	158 A8/ 154 B



STD: Standard - AB HD: Aramid Belted Heavy Duty





FLOTATION 647

FLOTATION 647 is an implement tire that features best traction on soft soil and grassland. In addition to excellent self-cleaning properties, the specially designed tread pattern provides a wide contact area, which ensures optimized ground pressure and excellent performance on soft soil.

	Tire size	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS	
		Rec.	Alt.								DW	FR
												
Ø 15.3"	260/75 - 15.3	9.00	-	275	785	363	2380	STD	-	TL	119 A8	131 A8
Ø 17"	380/55 - 17	13.00	-	385	882	-	-	STD	-	TL	125 A8	138 A8
	520/50 - 17	AG 16.00	-	516	965	426	2907	STD	-	TL	147 B	159 B
Ø 18"	425/70 - 18	13.00	-	435	1065	-	-	STD	-	TL	143 B	155 B

STD: Standard



Bias



B



159

Performance



Self-Cleaning



Traction





Bias



189



FLOTATION 648

FLOTATION 648 is particularly suitable for field and road transport as well as for spreading operations. Some sizes are designed for hay harvesters/balers. The special tread design allows for carrying very heavy loads at low pressure, guaranteeing at the same time reduced soil compaction and preventing damage to crops.

Technologies



Heavy Duty



Reinforced Carcass



High Speed

Performance



High Load Capacity



Durability



Reduced Soil Compaction





Traction

	Tire size	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS	
		Rec.	Alt.								DW	FR
Ø 17"	500/50 - 17	16.00	-	510	945	416	2750	STD	10	TL	128 A8/ 124 B	140 A8/ 136 B
	500/50 - 17	16.00	-	510	945	416	2750	STD	14	TL	137 A8/ 133 B	149 A8/ 145 B
	500/50 - 17	16.00	-	510	945	416	2750	STD	16	TL	139 A8/ 135 B	152 A8/ 148 B
	500/50 - 17	16.00	-	510	945	416	2750	STD	18	TL	145 A8/ 141 B	157 A8/ 154 B
Ø 20"	500/55 - 20	16.00	-	508	1058	458	3153	STD	12	TL	138 A8/ 134 B	150 A8/ 146 B
Ø 22.5"	350/65 - 22.5	AG 11.75	-	358	1030	451	3069	STD	18	TL	139 A8/ 135 B	151 A8/ 147 B
	385/65 - 22.5 (400/60 - 22.5)	AG 11.75	-	400	1070	475	3233	STD	16	TL	144 A8/ 140 B	156 A8/ 152 B
	385/65 - 22.5 (400/60 - 22.5)	AG 11.75	-	400	1070	475	3233	STD	18	TL	148 A8/ 144 B	160 A8/ 156 B
	385/65 - 22.5 (400/60 - 22.5)	AG 11.75	-	400	1070	475	3233	STD	22	TL	155 A8/ 151 B	167 A8/ 163 B
	400/60 - 22.5 (385/65 - 22.5)	AG 11.75	-	400	1070	475	3233	STD	22	TL	155 A8/ 151 B	167 A8/ 163 B
	400/60 - 22.5 (385/65 - 22.5)	AG 11.75	-	400	1070	475	3233	STD	16	TL	144 A8/ 140 B	156 A8/ 152 B
	400/60 - 22.5 (385/65 - 22.5)	AG 11.75	-	400	1070	475	3233	STD	18	TL	148 A8/ 144 B	160 A8/ 156 B
	500/50 - 22.5	AG 16.00	-	500	1070	475	3200	STD	16	TL	146 A8/ 142 B	158 A8/ 155 B
	500/50 - 22.5	AG 16.00	-	500	1070	475	3200	STD	20	TL	151 A8/ 147 B	163 A8/ 159 B

STD: Standard



	Tire size	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS	
		Rec.	Alt.								DW	FR
												
Ø 22.5"	500/50 - 22.5	AG 16.00	-	500	1070	475	3200	STD	12	TL	140 A8/ 136 B	152 A8/ 148 B
	500/60 - 22.5	AG 16.00	15.00 ; 17.00	500	1170	510	3489	STD	18	TL	153 A8/ 149 B	165 A8/ 161 B
	500/60 - 22.5	AG 16.00	15.00 ; 17.00	500	1170	510	3489	STD	12	TL	145 A8/ 142 B	157 A8/ 154 B
	500/60 - 22.5	AG 16.00	15.00 ; 17.00	500	1170	510	3489	STD	16	TL	151 A8/ 148 B	163 A8/ 159 B
	550/45 - 22.5	AG 16.00	-	525	1070	488	3253	STD	20	TL	154 A8/ 150 B	166 A8/ 162 B
	550/45 - 22.5	AG 16.00	-	525	1070	488	3253	STD	16	TL	147 A8/ 144 B	159 A8/ 156 B
	550/60 - 22.5	AG 16.00	-	550	1240	540	3725	STD	12	TL	148 A8/ 144 B	160 A8/ 156 B
	550/60 - 22.5	AG 16.00	-	550	1240	540	3725	STD	18	TL	156 A8/ 152 B	169 A8/ 165 B
	550/60 - 22.5	AG 16.00	-	550	1240	540	3725	STD	20	TL	158 A8/ 154 B	171 A8/ 167 B
	550/60 - 22.5	AG 16.00	-	550	1240	540	3725	DB	20	TL	158 A8/ 154 B	171 A8/ 167 B
	600/50 - 22.5	AG 20.00	-	611	1170	510	3501	STD	12	TL	147 A8/ 144 B	159 A8/ 156 B
	600/50 - 22.5	AG 20.00	-	611	1170	510	3501	STD	16	TL	153 A8/ 149 B	165 A8/ 161 B
	600/50 - 22.5	AG 20.00	-	611	1170	510	3501	STD	18	TL	155 A8/ 151 B	167 A8/ 163 B
600/50 - 22.5	AG 20.00	-	611	1170	510	3501	DB	20	TL	156 A8/ 152 B	169 A8/ 165 B	

STD: Standard - DB: Dual Bead





Bias



189



FLOTATION 648

FLOTATION 648 is particularly suitable for field and road transport as well as for spreading operations. Some sizes are designed for hay harvesters/balers. The special tread design allows for carrying very heavy loads at low pressure, guaranteeing at the same time reduced soil compaction and preventing damage to crops.

Technologies



Heavy Duty



Reinforced Carcass



High Speed

Performance



High Load Capacity



Durability



Reduced Soil Compaction





Traction

	Tire size	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS	
		Rec.	Alt.								DW	FR
Ø 22.5"	600/55 - 22.5	AG 20.00	-	600	1230	540	3716	STD	12	TL	151 A8/ 148 B	164 A8/ 160 B
	600/55 - 22.5	AG 20.00	-	600	1230	540	3716	STD	16	TL	156 A8/ 153 B	169 A8/ 166 B
	600/55 - 22.5	AG 20.00	-	600	1230	540	3716	DB	20	TL	160 A8/ 156 B	173 A8/ 169 B
	700/40 - 22.5	AG 24.00	-	700	1170	510	3537	STD	16	TL	154 A8/ 150 B	166 A8/ 162 B
	700/40 - 22.5	AG 24.00	-	700	1170	510	3537	STD	12	TL	148 A8/ 144 B	160 A8/ 157 B
	700/40 - 22.5	AG 24.00	-	700	1170	510	3537	HD	18	TL	160 A8/ 156 B	173 A8/ 169 B
	700/50 - 22.5	24.00	-	700	1270	550	3775	STD	12	TL	156 A8/ 153 B	168 A8/ 164 B
	700/50 - 22.5	24.00	-	700	1270	550	3775	STD	16	TL	162 A8/ 158 B	174 A8/ 170 B
	700/50 - 22.5	24.00	-	700	1270	550	3775	HS	16	TL	158 B/ 154 E	170 B/ 166 E
Ø 26.5"	600/55 - 26.5	AG 20.00	-	611	1354	581	4017	STD	18	TL	160 A8/ 157 B	172 A6/ 169 B
	600/55 - 26.5	AG 20.00	-	611	1354	581	4017	STD	12	TL	153 A8/ 149 B	165 A8/ 161 B
	600/55 - 26.5	AG 20.00	-	611	1354	581	4017	STD	16	TL	159 A8/ 156 B	170 A8/ 167 B
	700/50 - 26.5	24.00	-	700	1373	621	4099	STD	12	TL	157 A8/ 154 B	169 A8/ 165 B
	700/50 - 26.5	24.00	-	700	1373	621	4099	STD	16	TL	162 A8/ 158 B	174 A8/ 170 B

STD: Standard - DB: Dual Bead - HS: High Speed - HD: Heavy Duty



	Tire size	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS	
		Rec.	Alt.								DW	FR
												
Ø 26.5"	800/45 - 26.5	AG 28.00	-	800	1393	631	4185	STD	12	TL	158 A8/ 155 B	170 A8/ 167 B
	800/45 - 26.5	AG 28.00	-	800	1393	631	4185	STD	20	TL	170 A8/ 167 B	183 A8/ 180 B
	800/45 - 26.5	AG 28.00	-	800	1393	631	4185	STD	16	TL	164 A8/ 160 B	177 A8/ 173 B
Ø 30.5"	650/65 - 30.5	AG 20.00	-	670	1660	710	4935	STD	12	TL	162 A8/ 158 B	174 A8/ 170 B
	650/65 - 30.5	AG 20.00	-	670	1660	710	4935	STD	16	TL	167 A8/ 163 B	179 A8/ 175 B
	650/65 - 30.5	AG 20.00	-	670	1660	710	4935	HD	16	TL	167 A8/ 163 B	179 A8/ 175 B
	650/65 - 30.5	AG 20.00	-	670	1660	710	4935	HD	18	TL	169 A8/ 165 B	181 A8/ 178 B
	750/60 - 30.5	AG 24.00	-	754	1675	710	4935	STD	12	TL	164 A8/ 160 B	176 A8/ 172 B
	750/60 - 30.5	AG 24.00	-	754	1675	710	4935	STD	16	TL	170 A8/ 167 B	182 A8/ 179 B
	850/50 - 30.5	AG 28.00	-	850	1650	710	4935	STD	12	TL	168 A8/ 164 B	180 A8/ 176 B
	850/50 - 30.5	AG 28.00	-	850	1650	710	4935	STD	16	TL	174 A8/ 170 B	186 A8/ 182 B
	850/50 - 30.5	AG 28.00	-	850	1650	710	4935	HD	16	TL	174 A8/ 170 B	186 A8/ 182 B
	850/50 - 30.5	AG 28.00	-	850	1650	710	4935	HD	18	TL	176 A8/ 173 B	189 A8/ 185 B

STD: Standard - HD: Heavy Duty



Bias



166



FLOTATION 648 T

FLOTATION 648 T is particularly suitable for hay harvesting as well as for field and road transport. The special tread design allows for carrying very heavy loads at low pressure and ensures outstanding self-cleaning properties. The tire also stands for excellent traction and durability.

Performance



Durability



High Load Capacity



Traction

Tire size	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS	
	Rec.	Alt.								DW	FR
	Ø 22.5"	AG 16.00	-	550	1070	475				3203	STD
550/45 - 22.5	AG 16.00	-	550	1070	475	3203	STD	20	TL	154 A8/ 150 B	166 A8/ 162 B



STD: Standard





FLOTATION TR 675

FLOTATION TR 675 is best suited for field and road transport. It fits trailers and implement machinery. FLOTATION TR 675 has been engineered to provide outstanding traction, high load capacity and a longer tire life.

	Tire size	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS	
		Rec.	Alt.								DW	FR
												
Ø 22.5"	500/60 - 22.5	AG 16.00	15.00; 17.00	515	1181	542	3604	DB	20	TL	155 A8/ 151 B	168 A8/ 164 B
	500/60 - 22.5	AG 16.00	15.00; 17.00	515	1181	542	3604	STD	12	TL	145 A8/ 142 B	157 A8/ 154 B
	500/60 - 22.5	AG 16.00	15.00; 17.00	515	1181	542	3604	STD	16	TL	151 A8/ 148 B	163 A8/ 159 B
	550/45 - 22.5	AG 16.00	-	543	1070	-	-	STD	20	TL	154 A8/ 150 B	166 A8/ 162 B
	550/60 - 22.5	AG 16.00	-	550	1260	547	3640	STD	12	TL	148 A8/ 144 B	160 A8/ 156 B
	550/60 - 22.5	AG 16.00	-	550	1260	547	3640	STD	16	TL	154 A8/ 150 B	167 A8/ 163 B

DB: Dual Bead - STD: Standard



Bias



B



168

Performance



Durability



High Load Capacity



Traction



Bias



173



FLOTATION TR 678

FLOTATION TR 678 has been specially designed for trailers and agricultural implements both on- and off the road. This tire allows for carrying very heavy loads at low pressure ensuring reduced soil compaction at the same time. It provides excellent traction and outstanding self-cleaning properties.

Performance



Durability



High Load Capacity



Self-Cleaning



Traction



	Tire size	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS	
		Rec.	Alt.								DW	FR
Ø 12"	320/60 - 12	10.50 I	-	328	689	327	2111	STD	-	TT	120A8	132A8
Ø 15.5"	280/60 - 15.5	8.0	-	275	750	357	2250	STD	-	TL	115A8	
	280/60 - 15.5	8.0	-	275	750	357	2250	STD	-	TL	128A8	
Ø 20"	500/45 - 20	16.00 DC	-	495	980	-	-	STD	-	TL	148A8	160A8
Ø 22.5"	600/40 - 22.5	AG 20.00	-	615	1085	483	3264	DB	20	TL	157A8	169A8
	600/40 - 22.5	AG 20.00	-	615	1085	483	3264	DB HD	20	TL	157A8	169A8
	600/40 - 22.5	AG 20.00	-	615	1085	483	3264	IND	20	TL	157A8	169A8
	650/45 - 22.5	AG 20.00	-	650	1150	502	3302	STD	20	TL	166 B	
	650/45 - 22.5	AG 20.00	-	650	1150	502	3302	SB	20	TL	166 B	
	650/45 - 22.5	AG 20.00	-	650	1150	502	3302	STD	-	TL	160 D	
	710/40 - 22.5	AG 24.00	-	707	1165	545	3624	SB	-	TL	173A8	
	710/40 - 22.5	AG 24.00	-	707	1165	-	-	A + SB	-	TL	173A8	

STD: Standard - DB: Dual Bead - DB HD: Dual Bead Heavy Duty - IND: Industrial - SB: Steel Belted - A + SB: Aramid + Steel Belted



FLOTATION RIB 774

FLOTATION RIB 774 is suitable in all free-rolling applications, hay harvesting applications and ideal for trailers. It has been designed to provide best handling comfort optimizing the timing of operations as well as high load capacity and a longer tire life.

	Tire size	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS	
		Rec.	Alt.								DW	FR
												
Ø 22.5"	550/60 - 22.5	AG 16.00	-	550	1240	540	3725	STD	12	TL	-	160 A8/ 156 B
	550/60 - 22.5	AG 16.00	-	550	1240	540	3725	STD	16	TL	-	167 A8/ 163 B
	600/55 - 22.5	AG 20.00	-	600	1230	540	3716	STD	16	TL	-	169 A8/ 166 B
	600/55 - 22.5	AG 20.00	-	600	1230	540	3716	STD	12	TL	-	164 A8/ 160 B

STD: Standard



Bias



169

Performance



Durability



High Load Capacity



Radial



Technologies



All Steel



VF Technology



Steel Belted



Larger Footprint



Special Compound

Performance



Reduced Soil Compaction



Comfort



Field Protection



Traction



Durability



Low Rolling Resistance



Fuel Economy



SR 234

SR 234 is a versatile All-Steel radial tire for agricultural implements that can be fitted on harvesters and balers, tillage toolbars, seeders, large feed mixers, and anhydrous ammonia trailers. Designed with VF (Very High Flexion) technology, SR 234 can carry up to 40% more load than a standard tire of the same size at the same inflation pressure. Thanks to its wide footprint and ability to operate at lower pressure, this VF tire ensures reduced soil compaction preserving soil fertility and porosity in addition to enhanced traction. The strong steel-belted casing and a multi-rib tread pattern along with a specially engineered compound provide uniform tread wear and great durability. The low rolling resistance enhances fuel efficiency on the road and a smooth ride. The hexagonal bead has been designed for easy mounting and a secure rim fitment. SR 234 is the ideal tire for operators looking for great performance both in the fields and on the road.

	Tire size	LI/SS	RIM		O.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	SRI (index)	Version
			Re.	Alt.						
Ø 22.5"	VF 445/50 R 22.5	167 D	14.00	-	438	1018	452	3050	-	STD

STD: Standard





Load index

The load index is a code that defines a tire's maximum weight capacity at the speed given by its speed index provided that the usage conditions recommended by the Manufacturer are fully complied with.

Corresponding values of load index (LI) and load capacity per wheel (kg / lbs)

LI	lbs	kg	LI	lbs	kg	LI	lbs	kg	LI	lbs	kg
50	420	190	85	1135	515	120	3085	1400	155	8540	3875
51	430	195	86	1170	530	121	3195	1450	156	8820	4000
52	440	200	87	1200	545	122	3305	1500	157	9095	4125
53	455	206	88	1235	560	123	3415	1550	158	9370	4250
54	465	212	89	1280	580	124	3525	1600	159	9645	4375
55	480	218	90	1325	600	125	3635	1650	160	9920	4500
56	495	224	91	1355	615	126	3750	1700	161	10195	4625
57	505	230	92	1390	630	127	3860	1750	162	10470	4750
58	520	236	93	1435	650	128	3970	1800	163	10745	4875
59	535	243	94	1475	670	129	4080	1850	164	11025	5000
60	550	250	95	1520	690	130	4190	1900	165	11355	5150
61	565	257	96	1565	710	131	4300	1950	166	11685	5300
62	585	265	97	1610	730	132	4410	2000	167	12015	5450
63	600	272	98	1655	750	133	4540	2060	168	12345	5600
64	615	280	99	1710	775	134	4675	2120	169	12785	5800
65	640	290	100	1765	800	135	4805	2180	170	13225	6000
66	660	300	101	1820	825	136	4940	2240	171	13560	6150
67	675	307	102	1875	850	137	5070	2300	172	13890	6300
68	695	315	103	1930	875	138	5205	2360	173	14330	6500
69	715	325	104	1985	900	139	5355	2430	174	14770	6700
70	740	335	105	2040	925	140	5510	2500	175	15210	6900
71	760	345	106	2095	950	141	5675	2575	176	15650	7100
72	785	355	107	2150	975	142	5840	2650	177	16095	7300
73	805	365	108	2205	1000	143	6005	2725	178	16535	7500
74	825	375	109	2270	1030	144	6175	2800	179	17085	7750
75	855	387	110	2335	1060	145	6395	2900	180	17635	8000
76	880	400	111	2405	1090	146	6615	3000	181	18185	8250
77	910	412	112	2470	1120	147	6780	3075	182	18740	8500
78	935	425	113	2535	1150	148	6945	3150	183	19290	8750
79	965	437	114	2600	1180	149	7165	3250	184	19840	9000
80	990	450	115	2680	1215	150	7385	3350	185	20390	9250
81	1020	462	116	2755	1250	151	7605	3450	186	20945	9500
82	1045	475	117	2835	1285	152	7825	3550	187	21495	9750
83	1075	487	118	2910	1320	153	8045	3650	188	22045	10000
84	1100	500	119	3000	1360	154	8265	3750	189	22705	10300

LI	lbs	kg	LI	lbs	kg	LI	lbs	kg
190	23370	10600	200	30865	14000	210	41885	19000
191	24030	10900	201	31965	14500	211	42990	19500
192	24690	11200	202	33070	15000	212	44090	20000
193	25350	11500	203	34170	15500	213	45415	20600
194	26015	11800	204	35270	16000	214	46735	21200
195	26785	12150	205	36375	16500	215	48060	21800
196	27555	12500	206	37475	17000	216	49380	22400
197	28330	12850	207	38580	17500	217	50705	23000
198	29100	13200	208	39680	18000	218	52025	23600
199	29980	13600	209	40785	18500	219	53570	24300

Speed index

The speed index is a value that indicates the maximum admitted speed at which the tire can carry the weight corresponding to its load index provided that the usage conditions recommended by the Manufacturer are fully complied with.

Speed index	A2	A4	A6	A8	B	C	D	E	F	G	J	K
km/h	10	20	30	40	50	60	65	70	80	90	100	110
mph	5	10	20	25	30	35	40	45	50	55	62	68



Corporate Office

Balkrishna Industries Ltd.

BKT HOUSE, C/15, Trade World, Kamala Mills Compound, Senapati Bapat Marg, Lower Parel, Mumbai - 400013, India
Tel: (+91) 22-6666 3800 - Fax: (+91) 22-6666 3898/99 - e-mail: info@bkt-tires.com - bkt-tires.com

BKT Europe srl

Viale Della Repubblica, 133
20831 Seregno (MB), Italy
Tel: (+39) 0362 33 03 28
(+39) 0362 32 51 07
Fax: (+39) 0362 23 24 72

BKT USA Inc.

202 Montrose West Ave. Suite 240
Copley, Ohio 44321
Office: (+1) 330 836 1090
Fax: (+1) 330 836 1091

BKT Tires (CANADA) Inc.

55 York Street, Suite 401
Toronto, Ontario M5J 1R7, Canada
Tel: AG/IND (+1) 514 792 9220
OTR (+1) 780 888 5667
Fax: (+1) 416 229 1711



bkt-tires.com