

BKT

GROWING TOGETHER

LAWN & GARDEN

AGRICULTURAL TIRES





A G R I C U L T U R A L T I R E S

Taking care of a garden means to do some gardening without damaging it. It is hence essential that tires are gentle to the terrain without compromising the growth of grass and without leaving an unaesthetic impact. For this reason, agility, power and precision are needed so that small tractors and mowers can do their best on the spot. It is here, where BKT tires come into play – perfect for all Lawn & Garden applications: An extended tire life-cycle, excellent handling plus extraordinary puncture resistance in addition to a “gentle” approach on the terrain are their distinguishing features. Find out which BKT tire best suits your needs.



Radial

Radial tires have steel cords that are arranged running radially from bead to bead around the tire. Sidewall and tread have independent functional features providing more flexibility, great performance, durability, and fuel economy.















Bias

Bias tires have cord plies that are arranged running diagonally from bead to bead across the tire. Layers overlap forming a crisscross pattern. This design features extraordinary sidewall resistance and puncture resistance.

LAWN & GARDEN



TECHNOLOGIES AND PERFORMANCE



LAWN & GARDEN TIRES



TR 360



[p. 6]



LG SMOOTH



[p. 7]



LG 306



[p. 8]



LG 307



[p. 13]



LG 408



[p. 14]



LG RIB



[p. 15]



LG RIB PLUS



[p. 16]



AGRIMAX TURF RT 333



[p. 17]



TRAC MASTER



[p. 19]





TR 313



[p. 20]



TR 315



[p. 21]



AT 316



[p. 23]



AT 523



[p. 24]



TR 317



[p. 25]



TR 318



[p. 26]



TR 319



[p. 27]



GF 304



[p. 28]



GF 305 CLASSIC



[p. 29]





Bias



A8



115

Performance



Durability



TR 360

TR 360 is suitable for implement machinery in on-and-off-the-road transport as well as lawn and garden applications. The particular tread design along with the casing structure ensures a long tire life-cycle.

	Tire size	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS
		Rec.	Alt.								
Ø 8"	18 X 7 - 8	5.5	-	180	460	202	1334	STD	6	TL	-
Ø 15"	240/70 - 15 (28 X 9.00 - 15)	7.00 I	6½ K	235	740	-	-	STD	8	TL	115A8

STD: Standard





LG SMOOTH

LG SMOOTH is a lawn and garden tire suitable for mowers. While the tire is gentle on the ground, the enhanced design ensures increased durability and eases handling. LG SMOOTH is available in an "aramid-belted" version for users who need strengthened puncture resistance.

	Tire size	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS
		Rec.	Alt.								
Ø 8"	16 X 6.50 - 8	5.375 I-55; I-70;I-90	-	160	400	-	-	AB	10	TL	-
Ø 10"	18 X 10.50 - 10	8.5 I-55; I-70;I-90	8½ JA	254	460	207	1334	STD	2	TL	-
	20 X 10.00 - 10	8.00 I-55	7.00 I-55; I-70;I-90	245	500	223	1450	STD	2	TL	-
	20 X 10.00 - 10	8.00 I-55	7.00 I-55; I-70;I-90	245	500	223	1450	STD	4	TL	-
	20 X 10.00 - 10	8.00 I-55	7.00 I-55; I-70;I-90	245	500	223	1450	AB	6	TL	-
	20 X 10.00 - 10	8.00 I-55	7.00 I-55; I-70;I-90	245	500	223	1450	STD	6	TL	-

AB: Aramid Belted - STD: Standard



Bias

Technologies



Aramid Belted

Performance



Field Protection



High Puncture Resistance



Bias



155



LG 306

LG 306 is a lawn and garden tire suitable for mowers. In some sizes, LG 306 is also fit for small tractors. The specific tread pattern makes the tire gentle on the ground, easing handling at the same time. LG 306 is available in an "aramid-belted" version for users who need strengthened puncture resistance.

Technologies



Aramid Belted

Performance



Comfort



Field Protection



High Puncture Resistance

	Tire size	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS	
		Rec.	Alt.								DW	FR
Ø 5"	11 X 4.00 - 5	3.00 A	-	104	272	120	789	STD	4	TL	-	-
	Ø 6"	13 X 5.00 - 6	3.50 A	-	127	325	144	943	STD	6	TL	-
Ø 6"	13 X 5.00 - 6	3.50 A	-	127	325	144	943	STD	4	TL	-	-
	15 X 6.00 - 6	4.50 A	-	152	365	159	1059	STD	4	TL	-	-
	15 X 6.00 - 6	4.50 A	-	152	365	159	1059	STD	6	TL	-	-
Ø 8"	16 X 6.50 - 8	5.375 I - 55 ; I - 70 ; I - 90	-	170	408	182	1183	AB	6	TL	-	-
	16 X 6.50 - 8	5.375 I - 55 ; I - 70 ; I - 90	-	170	408	182	1183	STD	8	TL	-	-
	16 X 6.50 - 8	5.375 I - 55 ; I - 70 ; I - 90	-	170	408	182	1183	STD	6	TL	-	-
	16 X 6.50 - 8	5.375 I - 55 ; I - 70 ; I - 90	-	170	408	182	1183	STD	4	TL	-	-
	16 X 7.50 - 8	5.375 I - 55 ; I - 70 ; I - 90	-	178	400	-	-	AB	4	TL	-	-
	18 X 8.50 - 8	7.00 I - 55 ; I - 70 ; I - 90	-	215	450	204	1346	AB	6	TL	-	-
	18 X 8.50 - 8	7.00 I - 55 ; I - 70 ; I - 90	-	215	450	204	1346	STD	4	TL	-	-
	18 X 8.50 - 8	7.00 I - 55 ; I - 70 ; I - 90	-	215	450	204	1346	STD	6	TL	-	-
18 X 9.50 - 8	7.00 I - 55 ; I - 70 ; I - 90	-	230	470	206	1363	AB	6	TL	-	-	

STD: Standard - AB: Aramid Belted



	Tire size	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS	
		Rec.	Alt.								DW	FR
												
Ø 8"	18 X 9.50 - 8	7.00 I - 55 ; I - 70 ; I - 90	-	230	470	206	1363	STD	6	TL	-	-
	18 X 9.50 - 8	7.00 I - 55 ; I - 70 ; I - 90	-	230	470	206	1363	STD	4	TL	-	-
	20 X 10.00 - 8	8.00 I - 55	7.00 I - 55 ; I - 70 ; I - 90	254	508	221	1473	AB	6	TL	-	-
	20 X 10.00 - 8	8.00 I - 55	7.00 I - 55 ; I - 70 ; I - 90	254	508	221	1473	STD	4	TL	-	-
	20 X 10.00 - 8	8.00 I - 55	7.00 I - 55 ; I - 70 ; I - 90	254	508	221	1473	STD	6	TL	-	-
Ø 10"	18 X 8.50 - 10	7.00 I - 55 ; I - 70 ; I - 90	-	210	460	206	1370	STD	4	TL	-	-
	20 X 8.00 - 10	6.00 I - 55 ; I - 70 ; I - 90	6 JA	205	500	223	1450	STD	4	TL	-	-
	20 X 8.00 - 10	6.00 I - 55 ; I - 70 ; I - 90	6 JA	205	500	223	1450	STD	6	TL	-	-
	20 X 10.00 - 10	8.00 I - 55	7.00 I - 55	250	508	226	1473	AB	6	TL	-	-
	20 X 10.00 - 10	8.00 I - 55	7.00 I - 55	250	508	226	1473	STD	6	TL	-	-
	20 X 10.00 - 10	8.00 I - 55	7.00 I - 55	250	508	226	1473	STD	4	TL	-	-
Ø 12"	23 X 8.50 - 12	7.00 I - 55 ; I - 70 ; I - 90	7 JA	210	575	258	1709	AB	6	TL	-	-
	23 X 8.50 - 12	7.00 I - 55 ; I - 70 ; I - 90	7 JA	210	575	261	1717	STD	12	TL	-	-
	23 X 8.50 - 12	7.00 I - 55 ; I - 70 ; I - 90	7 JA	210	575	258	1709	STD	4	TL	-	-

STD: Standard - AB: Aramid Belted





Bias



155



LG 306

LG 306 is a lawn and garden tire suitable for mowers. In some sizes, LG 306 is also fit for small tractors. The specific tread pattern makes the tire gentle on the ground, easing handling at the same time. LG 306 is available in an "aramid-belted" version for users who need strengthened puncture resistance.

Technologies



Aramid Belted

Performance



Comfort



Field Protection





High Puncture Resistance

	Tire size	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS	
		Rec.	Alt.								DW	FR
Ø 12"	23 X 8.50 - 12	7.00 I - 55 ; I - 70 ; I - 90	7 JA	210	575	258	1709	STD	6	TL	-	-
	23 X 8.50 - 12	7.00 I - 55 ; I - 70 ; I - 90	7 JA	210	575	258	1709	STD	8	TL	-	-
	23 X 10.50 - 12	8.5 I - 55	7.00 I - 55 ; I - 70 ; I - 90	260	585	262	1697	AB	6	TL	-	-
	23 X 10.50 - 12	8.5 I - 55	7.00 I - 55 ; I - 70 ; I - 90	260	585	262	1697	STD	6	TL	-	-
	23 X 10.50 - 12	8.5 I - 55	7.00 I - 55 ; I - 70 ; I - 90	260	585	262	1697	STD	4	TL	-	-
	23 X 10.50 - 12	8.5 I - 55	7.00 I - 55 ; I - 70 ; I - 90	260	585	262	1697	STD	8	TL	-	-
	23 X 10.50 - 12	8.5 I - 55	7.00 I - 55 ; I - 70 ; I - 90	260	585	262	1697	STD	12	TL	-	-
	24 X 12.00 - 12	9.5 AT	9.0 AT ; 8.5 AT ; 8.0 AT	298	610	276	1774	STD	4	TL	-	-
	26 X 12.00 - 12	10.50 I - 55 ; I - 70 ; I - 90	10½ JA ; 8½ JA	310	640	283	1856	AB	6	TL	-	-
	26 X 12.00 - 12	10.50 I - 55 ; I - 70 ; I - 90	10½ JA ; 8½ JA	310	640	283	1856	AB	8	TL	-	-
	26 X 12.00 - 12	10.50 I - 55 ; I - 70 ; I - 90	10½ JA ; 8½ JA	310	640	283	1856	STD	8	TL	-	-
	26 X 12.00 - 12	10.50 I - 55 ; I - 70 ; I - 90	10½ JA ; 8½ JA	310	640	283	1856	STD	4	TL	-	-
	26 X 12.00 - 12	10.50 I - 55 ; I - 70 ; I - 90	10½ JA ; 8½ JA	310	640	283	1856	STD	12	TL	-	-
	26 X 12.00 - 12	10.50 I - 55 ; I - 70 ; I - 90	10½ JA ; 8½ JA	310	640	294	1945	STD	14	TL	-	-
	260/55 - 12 (23 X 10.50 - 12)	8.5 I - 55	7.00 I - 55 ; I - 70 ; I - 90	260	585	262	1697	IMP	14	TL	110A8	122A8

STD: Standard - IMP: Implement - AB: Aramid Belted



	Tire size	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS	
		Rec.	Alt.								DW	FR
												
Ø 14"	24 X 8.50 - 14	7 JA	-	210	610	280	1769	STD	4	TL	-	-
	25 X 8.50 - 14	7.00 I - 55 ; I - 70 ; I - 90	-	220	638	294	1915	STD	6	TL	-	-
	25 X 8.50 - 14	7.00 I - 55 ; I - 70 ; I - 90	-	220	638	294	1915	STD	8	TL	-	-
Ø 15"	27 X 8.50 - 15	7.00 JA	-	216	685	329	2076	STD	4	TL	-	-
	27 X 10.50 - 15	8.00 LB	-	272	705	318	2042	STD	4	TL	-	-
	27 X 10.50 - 15	8.00 LB	-	272	705	337	2055	STD	12	TL	-	-
	29 X 12.50 - 15	10 LB	-	318	740	349	2230	AB	10	TL	113 B	
	29 X 12.50 - 15	10 LB	-	325	740	353	2177	STD	10	TL	113 B	
	31 X 15.5 - 15	13 LB	-	391	792	350	2313	AB	8	TL	-	-
	31 X 15.5 - 15	13 LB	-	391	792	350	2313	STD	4	TL	-	-
	31 X 15.5 - 15	13 LB	-	391	792	350	2313	STD	8	TL	-	-
Ø 16"	13.6 - 16	W 12	W 11	388	975	442	2860	STD	4	TL	-	-
Ø 16.5"	10 - 16.5	8.25	-	264	775	341	2322	STD	8	TL	124A2	

STD: Standard - AB: Aramid Belted





Bias



155



LG 306

LG 306 is a lawn and garden tire suitable for mowers. In some sizes, LG 306 is also fit for small tractors. The specific tread pattern makes the tire gentle on the ground, easing handling at the same time. LG 306 is available in an "aramid-belted" version for users who need strengthened puncture resistance.

Technologies



Aramid Belted

Performance



Comfort



Field Protection



High Puncture Resistance

	Tire size	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS	
		Rec.	Alt.								DW	FR
Ø 16.5"	12 - 16.5	10.15	-	306	833	363	2476	STD	12	TL	-	-
	33 X 15.50 - 16.5	12.00	-	396	840	385	2538	STD	10	TL	-	-
Ø 17.5"	14 - 17.5	10.50	-	355	921	371	2632	STD	6	TL	155 A2	
Ø 20"	38 X 14.00 - 20	W 11	W 11 H	375	980	447	2912	STD	4	TL	-	-
	41 X 14.00 - 20	W 11	W 11 H	370	1067	449	3098	STD	4	TL	120 B	
	44 X 18.00 - 20	W 14 L	W 14 LH	490	1165	518	3509	STD	4	TL	-	-
Ø 24"	17.5 L - 24	W 15 L	DW 14 L	455	1241	556	3708	STD	8	TL	139 A8	

STD: Standard





LG 307

LG 307 is a lawn and garden tire suitable for mowers. The specific tread pattern makes the tire gentle on the ground to prevent turf damages, easing handling at the same time.

	Tire size	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS
		Rec.	Alt.								
∅ 8"	20 X 10.00 - 8	8.00 I - 55 ; I - 70 ; I - 90	7.00 I - 55 ; I - 70 ; I - 90	255	495	215	1435	STD	4	TL	-
	20 X 10.00 - 8	8.00 I - 55 ; I - 70 ; I - 90	7.00 I - 55 ; I - 70 ; I - 90	255	495	215	1435	STD	6	TL	-
∅ 10"	20 X 12.00 - 10	8.5 I - 55 ; I - 70 ; I - 90	-	285	500	221	1435	STD	4	TL	-

STD: Standard



Bias

Performance



Comfort



Field Protection





Bias



LG 408

LG 408 is a lawn and garden tire suitable for mowers and small tractors. The specific tread pattern makes the tire gentle on the ground to prevent turf damages making handling easier at the same time. LG 408 is available in an "aramid-belted" version for users who need strengthened puncture resistance.

Technologies



Aramid Belted

Performance



Comfort



Field Protection



High Puncture Resistance

	Tire size	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS
		Rec.	Alt.								
Ø 12"	24 X 13.00 - 12	10.5 I - 55 ; I - 70 ; I - 90	-	325	610	269	1755	STD	4	TL	-
	24 X 13.00 - 12	10.5 I - 55 ; I - 70 ; I - 90	-	325	610	269	1755	AB	6	TL	-
	24 X 13.00 - 12	10.5 I - 55 ; I - 70 ; I - 90	-	325	610	269	1755	STD	6	TL	-
	26.5 X 14.00 - 12	12.00 I	-	380	665	293	1929	STD	4	TL	-
	26.5 X 14.00 - 12	12.00 I	-	380	665	293	1929	AB	6	TL	-
	26.5 X 14.00 - 12	12.00 I	-	380	665	293	1929	STD	6	TL	-
	26.5 X 14.00 - 12	12.00 I	-	380	665	293	1929	STD	10	TL	-

STD: Standard - AB: Aramid Belted





LG RIB

LG RIB is a lawn and garden tire suitable for mowers and small tractors. Its tread pattern has been designed for making the tire gentle on the ground to prevent turf damages making handling easier at the same time. LG RIB is available in an "aramid-belted" version for users who need strengthened puncture resistance.



Bias

	Tire size	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS
		Rec.	Alt.								
Ø 5"	11 X 4.00 - 5	3.00 A	-	104	272	-	-	STD	4	TL	39 A6
Ø 6"	13 X 5.00 - 6	3.50 A	-	127	325	144	943	AB	6	TL	-
	13 X 5.00 - 6	3.50 A	-	127	325	144	943	STD	4	TL	-
	15 X 6.00 - 6	4.50 A	-	152	365	159	1059	AB	6	TL	-
	15 X 6.00 - 6	4.50 A	-	152	365	159	1059	STD	4	TL	-
	15 X 6.00 - 6	4.50 A	-	152	365	159	1059	STD	6	TL	-
Ø 8"	16 X 6.50 - 8	5.375 I - 55 ; I - 70 ; I - 90	-	170	408	182	1183	AB	6	TL	-
	16 X 6.50 - 8	5.375 I - 55 ; I - 70 ; I - 90	-	170	408	182	1183	AB	10	TL	-
	16 X 6.50 - 8	5.375 I - 55 ; I - 70 ; I - 90	-	170	408	182	1183	STD	4	TT	-
	16 X 6.50 - 8	5.375 I - 55 ; I - 70 ; I - 90	-	170	408	182	1183	STD	4	TL	-
	16 X 6.50 - 8	5.375 I - 55 ; I - 70 ; I - 90	-	170	408	182	1183	STD	6	TL	-
	16 X 6.50 - 8	5.375 I - 55 ; I - 70 ; I - 90	-	170	408	182	1183	STD	8	TL	-
	16 X 6.50 - 8	5.375 I - 55 ; I - 70 ; I - 90	-	170	408	182	1183	STD	10	TL	-
Ø 10"	20 X 10.00 - 10	8.00 I - 55 ; I - 70 ; I - 90	7.00 I - 55 ; I - 70 ; I - 90	236	498	222	1444	STD	4	TL	-

AB: Aramid Belted - STD: Standard

Technologies



Aramid Belted

Performance



Comfort



Field Protection



High Puncture Resistance



Steering Control



Bias



LG RIB PLUS

LG RIB PLUS is a lawn and garden tire suitable for applications with mowers, small tractors and tedders. Its tread pattern has been specially designed for making the tire gentle on the ground preventing turf damages, while at the same time making the handling easier. The round profile makes LG RIB PLUS able to slide and drag easily while turning in the field.

Performance



Handling and Comfort

	Tire size	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS
		Rec.	Alt.								
Ø 8"	16 X 6.50 - 8	5.375 I - 55 ; I - 70 ; I - 90	-	170	408	-	-	STD	10	TL	-

STD: Standard







AGRIMAX TURF RT 333

RADIAL TRACTOR TIRES

AGRIMAX TURF RT 333 (R-3+) is a radial tire designed for small tractors in gardening, vineyards and orchards applications. Its rounded shoulder design provides low soil compaction and makes it extremely delicate on the ground. Its unique extra-deep tread (R-3+) and the special design with directional blocks stand for excellent traction both in the field and on the road, and an extended tire life cycle. AGRIMAX TURF RT 333 (R-3+) ensures great self-cleaning properties and thanks to its low rolling resistance, allows for significant fuel saving.

	Tire size	LI/SS	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	SRI (index)	Version
			Rec.	Alt.						
										
Ø 12"	220/55 R 12	82 A8/B	7	-	221	550	249	1645	260	STD
	240/60 R 12	89 A8/B	7	-	242	592	269	1777	-	STD
Ø 14"	215/65 R 14	90 A8/ 90 B	W 7	W 6	220	630	290	1906	310	STD
Ø 16"	200/65 R 16	94 A8/B	W 6	-	202	666	309	2000	320	STD
	200/70 R 16	94 A8/B	W 6	-	200	686	317	2054	330	STD
	240/70 R 16	104 A8/B	W 8	W 8 L; W 9	244	742	340	2213	350	STD
	260/70 R 16	109 A8/ 109 B	W 8	W 8 L; W 9	258	770	348	2287	370	STD
	280/70 R 16	112 A8/ 112 B	W 9	W 8; W 10	289	800	359	2371	380	STD
Ø 18"	280/70 R 18	114 A8/ 114 B	W 9	W 8; W 10	289	840	390	2550	400	STD
	320/65 R 18	109 A8/ 109 B	W 10	W 9; W 11	319	873	394	2591	425	STD
Ø 20"	300/70 R 20	110 A8/ 110 B	W 9	W 10	295	952	431	2826	450	STD
	320/70 R 20	113 A8/ 113 B	W 10	W 9; W 11	319	982	441	2916	475	STD
	380/70 R 20	122 A8/ 122 B	W 12	W 11; W 13	380	1082	486	3213	525	STD

STD: Standard



Radial



Technologies



Extra Deep Tread



Block Pattern

Performance



Durability



Reduced Soil Compaction



Traction



Self-Cleaning



Low Rolling Resistance





Radial

R-1W



B



AGRIMAX TURF RT 333

RADIAL TRACTOR TIRES



AGRIMAX TURF RT 333 (R-3+) is a radial tire designed for small tractors in gardening, vineyards and orchards applications. Its rounded shoulder design provides low soil compaction and makes it extremely delicate on the ground. Its unique extra-deep tread (R-3+) and the special design with directional blocks stand for excellent traction both in the field and on the road, and an extended tire life cycle. AGRIMAX TURF RT 333 (R-3+) ensures great self-cleaning properties and thanks to its low rolling resistance, allows for significant fuel saving.

Technologies



Extra Deep Tread



Block Pattern

Performance



Durability



Reduced Soil Compaction



Traction



Self-Cleaning



Low Rolling Resistance

	Tire size	LI/SS	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	SRI (index)	Version
			Rec.	Alt.						
Ø 24"	360/70 R 24	122 A8/ 122 B	W 11	W 10; W 12	357	1152	518	3409	550	STD
	380/70 R 24	125 A8/ 125 B	W 12	W 11; W 13	380	1190	534	3538	550	STD
	420/70 R 24	130 A8/ 130 B	W 13	W 12; W 14 L	418	1248	557	3728	600	STD
	420/85 R 24	137 A8/ 137 B	W 15 L	DW 15 L; DW 14 L	435	1324	594	3957	625	STD
Ø 28"	340/85 R 28	127 A8/ 127 B	W 12	W 11; DW 11; DW 12	370	1289	585	3874	625	STD
	480/70 R 28	140 A8/ 140 B	W 15 L	W 14 L; W 16 L	479	1421	631	4228	675	STD
Ø 30"	480/70 R 30	141 A8/ 141 B	W 15 L	W 14 L; W 16 L	479	1478	660	4396	700	STD
Ø 34"	480/70 R 34	149 A8/ 149 B	W 15 L	W 14 L; W 16 L	490	1580	723	4785	750	STD

STD: Standard





TRAC MASTER

TRAC MASTER is a soil tillage and lawn and garden tire, suitable for small tractors and implement machinery. Its tread design provides excellent field protection along with great traction in the fields and optimum self-cleaning properties.

	Tire size	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS
		Rec.	Alt.								
Ø 12"	300/60 - 12	10.5	9.5	306	645	285	1885	STD	8	TL	-
Ø 15"	31 X 15.50 - 15	13 LB	-	405	792	370	2372	STD	6	TL	-
	31 X 15.50 - 15	13 LB	-	405	792	370	2372	STD	8	TL	-
	33 X 15.50 - 15	13 LB	-	404	865	378	2526	STD	6	TL	-
	33 X 15.50 - 15	13 LB	-	404	865	378	2526	STD	8	TL	-
	380/50 - 15	13 LB	-	380	780	364	2229	STD	8	TL	116 B

STD: Standard



Bias

Performance



Field Protection



Self-Cleaning



Traction





Bias



TR 313

TR 313 is a lawn and garden tire suitable for municipality and soil tillage operations with implement machinery, trenchers and orchard harvesters. The large contact area provides excellent grip. The TR 313 tire has been engineered to ensure a high level of stability also in critical operating conditions along with great self-cleaning properties.

Performance



Self-Cleaning



Stability



Traction

	Tire size	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS
		Rec.	Alt.								
Ø 15"	31 X 15.50 - 15	13 LB	-	370	780	342	2233	STD	8	TL	-

STD: Standard





TR 315

TR 315 is suitable for lawn and garden, soil tillage and municipalities operations. It is ideal with implement machinery, trenchers and orchard harvesters. The TR 315 tire has a large contact area which provides excellent grip, great self-cleaning properties and outstanding stability in any condition.



Bias

	Tire size	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS
		Rec.	Alt.								
Ø 8"	16 X 6.50 - 8	5.375 I - 55 ; I - 70 ; I - 90	-	155	408	182	1183	STD	4	TL	-
	16 X 6.50 - 8	5.375 I - 55 ; I - 70 ; I - 90	-	155	408	182	1183	STD	6	TL	-
	19 X 7.00 - 8	5.50 A	-	178	475	212	1458	STD	8	TL	90A3
Ø 12"	23 X 8.50 - 12	7 JA ; 7.00 I - 55 ; I - 70 ; I - 90	-	205	575	258	1668	STD	4	TL	-
	23 X 8.50 - 12	7 JA ; 7.00 I - 55 ; I - 70 ; I - 90	-	205	575	258	1668	STD	6	TL	-
	23 X 10.50 - 12	8½ JA	7 JA	255	600	272	1840	STD	4	TL	-
	23 X 10.50 - 12	8½ JA	7 JA	255	600	272	1840	STD	6	TL	-
	23 X 10.50 - 12	8½ JA	7 JA	255	600	272	1840	STD	8	TL	-
	23 X 10.50 - 12	8½ JA	7 JA	255	600	272	1840	STD	10	TL	-
	23 X 10.50 - 12	8½ JA	7 JA	255	600	272	1840	STD	12	TL	-
	26 X 12.00 - 12	10½ JA	8½ JA ; 9½ JA	308	655	289	1905	STD	4	TL	-
	26 X 12.00 - 12	10½ JA	8½ JA ; 9½ JA	308	655	289	1905	STD	8	TL	-
	26 X 12.00 - 12	10½ JA	8½ JA ; 9½ JA	308	655	289	1905	SPL	10	TL	-
26 X 12.00 - 12	10½ JA	8½ JA ; 9½ JA	308	655	289	1905	STD	10	TL	-	

STD: Standard - SPL: Special

Performance



Self-Cleaning



Stability



Traction





Bias



TR 315

TR 315 is suitable for lawn and garden, soil tillage and municipalities operations. It is ideal with implement machinery, trenchers and orchard harvesters. The TR 315 tire has a large contact area which provides excellent grip, great self-cleaning properties and outstanding stability in any condition.

Performance



Self-Cleaning



Stability



Traction

	Tire size	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS
		Rec.	Alt.								
Ø 12"	26 X 12.00 - 12	10½ JA	8½ JA ; 9½ JA	308	655	289	1905	STD	12	TL	-
Ø 15"	31 X 15.50 - 15	13 LB	-	390	800	354	2320	STD	8	TL	-
	31 X 15.50 - 15	13 LB	-	390	800	354	2320	STD	10	TL	-
	31 X 15.50 - 15	13 LB	-	390	800	354	2320	STD	12	TL	-






STD: Standard





AT 316

AT 316 is suitable for compact utility tractors in municipality and maintenance applications. The special tread design provides excellent traction without compromising field protection - an essential feature for this kind of application. AT 316 is also available as "aramid-belted" version to provide increased puncture resistance.

	Tire size	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS
		Rec.	Alt.								
											
Ø 12"	24 X 12.00 - 12	10.50 I - 55 ; I - 70 ; I - 90	-	315	610	271	1769	STD	4	TL	-
	24 X 12.00 - 12	10.50 I - 55 ; I - 70 ; I - 90	-	315	610	271	1769	AB	6	TL	-

STD: Standard - AB: Aramid Belted



Bias

Performance



Self-Cleaning



Traction





Bias



AT 523

BKT's AT 523 is a multifunctional tire designed to provide reliable performance in agricultural, turf, and industrial applications. Its tread design ensures excellent traction and self-cleaning capabilities, which are key features for tackling a variety of surfaces: from rammed earth and turf to hard surfaces typical of industrial settings. The flatter profile and enlarged center block, combined with the R-1 and R-4 type design, provide greater stability on the road, while the rounded shoulders protect the turf, preserving its integrity even under intensive operating conditions. The strong carcass and a cut-resistant tread compound make AT 523 particularly durable. This combination of ruggedness, versatility and ease of use makes AT 523 the ideal solution for those who need a single tire that can cope with a variety of situations: from soil preparation and lawn operations to industrial use.

Technologies



Strong Casing



Rounded Shoulder Technology

Performance



Traction



Self-Cleaning



Hard Surfaces



Ideal for grassland



Stability

	Tire size	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS
		Rec.	Alt.								
Ø 12"	26 X 12.00 - 12	10.50 I - 55 ; I - 70 ; I - 90	10½ JA ; 8½ JA	300	650	300	1898	STD	6	TL	107 A8

STD: Standard





TR 317

TR 317 is suitable for municipality and soil tillage operations with implement machinery, trenchers and orchard harvesters. The TR 317 tire has a large contact area which provides excellent grip and outstanding stability in any condition along with great self-cleaning properties.

	Tire size	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS
		Rec.	Alt.								
Ø 8"	18 X 8.50 - 8	7.00 I - 55; I - 70; I - 90	-	215	450	198	1305	HD	6	TL	-
	18 X 8.50 - 8	7.00 I - 55; I - 70; I - 90	-	215	450	198	1305	STD	4	TL	-

HD: Heavy Duty - STD: Standard



Bias

Performance



Self-Cleaning



Stability



Traction





Bias



TR 318

TR 318 is specifically designed for sprayers and implement machinery. Its dual-angled lugs provide excellent traction and outstanding driving comfort. TR 318 also features extraordinary self-cleaning properties.

Performance



Self-Cleaning



Stability



Traction

	Tire size	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS
		Rec.	Alt.								
Ø 12"	23 X 9.00 - 12	7.0	-	220	585	-	-	STD	6	TT	93A3
	23 X 9.00 - 12	7.0	-	220	585	-	-	STD	6	TL	93A3
	26 X 10.00 - 12	8.5	-	265	675	-	-	STD	8	TT	107A3

STD: Standard





TR 319

TR 319 is a tire for implement machinery, orchard harvesters and trenchers in lawn and garden, municipality and soil tillage applications. Featuring a large contact area providing best traction, TR 319 is very suitable for applications on wet surfaces, where stability and self-cleaning properties are required.

	Tire size	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS
		Rec.	Alt.								
Ø 12"	26 X 12.00 - 12	10.50 AT	8.0 AT ; 8.5 AT ; 9.0 AT	318	640	290	1908	STD	8	TL	116A3
Ø 15"	29 X 12.50 - 15	10 LB	-	312	755	360	2264	STD	6	TL	98 B
	29 X 12.50 - 15	10 LB	-	312	755	360	2264	STD	8	TL	106 B

STD: Standard



Bias



B



116

Performance



Self-Cleaning



Stability



Traction





Bias



GF 304

GF 304 is suitable for golf applications with golf carts. GF 304 ensures best comfort and turf protection. GF 304 is also available as "aramid-belted" version to provide increased puncture resistance.

Performance



Field Protection

	Tire size	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS
		Rec.	Alt.								
∅ 8"	18 X 8.50 - 8	7.00 1-55 ; 1-70 ; 1-90	-	216	460	202	1334	AB	4	TL	-
	18 X 8.50 - 8	7.00 1-55 ; 1-70 ; 1-90	-	216	460	202	1334	STD	4	TL	-
	18 X 8.50 - 8	7.00 1-55 ; 1-70 ; 1-90	-	216	460	202	1334	STD	6	TL	-

AB: Aramid Belted - STD: Standard







GF 305 CLASSIC

GF 305 CLASSIC is a special tire mainly designed for golf carts. This tire is naturally gentle on the ground and protects the field from damages. GF 305 CLASSIC is a really comfortable tire which makes riding a pleasure.



Bias

	Tire size	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS
		Rec.	Alt.								
											
Ø 10"	205/50 - 10	7.00 I - 55	6.00 I - 55 ; 1-70 ; 1-90	215	470	211	1363	STD	4	TL	-
	205/50 - 10	7.00 I - 55	6.00 I - 55 ; 1-70 ; 1-90	215	470	211	1363	STD	6	TL	-

STD: Standard

Performance



Field Protection





Load index

The load index is a code that defines a tire's maximum weight capacity at the speed given by its speed index provided that the usage conditions recommended by the Manufacturer are fully complied with.

Corresponding values of load index (LI) and load capacity per wheel (kg / lbs)

LI	lbs	kg	LI	lbs	kg	LI	lbs	kg	LI	lbs	kg
50	420	190	85	1135	515	120	3085	1400	155	8540	3875
51	430	195	86	1170	530	121	3195	1450	156	8820	4000
52	440	200	87	1200	545	122	3305	1500	157	9095	4125
53	455	206	88	1235	560	123	3415	1550	158	9370	4250
54	465	212	89	1280	580	124	3525	1600	159	9645	4375
55	480	218	90	1325	600	125	3635	1650	160	9920	4500
56	495	224	91	1355	615	126	3750	1700	161	10195	4625
57	505	230	92	1390	630	127	3860	1750	162	10470	4750
58	520	236	93	1435	650	128	3970	1800	163	10745	4875
59	535	243	94	1475	670	129	4080	1850	164	11025	5000
60	550	250	95	1520	690	130	4190	1900	165	11355	5150
61	565	257	96	1565	710	131	4300	1950	166	11685	5300
62	585	265	97	1610	730	132	4410	2000	167	12015	5450
63	600	272	98	1655	750	133	4540	2060	168	12345	5600
64	615	280	99	1710	775	134	4675	2120	169	12785	5800
65	640	290	100	1765	800	135	4805	2180	170	13225	6000
66	660	300	101	1820	825	136	4940	2240	171	13560	6150
67	675	307	102	1875	850	137	5070	2300	172	13890	6300
68	695	315	103	1930	875	138	5205	2360	173	14330	6500
69	715	325	104	1985	900	139	5355	2430	174	14770	6700
70	740	335	105	2040	925	140	5510	2500	175	15210	6900
71	760	345	106	2095	950	141	5675	2575	176	15650	7100
72	785	355	107	2150	975	142	5840	2650	177	16095	7300
73	805	365	108	2205	1000	143	6005	2725	178	16535	7500
74	825	375	109	2270	1030	144	6175	2800	179	17085	7750
75	855	387	110	2335	1060	145	6395	2900	180	17635	8000
76	880	400	111	2405	1090	146	6615	3000	181	18185	8250
77	910	412	112	2470	1120	147	6780	3075	182	18740	8500
78	935	425	113	2535	1150	148	6945	3150	183	19290	8750
79	965	437	114	2600	1180	149	7165	3250	184	19840	9000
80	990	450	115	2680	1215	150	7385	3350	185	20390	9250
81	1020	462	116	2755	1250	151	7605	3450	186	20945	9500
82	1045	475	117	2835	1285	152	7825	3550	187	21495	9750
83	1075	487	118	2910	1320	153	8045	3650	188	22045	10000
84	1100	500	119	3000	1360	154	8265	3750	189	22705	10300

LI	lbs	kg	LI	lbs	kg	LI	lbs	kg
190	23370	10600	200	30865	14000	210	41885	19000
191	24030	10900	201	31965	14500	211	42990	19500
192	24690	11200	202	33070	15000	212	44090	20000
193	25350	11500	203	34170	15500	213	45415	20600
194	26015	11800	204	35270	16000	214	46735	21200
195	26785	12150	205	36375	16500	215	48060	21800
196	27555	12500	206	37475	17000	216	49380	22400
197	28330	12850	207	38580	17500	217	50705	23000
198	29100	13200	208	39680	18000	218	52025	23600
199	29980	13600	209	40785	18500	219	53570	24300

Speed index

The speed index is a value that indicates the maximum admitted speed at which the tire can carry the weight corresponding to its load index provided that the usage conditions recommended by the Manufacturer are fully complied with.

Speed index	A2	A4	A6	A8	B	C	D	E	F	G	J	K
km/h	10	20	30	40	50	60	65	70	80	90	100	110
mph	5	10	20	25	30	35	40	45	50	55	62	68



Corporate Office

Balkrishna Industries Ltd.

BKT HOUSE, C/15, Trade World, Kamala Mills Compound, Senapati Bapat Marg, Lower Parel, Mumbai - 400013, India
Tel: (+91) 22-6666 3800 - Fax: (+91) 22-6666 3898/99 - e-mail: info@bkt-tires.com - bkt-tires.com

BKT Europe srl

Viale Della Repubblica, 133
20831 Seregno (MB), Italy
Tel: (+39) 0362 33 03 28
(+39) 0362 32 51 07
Fax: (+39) 0362 23 24 72

BKT USA Inc.

202 Montrose West Ave. Suite 240
Copley, Ohio 44321
Office: (+1) 330 836 1090
Fax: (+1) 330 836 1091

BKT Tires (CANADA) Inc.

55 York Street, Suite 401
Toronto, Ontario M5J 1R7, Canada
Tel: AG/IND (+1) 514 792 9220
OTR (+1) 780 888 5667
Fax: (+1) 416 229 1711



bkt-tires.com