

BKT

GROWING TOGETHER

MULTIUSE

AGRO-INDUSTRIAL TIRES





AGRO-INDUSTRIAL TIRES

MU

Are you looking for a multi-use tire? BKT has the perfect product for your needs.

Designed for both agricultural and industrial applications, these tires are suitable for any type of terrain.

Their strength consists in compounds, which have been specifically developed to avoid cuts and wear, so that they feature long durability and high load capacity.

BKT multi-purpose tires are suitable for a variety of applications ranging from municipality operations to transport in agriculture. As a result, they are extremely versatile not least thanks to top self-cleaning properties enabling easy transfer from field to road.

These tires are the response to your needs.





MULTIUSE



Radial

Radial tires have steel cords that are arranged running radially from bead to bead around the tire. Sidewall and tread have independent functional features providing more flexibility, great performance, durability, and fuel economy.



Bias

Bias tires have cord plies that are arranged running diagonally from bead to bead across the tire. Layers overlap forming a crisscross pattern. This design features extraordinary sidewall resistance and puncture resistance.



GROWING TOGETHER

AGRO-INDUSTRIAL TIRES

MU

TECHNOLOGIES



All Steel



Aramid Belted



Block Pattern



Heavy Duty



High Speed



Larger Footprint



M+S



More Lugs



Reinforced Carcass



Reinforced Shoulder



Special Compound














Steel Belted



MULTIUSE

PERFORMANCE



MULTIUSE TIRES



MULTIMAX MP 513



[p. 8]



MULTIMAX MP 515



[p. 9]



MULTIMAX MP 519



[p. 10]



MULTIMAX MP 522



[p. 11]



MULTIMAX MP 527



[p. 12]



MULTIMAX MP 529



[p. 13]



MULTIMAX MP 540



[p. 14]



MULTIMAX MT 518



[p. 15]



MULTIMAX MP 538



[p. 16]



RT 747 AGRO INDUSTRIAL



[p. 17]



CON STAR



[p. 18]



AS 504



[p. 19]



AT 603



[p. 25]



AT 621



[p. 26]



MP 567



[p. 28]



MP 570



[p. 31]



MP 585



[p. 32]



MP 590



[p. 33]



MP 600



[p. 34]



TR 459



[p. 36]



TR 461



[p. 38]



TR 463



[p. 39]



Radial



MULTIMAX MP 513

RADIAL MPT TIRES

MULTIMAX MP 513 has been designed by BKT for multi-purpose vehicles in municipality/maintenance and transport applications, for both agricultural and industrial uses. It is perfect for universal vehicles and fertilizer trucks. Thanks to the strong steel-belted nylon casing, MULTIMAX MP 513 allows to carry heavy loads at high speeds providing a comfortable driving experience. It ensures a longer service life and traction along with outstanding self-cleaning properties.

Technologies



High Speed



Steel Belted

Performance



Handling and Comfort



Self-Cleaning



Traction



Durability

	Tire size	Type	STAR RATING	LI/SS	Version	S.W.	O.D.	SLR	RC	RIM	
						(mm)	(mm)	(mm)	(mm)	Rec.	Alt.
Ø 16"	285/80 R 16 MPT	TL	-	128 G	STD	304	866	394	2617	W 10	-
Ø 17"	425/55 R 17 MPT	TL	-	142 A8/B	STD	421	900	399	2705	13	13.00
	425/55 R 17 MPT	TL	-	134 G	STD	421	900	399	2695	13	13.00
Ø 18"	325/70 R 18 MPT	TL	-	132 G	STD	322	916	410	2771	W 10	-
	365/70 R 18 MPT	TL	-	133 G	STD	360	969	448	2954	11	11 SDC; 12; 12 SDC
Ø 20"	375/70 R 20 MPT	TL	-	136 G	STD	377	1034	472	3121	12	W 10; DW 10; 11; 11 SDC; W 11; DW 11; 12 SDC
	405/70 R 20 MPT	TL	-	136 G	STD	407	1076	493	3253	13	13 SDC; 12 SDC
	425/75 R 20 MPT	TL	-	148 G	STD	421	1146	521	3479	13	13 SDC; 11 SDC; 12 SDC; 11; 12
Ø 24"	495/70 R 24 MPT	TL	-	155 G	STD	499	1304	588	3974	W 16 L	DW 15 L; DW 16 L; W 15 L

STD: Standard







MULTIMAX MP 515

RADIAL MPT TIRES

MULTIMAX MP 515 is an agro-industrial radial tire designed for universal vehicles and fertilizer trucks. It is suitable for municipality and transport applications. The tire shows a unique tread design providing superior riding comfort on the road as well as excellent self-cleaning properties and great traction. The strong steel-belted nylon casing and the reinforced shoulder ensure extraordinary durability. MULTIMAX MP 515 is the perfect tire also at high speeds (90km/h).

	Tire size	LI/SS	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	SRI (index)	Version
			Rec.	Alt.						
										
Ø 20"	405/70 R 20 MPT	136 G	13	13 SDC ; 12 SDC ; 11 SDC ; 11	407	1076	493	3286	-	STD
	425/75 R 20 MPT	148 G	13	13 SDC ; 11 SDC ; 12 SDC ; 11 ; 12	421	1146	522	3491	-	STD
Ø 22.5"	445/65 R 22.5 MPT	160 G	13	14	444	1150	527	3532	-	STD

STD: Standard



Radial



160

Technologies



High Speed



Reinforced Shoulder



Steel Belted

Performance



Durability



Handling and Comfort



Self-Cleaning



Traction



Radial



MULTIMAX MP 519

RADIAL MPT TIRES

MULTIMAX MP 519 is a particularly suitable tire for light trucks in all transport applications. The steel-belted casing provides excellent stability at high-speed (90 km/h - 60 mph). Thanks to its low rolling resistance, the tire ensures reduced fuel consumption.

Technologies



High Speed

Performance



Fuel Economy



Stability

	Tire size	Type	PR	LI/SS	Version	S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	RIM	
										Rec.	Alt.
Ø 16"	7.50 R 16 LT	TL	6	109/ 107 G	STD	220	810	377	2449	6.00	5.50 F; 6 L; 7 L
	7.50 R 16 LT	TL	8	112/ 110 G	STD	220	810	377	2449	6.00	5.50 F; 6 L; 7 L

STD: Standard





MULTIMAX MP 522

RADIAL MPT TIRES

MULTIMAX MP 522 is the BKT multi-purpose tire developed for agro-industrial applications. It is suitable for all lifting and loading operations on vehicles such as telehandlers and compact loaders. Stability and traction are its strengths as well as outstanding puncture resistance. Thanks to its special compound, MULTIMAX MP 522 has an incredible cut and chip resistance.

	Tire size	LI/SS	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	SRI (index)	Version
			Rec.	Alt.						
Ø 18"	280/80 R 18 IND (10.5/80 R 18)	132 A8/B	W 9; 9; 9 SDC	W 8; W 10	282	907	421	2748	425	STD
	340/80 R 18 IND (12.5/80 R 18)	143 A8/B	11; 11 SDC; W 11	W 10; 12; 12 SDC	343	1006	458	3023	475	STD
Ø 20"	340/80 R 20 IND	144 A8/B	11	W 10; 11 SDC; W 11; 12; 12 SDC	343	1052	481	3212	500	STD
	380/75 R 20 IND (14.5 R 20)	148 A8/B	W 12	W 11; 11; 12	384	1074	483	3251	500	STD
	400/70 R 20 IND (16.0/70 R 20)	149 A8/B	13	12 SDC; 13 SDC; 14	404	1068	476	3199	525	STD
Ø 24"	400/70 R 24 IND	152 A8/B	13	DW 12; 13 SDC; DW 13; DW 13 L; DW 14 L	404	1170	533	3527	575	STD
	400/80 R 24 IND (16.0/80 R 24)	162 A8/B	DW 13	DW 12; DW 13 L; DW 14 L	404	1250	553	3778	600	STD
	440/80 R 24 IND	161 A8/B	DW 14 L	DW 13; DW 13 L; DW 15 L	441	1314	586	3958	625	STD
	460/70 R 24 IND (17.5 L R 24)	159 A8/B	DW 15 L	DW 14 L; DW 16 L	465	1250	568	3766	600	STD
	500/70 R 24 IND (19.5 L R 24)	164 A8/B	DW 16 L	DW 15 L; DW 18 L	503	1310	595	3940	625	STD
	540/70 R 24 IND	168 A8/B	DW 16 L	DW 18 L	530	1366	611	4133	650	STD
Ø 26"	480/80 R 26 IND	160 A8/B	DW 15 L	DW 16 L	479	1428	638	4287	675	STD
	480/80 R 26 IND	167 A8/B	DW 15 L	DW 16 L	479	1428	638	4287	675	STD
Ø 28"	440/80 R 28 IND	156 A8/B	DW 14 L	DW 13; DW 13 L; DW 15 L	441	1415	643	4278	675	STD

STD: Standard



Radial



A8/B



168

Technologies



Steel Belted



Special Compound

Performance



Stability



Traction



High Puncture Resistance



Cut and Chip Resistance



Radial



A8/B



164



MULTIMAX MP 527

RADIAL MPT TIRES

MULTIMAX MP 527 is a multi-purpose radial tire designed for telehandlers and compact loaders in agro-industrial applications. The tire shows a block pattern design providing excellent traction even on the harder surfaces. The strong sidewall ensures outstanding stability in lift mode. MULTIMAX MP 527 is made of a special cut-and-chip-resistant compound providing a long service life.

Technologies



Block Pattern

Performance



Stability



Traction



High Load Capacity



Cut and Chip Resistance



Hard Surfaces

	Tire size	LI/SS	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	SRI (index)	Version
			Rec.	Alt.						
Ø 18"	340/80 R 18 IND	143 A8/B	11 ; 11 SDC ; W 11	W 10 ; 12 ; 12 SDC	343	1001	455	3028	475	STD
	360/70 R 18 IND	142 A8/B	11	W 10 ; 11 SDC ; W 11 ; 12 ; 12 SDC	360	969	439	2887	475	STD
Ø 20"	340/80 R 20 IND	144 A8/B	11	W 10 ; 11 SDC ; W 11 ; 12 ; 12 SDC	343	1052	483	3176	500	STD
	400/70 R 20 IND (16.0/70 R 20)	149 A8/B	13	12 SDC ; 13 SDC ; 14	404	1068	494	3282	525	STD
Ø 24"	400/70 R 24 IND	152 A8/B	13	DW 12 ; DW 13 ; DW 13 L ; 13 SDC ; DW 14 L	404	1170	542	3597	575	STD
	400/80 R 24 IND	162 A8/B	DW 13	DW 12 ; DW 13 L ; DW 14 L	404	1250	578	3834	600	STD
	440/80 R 24 IND	161 A8/B	DW 14 L	DW 13 ; DW 13 L ; DW 15 L	441	1314	601	3985	625	STD
	460/70 R 24 IND (17.5 L R 24)	159 A8/B	DW 15 L	DW 14 L ; DW 16 L	465	1254	574	3801	600	STD
	500/70 R 24 IND	164 A8/B	DW 16 L	DW 15 L ; DW 18 L	503	1310	597	4019	625	STD
Ø 26"	480/80 R 26 IND	160 A8/B	DW 15 L	DW 16 L	479	1428	642	4259	675	STD
Ø 28"	440/80 R 28 IND	156 A8/B	DW 14 L	DW 13 ; DW 13 L ; DW 15 L	441	1415	648	4270	675	STD

STD: Standard



MULTIMAX MP 529

RADIAL MPT TIRES

MULTIMAX MP 529 is a steel belted multi-purpose radial tire designed for telehandlers in industrial applications. Its tread design has been specially developed for hard surfaces. The strong sidewall and the larger footprint area ensure outstanding stability in lift mode. MULTIMAX MP 529 also features a strong puncture-resistant casing and is made of a special cut-and-chip-resistant compound providing extraordinary durability and a long service life.

	Tire size	Type	STAR RATING	LI/SS	Version	S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	RIM	
										Rec.	Alt.
Ø 18"	340/80 R 18	TL	-	143 A8/B	SB	343	1001	445	3007	11 ; 11 SDC ; W 11	W 10 ; 12 ; 12 SDC
Ø 20"	400/70 R 20 IND (405/70 R 20)	TL	-	149 A8/B	SB	415	1090	500	3314	13	12 SDC ; 13 SDC ; 14

SB: Steel Belted



Radial



143

Technologies



Larger Footprint



Steel Belted

Performance



Cut and Chip Resistance



Durability



Hard Surfaces



High Puncture Resistance



Stability



Radial



MULTIMAX MP 540

RADIAL MPT TIRES

MULTIMAX MP 540 has been designed by BKT for all multi-purpose vehicles. Thanks to the All Steel casing, MULTIMAX MP 540 enables to carry heavy loads during on and off road applications. In addition, its block pattern design provides outstanding stability and durability.

Technologies



Block Pattern



All Steel



M+S

Performance



Stability



Durability



High Load Capacity

	Tire size	Type	STAR RATING	LI/SS	Version	O.W.	O.D.	SLR	RC	RIM	
						(mm)	(mm)	(mm)	(mm)	Rec.	Alt.
Ø 16"	315/55 R 16	TL	-	120 K/124 F	STD	305	751	354	2325	W 10 L	11
Ø 18"	335/80 R 18 (12.5 R 18)	TL	-	132 K	STD	340	985	446	3000	11	-
Ø 20"	275/80 R 20 (10.5 R 20)	TL	-	134 K	STD	270	955	443	2913	W 9	9
	335/80 R 20	TL	-	149 K	STD	340	1044	492	3258	11	-
	365/80 R 20 (14.5 R 20)	TL	-	152 K	STD	365	1086	495	3308	11	-
Ø 20"	405/70 R 20 (16.0/70 R 20)	TL	-	152 K	STD	402	1082	490	3295	13	12 ; 13 SDC
	Ø 24"	405/70 R 24 (16.0/70 R 24)	TL	-	152 J	STD	402	1174	530	3586	13

STD: Standard





MULTIMAX MT 518

RADIAL MPT TIRES

MULTIMAX MT 518 has been specially designed for military trucks. It is a block pattern and steel-belted tire featuring high puncture resistance as well as outstanding stability. Besides, MULTIMAX MT 518 withstands high speed and provides an extended tire life-cycle.

	Tire size	Type	STAR RATING	LI/SS	Version	S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	RIM	
										Rec.	Alt.
Ø 16.5"	36 X 12.5 R 16.5	TL	-	129 N	STD	315	902	420	2758	9.75	-

STD: Standard



Radial



Technologies



High Speed



Steel Belted

Performance



Durability



High Puncture Resistance



Stability





Radial



MULTIMAX MP 538

RADIAL MPT TIRES

MULTIMAX MP 538 is a radial multipurpose tire specifically designed for several applications and machineries: graders and loaders operating in winter conditions, as well as telehandlers, universal vehicles and sweepers in road maintenance. Thanks to the strong steel-belted casing, MULTIMAX MP 538 allows to carry heavy loads even at high speeds. In addition, its unique tread design helps maintaining excellent traction on ice and snow.

Technologies



High Speed



Steel Belted



M+S

Performance



High Load Capacity



Ice and Snow



Durability



Traction

	Tire size	LI/SS	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	SRI (index)	Version
			Rec.	Alt.						
Ø 20"	405/70 R 20 MPT	152 G	W 13	-	407	1076	484	3289	-	SB

SB: Steel Belted





RT 747 AGRO INDUSTRIAL

RT 747 AGRO INDUSTRIAL is a radial agro-industrial tire suitable for compact loaders and telehandlers. Its extra wide lugs provide excellent traction and great stability in lifting operations. It has been designed with a special cut-and-chip resistance compound that enables the tire to carry heavy loads. RT 747 AGRO INDUSTRIAL is the right answer to all general farming operations that need outstanding versatility.

	Tire size	Type	STAR RATING	LI/SS	Version	S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	RIM	
										Rec.	Alt.
Ø 16"	11 L R 16	TL	-	122 A8/B	STD	290	850	371	2497	W 8	W 10 L
Ø 24"	460/70 R 24 (17.5 L R 24)	TL	-	152 A8/B	STD	465	1254	556	3840	DW 15 L	DW 14 L ; DW 16 L
	460/70 R 24 (17.5 L R 24)	TL	-	159 A8/ 156 B	STD	465	1254	556	3840	DW 15 L	DW 14 L ; DW 16 L
	500/70 R 24 (19.5 L R 24)	TL	-	157 A8/ 154 B	STD	485	1320	585	3949	DW 16 L	DW 15 L ; DW 18 L

STD: Standard



Radial



Technologies



Special Compound



More Lugs

Performance



Cut and Chip Resistance



High Load Capacity



Stability



Traction



Bias



CON STAR

CON STAR is particularly suitable for compact loaders and telehandlers in agro-industrial, lifting and loading applications. It features great traction along with excellent vertical and horizontal stability. CON STAR has been made of a cut-and-chip-resistant compound contributing to an extended tire life-cycle.

Technologies



Special Compound

Performance



Stability



Traction



Cut and Chip Resistance

	Tire size	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS
		Rec.	Alt.								
Ø 18"	340/80 - 18 (12.5/80 - 18)	11	12 ; 11 SDC ; 12 SDC ; W 10 ; W 11	350	1015	465	3040	IND	-	TL	143A8
Ø 20"	340/80 - 20 (12.5/80 - 20)	11	12 ; 11 SDC ; 12 SDC ; W 10 ; W 11	350	1065	491	3272	IND	-	TL	144A8
		W 12	W 11 ; 12 SDC ; 12 ; W 13 ; 13 SDC ; 13	385	1080	500	3273	IND	-	TL	148A8
	13	12 SDC ; 13 SDC ; 14	405	1080	501	3303	IND	16	TL	149A8	
	13	12 SDC ; 13 SDC ; 14	405	1080	501	3303	IND	-	TL	156A8	
	13	12 SDC ; 13 SDC ; 14	405	1080	496	3106	IND	-	TL	161A8	
Ø 24"	400/70 - 24 (16.0/70 - 24)	13	DW 12 ; 13 SDC ; DW 13 ; DW 13 L ; DW 14 L	395	1175	544	3556	IND	-	TL	158A8
		DW 13	DW 12 ; DW 13 L ; DW 14 L	405	1250	570	3781	IND	20	TL	162A8
	DW 14 L	DW 13 ; DW 13 L ; DW 15 L	455	1315	610	3986	IND	22	TL	168A8	
	DW 15 L	DW 14 L ; DW 16 L	460	1250	562	3784	IND	-	TL	159A8	
	DW 16 L	DW 15 L ; DW 18 L	505	1300	579	3926	IND	-	TL	164A8	
Ø 26"	480/80 - 26 (18.4 - 26)	DW 15 L	DW 16 L	490	1410	643	4272	IND	-	TL	160A8
Ø 28"	440/80 - 28 (16.9 - 28)	DW 14 L	DW 13 ; DW 13 L ; DW 15 L	450	1420	632	4299	IND	-	TL	156A8

IND: Industrial



AS 504

AS 504 is an agro-industrial tire mainly designed for soil tillage, implement and material-handling operations. This tire, which features excellent self-cleaning properties and increased grip, is suitable for field trailers and telehandlers. AS 504 is available in several versions to meet specific end-user requirements: an "HD" version with a special cut-and-chip resistance compound, while the "special" version has a reinforced casing that ensures a longer tire life.

	Tire size	Type	PR	LI/SS		Version	S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	RIM	
				DW	FR						Rec.	Alt.
Ø 12"	6.5/80 - 12	TT	4	72 A8	84 A8	STD	169	608	283	1836	5 J	5 JA
	6.5/80 - 12	TL	4	72 A8	84 A8	STD	169	608	283	1836	5 J	5 JA
	6.5/80 - 12	TT	6	80 A8	93 A8	STD	169	608	283	1836	5 J	5 JA
	6.5/80 - 12	TL	6	80 A8	93 A8	STD	169	608	283	1836	5 J	5 JA
	6.5/80 - 12	TT	6	80 A8	93 A8	HD	169	608	283	1836	5 J	5 JA
	7.00 - 12	TT	4	75 A8	88 A8	STD	187	683	311	2049	4.5	-
	7.00 - 12	TL	4	75 A8	88 A8	STD	187	683	311	2049	4.5	-
	7.00 - 12	TT	6	83 A8	95 A8	STD	187	683	300	2001	4.5	-
	7.00 - 12	TL	6	83 A8	95 A8	STD	187	683	311	2049	4.5	-
	7.00 - 12	TL	8	88 A8	100 A8	AB	187	683	311	2049	4.5	-
	7.00 - 12	TL	8	88 A8	100 A8	SPL	187	683	311	2049	4.5	-
	10.0/80 - 12	TL	-	109 A8	121 A8	STD	270	730	335	2233	9.00	7.0
	11.0/65 - 12	TT	8	101 A8	114 A8	STD	273	700	321	2072	9.00	-
	11.0/65 - 12	TL	8	101 A8	114 A8	STD	273	700	321	2072	9.00	-
	24 X 8.50 - 12	TL	6	81 A8	94 A8	STD	216	610	284	1761	7 JA ; 7.00 l	-

STD: Standard - HD: Heavy Duty - AB: Aramid Belted - SPL: Special



Bias



A8



168

Technologies



Aramid Belted



Heavy Duty



Reinforced Carcass

Performance



Durability



Self-Cleaning



Traction



Stability



Cut and Chip Resistance





Bias



A8



168



AS 504

AS 504 is an agro-industrial tire mainly designed for soil tillage, implement and material-handling operations. This tire, which features excellent self-cleaning properties and increased grip, is suitable for field trailers and telehandlers. AS 504 is available in several versions to meet specific end-user requirements: an "HD" version with a special cut-and-chip resistance compound, while the "special" version has a reinforced casing that ensures a longer tire life.

Technologies



Aramid Belted



Heavy Duty



Reinforced Carcass

Performance



Durability



Self-Cleaning



Traction



Stability



Cut and Chip Resistance

	Tire size	Type	PR	LI/SS		Version	S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	RIM	
				DW	FR						Rec.	Alt.
Ø 12"	26 X 12.00 - 12	TL	-	112 A6		STD	310	648	298	1932	10.50 AT	8.0 AT ; 8.5 AT ; 9.0 AT
Ø 15"	5.00 - 15	TT	4	67 A8	79 A8	STD	140	657	308	1957	3.50 D	3.00 D ; 4.00 E ; 4 J
	5.00 - 15	TT	6	75 A8	88 A8	STD	140	657	308	1957	3.50 D	3.00 D ; 4.00 E ; 4 J
	5.00 - 15	TL	6	75 A8	88 A8	STD	140	657	308	1957	3.50 D	3.00 D ; 4.00 E ; 4 J
	7.5 L - 15	TT	6	97 A8	109 A8	STD	210	765	354	2280	6 LB	5 K ; 5½ J ; 5½ K
	7.5 L - 15	TT	8	100 A8	113 A8	STD	210	765	354	2280	6 LB	5 K ; 5½ J ; 5½ K
	7.5 L - 15	TL	8	100 A8	113 A8	STD	210	765	354	2280	6 LB	5 K ; 5½ J ; 5½ K
	7.5 L - 15	TL	8	100 A8	113 A8	AB HD	210	765	354	2280	6 LB	5 K ; 5½ J ; 5½ K
	7.5 L - 15	TT	8	100 A8	113 A8	HD	210	765	354	2280	6 LB	5 K ; 5½ J ; 5½ K
	400/50 - 15	TL	-	109 A8	121 A8	STD	395	790	369	2387	13 LB	-
Ø 15.3"	10.0/75 - 15.3	TT	8	106 A8	119 A8	STD	264	785	360	2404	9.00	-
	10.0/75 - 15.3	TL	8	106 A8	119 A8	STD	264	785	360	2404	9.00	-
	10.0/75 - 15.3	TL	8	106 A8	119 A8	IND	264	785	360	2404	9.00	-
	10.0/75 - 15.3	TL	10	111 A8	123 A8	STD	264	785	360	2404	9.00	-
	10.0/75 - 15.3	TL	14	118 A8	130 A8	STD	264	785	360	2404	9.00	-

STD: Standard - HD: Heavy Duty - AB HD: Aramid Belted Heavy Duty - IND: Industrial



	Tire size	Type	PR	LI/SS		Version	S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	RIM	
				DW	FR						Rec.	Alt.
Ø 15.3"	10.0/75 - 15.3	TT	18	123 A8	135 A8	STD	264	785	360	2404	9.00	-
	10.0/75 - 15.3	TL	18	123 A8	135 A8	STD	264	785	360	2404	9.00	-
	11.5/80 - 15.3	TT	8	114 A8	126 A8	STD	290	867	380	2540	9.00	-
	11.5/80 - 15.3	TL	8	114 A8	126 A8	STD	290	867	380	2540	9.00	-
	11.5/80 - 15.3	TL	10	119 A8	131 A8	STD	290	867	380	2540	9.00	-
	11.5/80 - 15.3	TT	12	123 A8	135 A8	STD	290	867	380	2540	9.00	-
	11.5/80 - 15.3	TL	12	123 A8	135 A8	STD	290	867	380	2540	9.00	-
	11.5/80 - 15.3	TL	12	123 A8	135 A8	SR	290	867	380	2540	9.00	-
	11.5/80 - 15.3	TT	14	126 A8	139 A8	STD	290	867	380	2540	9.00	-
	11.5/80 - 15.3	TL	14	126 A8	139 A8	STD	290	867	380	2540	9.00	-
	27 X 10 - 15.3	TL	8	95 A8	107 A8	STD	260	695	317	2071	9.00	-
	27 X 10 - 15.3	TT	8	95 A8	107 A8	STD	260	695	317	2071	9.00	-
Ø 16"	4.00 - 16	TT	4	66 A8	78 A8	STD	110	628	296	1935	3.00 D	2.50 C
	6.00 - 16	TT	6	83 A8	95 A8	STD	164	735	343	2190	4.00 E	4.50 E ; 4½ K
	6.00 - 16	TT	6	83 A8	95 A8	HD	164	735	343	2190	4.00 E	4.50 E ; 4½ K

STD: Standard - SR: Stubble Resistant - HD: Heavy Duty





Bias



168



AS 504

AS 504 is an agro-industrial tire mainly designed for soil tillage, implement and material-handling operations. This tire, which features excellent self-cleaning properties and increased grip, is suitable for field trailers and telehandlers. AS 504 is available in several versions to meet specific end-user requirements: an "HD" version with a special cut-and-chip resistance compound, while the "special" version has a reinforced casing that ensures a longer tire life.

Technologies



Aramid Belted



Heavy Duty



Reinforced Carcass

Performance



Durability



Self-Cleaning



Traction



Stability



Cut and Chip Resistance

	Tire size	Type	PR	LI/SS		Version	S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	RIM	
				DW	FR						Rec.	Alt.
Ø 16"	6.00 - 16	TT	8	91 A8	103 A8	HD	164	735	343	2190	4.00 E	4.50 E ; 4½ K
	7.50 - 16	TT	6	92 A8	104 A8	STD	209	803	372	2475	5.50 F	4.50 E ; 5.00 F ; 4.00 E ; 5 K ; 6 LB ; 6.00 F
	7.50 - 16	TL	8	99 A8	112 A8	STD	209	803	372	2475	5.50 F	4.50 E ; 5.00 F ; 4.00 E ; 5 K ; 6 LB ; 6.00 F
	7.50 - 16	TT	8	99 A8	112 A8	STD	209	803	372	2475	5.50 F	4.50 E ; 5.00 F ; 4.00 E ; 5 K ; 6 LB ; 6.00 F
	7.50 - 16	TT	8	99 A8	112 A8	HD	209	803	372	2475	5.50 F	4.50 E ; 5.00 F ; 4.00 E ; 5 K ; 6 LB ; 6.00 F
	9.0/70 - 16 (230/70 - 16)	TL	10	106 A8	119 A8	STD	222	760	355	2285	W 7	-
	270/75 - 16 (10.0/75 - 16)	TL	-	111 A8	123 A8	STD	250	810	-	-	9.00	-
Ø 17"	15.0/55 - 17	TL	10	122 A8	134 A8	STD	380	890	395	2608	13.00	13
	15.0/55 - 17	TL	14	128 A8	141 A8	STD	380	890	395	2608	13.00	13
	19.0/45 - 17	TL	14	131 A8	144 A8	STD	465	865	389	2578	16.00	-
	19.0/45 - 17	TL	16	134 A8	147 A8	STD	465	865	389	2578	16.00	-
	420/55 - 17	TL	14	129 A8	142 A8	STD	430	910	407	2712	13.00	-
	420/55 - 17	TL	16	133 A8	145 A8	STD	430	910	407	2712	13.00	-
Ø 18"	7.50 - 18	TT	6	94 A8	106 A8	STD	209	854	407	2649	5.50 F	4.50 E ; 6.00 F ; 5.00 F
	7.50 - 18	TT	8	101 A8	114 A8	STD	209	854	407	2649	5.50 F	4.50 E ; 6.00 F ; 5.00 F

STD: Standard - HD: Heavy Duty



	Tire size	Type	PR	LI/SS		Version	S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	RIM	
				DW	FR						Rec.	Alt.
Ø 18"	7.50 - 18	TT	12	111 A8	122 A8	STD	209	854	407	2649	5.50 F	4.50 E ; 6.00 F ; 5.00 F
	10.5/80 - 18	TL	10	119 A8	131 A8	STD	274	907	430	2672	W 9	9 ; W 8
	12.5/80 - 18	TL	12	129 A8	142 A8	STD	308	987	438	2892	W 9	9 ; 11
	12.5/80 - 18	TL	12	129 A8	142 A8	SPL	308	987	438	2892	W 9	9 ; 11
	12.5/80 - 18	TL	16	135 A8	148 A8	STD	308	987	438	2892	W 9	9 ; 11
	12.5/80 - 18	TL	18	138 A8	150 A8	STD	308	987	438	2892	W 9	9 ; 11
Ø 20"	7.50 - 20	TT	8	103 A8	116 A8	STD	209	904	422	2695	5.50 F	4.50 E ; 6.00 F ; 5.00 F
	16.0/70 - 20	TL	10	135 A8	147 A8	STD	418	1097	487	3214	13	12 SDC ; 14 ; 13 SDC
	16.0/70 - 20	TL	12	139 A8	151 A8	STD	418	1097	487	3214	13	12 SDC ; 14 ; 13 SDC
	16.0/70 - 20	TL	14	142 A8	154 A8	STD	418	1097	487	3214	13	12 SDC ; 14 ; 13 SDC
	16.0/70 - 20	TL	16	144 A8	156 A8	STD	418	1097	487	3214	13	12 SDC ; 14 ; 13 SDC
	400/70 - 20	TL	-	149 A8		IND	408	1097	487	3214	13	12 SDC ; 14 ; 13 SDC
Ø 24"	15.5/80 - 24	TL	10	142 A8	154 A8	STD	384	1262	570	3875	W 12	W 13 ; W 14 L
	15.5/80 - 24	TL	12	145 A8	157 A8	STD	384	1262	570	3875	W 12	W 13 ; W 14 L
	15.5/80 - 24	TL	14	148 A8	160 A8	SPL	384	1262	570	3875	W 12	W 13 ; W 14 L

STD: Standard - SPL: Special - IND: Industrial





Bias



A8



168



AS 504

AS 504 is an agro-industrial tire mainly designed for soil tillage, implement and material-handling operations. This tire, which features excellent self-cleaning properties and increased grip, is suitable for field trailers and telehandlers. AS 504 is available in several versions to meet specific end-user requirements: an "HD" version with a special cut-and-chip resistance compound, while the "special" version has a reinforced casing that ensures a longer tire life.

Technologies



Aramid Belted



Heavy Duty



Reinforced Carcass

Performance



Durability



Self-Cleaning



Traction



Stability



Cut and Chip Resistance

	Tire size	Type	PR	LI/SS		Version	S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	RIM	
				DW	FR						Rec.	Alt.
Ø 24"	15.5/80 - 24	TL	14	148 A8	160 A8	STD	384	1262	570	3875	W 12	W 13 ; W 14 L
	15.5/80 - 24	TL	16	151 A8	163 A8	STD	384	1262	570	3875	W 12	W 13 ; W 14 L
	16.5/85 - 24	TL	10	146 A8	158 A8	STD	415	1325	584	4013	W 13	W 14 L ; W 15 L
	16.5/85 - 24	TL	12	151 A8	163 A8	STD	415	1325	584	4013	W 13	W 14 L ; W 15 L
	16.5/85 - 24	TT	16	155 A8	168 A8	STD	415	1325	584	4013	W 13	W 14 L ; W 15 L
	16.5/85 - 24	TL	16	155 A8	168 A8	STD	415	1325	584	4013	W 13	W 14 L ; W 15 L
	400/80 - 24	TL	-	156 A8		IND	394	1262	566	3655	W 13	W 12 ; W 14 L
	400/80 - 24	TL	-	162 A8		IND	394	1262	566	3655	W 13	W 12 ; W 14 L

STD: Standard - IND: Industrial





AT 603

AT 603 is a bias agro-industrial tire for implement machinery and backhoe loaders. AT 603 has been engineered to ensure great durability and traction on drive wheels providing best performance on every surface as well as excellent self-cleaning properties. The AT 603 "special" version has a reinforced casing, while the "HD" version offers improved cut and chip resistance.

	Tire size	Type	PR	LI/SS		Version	S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	RIM	
				DW	FR						Rec.	Alt.
Ø 18"	10.5/80 - 18	TL	10	119 A8	131 A8	STD	274	907	422	2727	W 9	W 8 ; 9
	10.5/80 - 18	TL	10	119 A8	131 A8	HD	274	907	422	2727	W 9	W 8 ; 9
	10.5/80 - 18	TL	10	119 A8	131 A8	SPL	274	907	422	2727	W 9	W 8 ; 9
	12.5/80 - 18	TL	12	129 A8	142 A8	STD	308	1000	448	3027	W 9	11
	12.5/80 - 18	TL	16	135 A8	148 A8	STD	308	1000	448	3027	W 9	11
	12.5/80 - 18	TL	18	138 A8	150 A8	STD	308	1000	448	3027	W 9	11
	12.5/80 - 18	TL	12	129 A8	142 A8	SPL	308	1000	448	3027	W 9	11
Ø 25"	15.5 - 25	TL	12	-	-	STD	410	1265	577	3861	12.00/1.3	12.00/ 1.3 (DC)

STD: Standard - HD: Heavy Duty - SPL: Special



Bias



A8



150

Technologies



Heavy Duty



Reinforced Carcass

Performance



Cut and Chip Resistance



Durability



Self-Cleaning



Traction



Bias



AT 621

AT 621 is suitable for backhoe loaders and compact loaders in all digging and loading operations in agriculture. The AT 621 tire features an extra deep tread which ensures great cut and chip resistance and higher durability. In addition, this BKT tire ensures great durability and self cleaning properties. AT 621 is available in several versions to meet the most differing user requirements.

Performance



Durability



Traction



Self-Cleaning



Cut and Chip Resistance

	Tire size	Type	PR	LI/SS		Version	S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	RIM	
				DW	FR						Rec.	Alt.
Ø 15"	33 X 12.5 - 15	TT	8	-	-	STD	318	851	394	2507	10.00 F SDC	-
Ø 15.3"	10.0/75 - 15.3	TL	10	127 A6	-	STD	267	780	373	2385	9.0	-
Ø 16"	9.00 - 16	TT	16	137 A6	-	IND	260	925	-	-	6.50 H	6.00 G
	12.5/70 - 16	TL	8	-	-	STD	315	855	385	2584	10 LB	-
	12.5/70 - 16	TT	14	-	-	STD	315	855	385	2584	10 LB	-
	12.5/70 - 16	TL	14	-	-	STD	315	855	385	2584	10 LB	-
Ø 18"	12.5/80 - 18	TT	12	129 A8	142 A8	STD	308	987	434	2916	W 9	11.0
	12.5/80 - 18	TL	12	129 A8	142 A8	STD	308	987	434	2916	W 9	11.0
	12.5/80 - 18	TL	12	129 A8	142 A8	SPL	308	987	434	2916	W 9	11.0
	12.5/80 - 18	TL	16	135 A8	148 A8	STD	308	987	434	2916	W 9	11.0
	12.5/80 - 18	TT	16	135 A8	148 A8	STD	308	987	434	2916	W 9	11.0
	12.5/80 - 18	TL	16	135 A8	148 A8	IND HD	308	987	434	2916	W 9	11.0
	15.5/60 - 18	TL	10	139 A2	-	STD	394	940	428	2871	W 13	-
	15.5/60 - 18	TL	12	141 A2	-	STD	394	940	428	2871	W 13	-
15.5/70 - 18 (400/70 - 18)	TL	10	-	-	STD	400	1030	474	3111	W 13	-	

STD: Standard - IND: Industrial - SPL: Special - IND HD: Industrial Heavy Duty



	Tire size	Type	PR	LI/SS	Version	S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	RIM	
										Rec.	Alt.
Ø 19.5"	385/65 D 19.5	TL	16	165 A2	STD	390	1020	478	3136	11.75	12.25
Ø 20"	12.5 - 20	TT	12	-	STD	325	1040	480	3103	11.0	-
	17.5/65 - 20	TL	10	-	STD	450	1090	490	3294	W 14 L	-
	42 X 17 - 20	TT	10	-	STD	432	1073	480	3198	14.00 TG SDC	-
	400/70 - 20	TL	16	152 B/ 168 A2	STD	405	1090	494	3271	13	12 SDC; 13 SDC; 14
	400/70 - 20	TL	-	149 A8	STD	405	1090	494	3271	13	12 SDC; 13 SDC; 14
Ø 24"	16.9 - 24	TL	12	149 A8	IND	450	1302	590	3906	DW 15 L	DW 14 L
	17.5 L - 24	TL	8	139 A8	STD	450	1255	558	3752	DW 15 L	DW 14 L
	19.5 L - 24	TL	12	151 A8	STD	482	1305	587	3936	DW 16 L	-
Ø 26"	18.4 - 26	TL	12	156 A8	STD	480	1425	649	4288	DW 16 L	DW 15 L
Ø 28"	16.9 - 28	TT	12	152 A8	IND	450	1410	639	4199	DW 15 L	DW 14 L
	16.9 - 28	TL	12	152 A8	IND	450	1410	639	4199	DW 15 L	DW 14 L
	16.9 - 28	TL	14	154 A8	IND	450	1410	639	4199	DW 15 L	DW 14 L
Ø 30"	16.9 - 30	TL	12	153 A8	IND	450	1460	670	4398	DW 15 L	DW 14 L

STD: Standard - IND: Industrial



Bias



MP 567

MP 567 is an agro-industrial tire suitable for field and road transport and municipality/maintenance operations. It is the perfect tire for telehandlers and implement machinery. The MP 567 tire provides good traction in all the weather conditions as well as excellent self-cleaning properties. This tire ensures a comfortable driving experience, together with a longer service life.

Performance



Comfort



Durability



Self-Cleaning



Traction

	Tire size	Type	PR	LI/SS		Version	S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	RIM	
				DW	FR						Rec.	Alt.
Ø 15"	11.5/80 - 15	TL	12	123 A8	135 A8	IMP	290	875	-	-	8 LB	-
	Ø 15.3"	10.0/75 - 15.3	TL	18	123 A8	135 A8	IMP	258	774	365	2401	9.0
	10.0/75 - 15.3	TL	10	111 A8	123 A8	IMP	258	774	365	2401	9.0	-
	10.0/75 - 15.3	TL	12	114 A8	126 A8	IMP	258	774	365	2401	9.0	-
	10.0/75 - 15.3	TL	14	118 A8	130 A8	IMP	258	774	365	2401	9.0	-
	11.5/80 - 15.3	TL	18	130 A8	143 A8	IMP	292	868	393	2578	9.0	-
	11.5/80 - 15.3	TL	10	119 A8	131 A8	IMP	292	868	393	2578	9.0	-
	11.5/80 - 15.3	TL	14	126 A8	139 A8	IMP	292	868	393	2578	9.0	-
Ø 18"	10.5 - 18	TT	10	-	-	STD	273	905	415	2768	9.0	9 SDC
	10.5 - 18	TL	10	-	-	STD	273	905	415	2768	9.0	9 SDC
	10.5 - 18	TL	12	-	-	STD	273	905	415	2768	9.0	9 SDC
	10.5 - 18	TL	12	-	-	SPL	273	905	415	2768	9.0	9 SDC
	12.0/75 - 18 (300/75 - 18)	TL	12	126 A8	139 A8	IMP	298	915	426	2723	W 9	9 ; 11
	12.5 - 18	TT	10	-	-	STD	325	990	450	2940	11.0	12 SDC
	12.5 - 18	TL	10	-	-	STD	325	990	450	2940	11.0	12 SDC
	12.5 - 18	TT	12	-	-	STD	325	990	450	2940	11.0	12 SDC

STD: Стандартна - SPL: Специално приложение - IMP: Селскостопанско оборудване



	Tire size	Type	PR	LI/SS	Version	S.W.	O.D.	SLR	RC	RIM	
						(mm)	(mm)	(mm)	(mm)	Rec.	Alt.
Ø 18"	12.5 - 18	TL	12	-	STD	325	990	466	3024	11.0	12 SDC
	12.5 - 18	TL	16	-	STD	325	990	450	2940	11.0	12 SDC
Ø 19.5"	18 - 19.5 IND	TL	16	160 B/ 162 A8	STD	460	1104	498	3280	14.00	-
	18 - 19.5 IND	TL	18	165 B/ 167 A8	STD	460	1104	498	3280	14.00	-
	18 - 19.5 IND	TL	18	165 B/ 167 A8	DB	460	1104	498	3280	14.00	-
Ø 20"	10.5 - 20	TT	10	-	STD	270	955	445	2880	9.0	9 SDC
	10.5 - 20	TL	10	-	STD	270	955	445	2880	9.0	9 SDC
	12.5 - 20	TT	10	-	STD	325	1040	490	3142	11.0	12 SDC
	12.5 - 20	TL	10	-	STD	325	1040	490	3142	11.0	12 SDC
	12.5 - 20	TT	12	-	STD	325	1040	490	3142	11.0	12 SDC
	12.5 - 20	TL	16	-	STD	325	1040	490	3142	11.0	12 SDC
	12.5 - 20	TL	12	-	STD	325	1040	490	3142	11.0	12 SDC
	12.5 - 20	TL	12	-	HD	325	1040	490	3142	11.0	12 SDC
	14.5 - 20	TL	10	-	STD	360	1116	495	3315	11.0	12 SDC
	14.5 - 20	TL	12	-	STD	360	1116	495	3315	11.0	12 SDC
	14.5 - 20	TL	14	-	HD	360	1116	495	3315	11.0	12 SDC

STD: Стандартна - HD: Подсилена конструкция - DB: Двойно мънисто





Bias



167



MP 567

MP 567 is an agro-industrial tire suitable for field and road transport and municipality/maintenance operations. It is the perfect tire for telehandlers and implement machinery. The MP 567 tire provides good traction in all the weather conditions as well as excellent self-cleaning properties. This tire ensures a comfortable driving experience, together with a longer service life.

Performance



Comfort



Durability



Self-Cleaning



Traction

	Tire size	Type	PR	LI/SS	Version	S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	RIM	
										Rec.	Alt.
Ø 20"	14.5 - 20	TL	16	-	STD	360	1116	495	3315	11.0	12 SDC
	14.5 - 20	TL	18	-	STD	360	1116	495	3315	11.0	12 SDC
	14.5 - 20	TL	14	-	STD	360	1116	495	3315	11.0	12 SDC
	16.0/70 - 20 (405/70 - 20)	TL	14	-	STD	405	1128	490	3350	13 SDC	12
	16.0/70 - 20 (405/70 - 20)	TT	14	-	STD	405	1128	490	3350	13 SDC	12

STD: Стандартна





MP 570

MP 570 is an agro-industrial tire, which is suitable for excavators and backhoe loaders. This tire provides good traction and durability, as well as excellent self-cleaning properties in all operating conditions.

	Tire size	Type	PR	LI/SS	Version	S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	RIM	
										Rec.	Alt.
Ø 18"	12.5 - 18	TL	12	-	STD	308	990	450	2950	11	12 SDC
	12.5 - 18	TL	10	-	STD	308	990	450	2950	11	12 SDC
Ø 20"	12.5 - 20	TL	10	-	STD	335	1050	480	3130	11	12 SDC
	12.5 - 20	TL	12	-	STD	335	1050	480	3130	11	12 SDC
	14.5 - 20	TL	12	-	STD	360	1116	505	3325	11	12 SDC

STD: Standard



Performance



Durability



Self-Cleaning



Traction





Bias



A6



106

MP 585



MP 585 is an agro-industrial tire, which is suitable for multi-purpose vehicles in municipality/maintenance applications. This tire is specially engineered with a block pattern that offers maximum stability and durability in the most difficult working conditions, also at high speeds.

Technologies



High Speed



Block Pattern

Performance



Durability



Stability

	Tire size	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS
		Rec.	Alt.								
Ø 20"	6.50 - 20	5.50 F	4.00 E ; 5.00 F	200	875	-	-	STD	10	TT	106 A6
	10.5 - 20	9	9 SDC	273	970	455	2890	STD	10	TL	-
	12.5 - 20	11	12 SDC	335	1050	480	3130	STD	12	TL	-

STD: Standard





MP 590

MP 590 is an agro-industrial tire suitable for loading operations with telehandlers and forklifts. This tire provides good traction and excellent stability as well as increased durability.

	Tire size	Type	PR	LI/SS	Version	S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	RIM	
										Rec.	Alt.
∅ 22.5"	18 - 22.5 (445/65 - 22.5)	TL	16	-	STD	480	1190	530	3534	14.0	-
	18 - 22.5 (445/65 - 22.5)	TL	20	-	STD	480	1190	530	3534	14.0	-

STD: Standard



Bias

Performance



Durability



Stability



Traction





Bias



158



MP 600

MP 600 is an agro-industrial tire, suitable for municipality/maintenance operations with telehandlers and implement machinery, providing a comfortable driving experience. This tire provides good traction and excellent self-cleaning properties along with an extended product life-cycle.

Performance



Comfort



Durability



Self-Cleaning



Traction

	Tire size	Type	PR	LI/SS		Version	S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	RIM	
				DW	FR						Rec.	Alt.
Ø 18"	10.5 - 18	TL	10	-	-	STD	272	920	420	2740	9	9SDC
	12.5 - 18	TL	10	-	-	STD	308	990	450	2950	11	12SDC
	12.5 - 18	TL	12	-	-	STD	308	990	450	2950	11	12SDC
Ø 20"	400/70 - 20 (16.0/70 - 20)	TL	14	-	-	STD	405	1085	-	-	13 SDC	12
Ø 24"	400/70 - 24 (16.0/70 - 24)	TL	10	-	-	STD	405	1185	545	3530	13 SDC	12
	400/70 - 24 (16.0/70 - 24)	TL	14	-	-	STD	405	1185	545	3530	13 SDC	12
	400/70 - 24 (16.0/70 - 24)	TL	14	-	-	SPL	405	1185	545	3530	13 SDC	12
	400/70 - 24 (16.0/70 - 24)	TL	18	158 A8	-	STD	405	1185	545	3530	13 SDC	12

STD: Standard - SPL: Special





Bias



Performance



Stability



Traction



TR 459

TR 459 has been particularly designed for digging and loading operations as well as municipality and maintenance applications with tractors and backhoe loaders. It offers high stability and is available in two versions. The "special" version provides an extended tire life-cycle.

	Tire size	Type	PR	LI/SS	Version	S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	RIM	
										Rec.	Alt.
Ø 20"	400/70 - 20	TL	-	149 A8	IND	404	1090	-	-	13	12 SDC ; 13 SDC ; 14
Ø 24"	14.9 - 24	TL	8	137 A8	IND	390	1244	562	3657	DW 13	DW 12 ; DW 11 ; DW 13 L
	14.9 - 24	TL	12	145 A8	IND	390	1244	562	3657	DW 13	DW 12 ; DW 11 ; DW 13 L
	16.9 - 24	TL	8	142 A8	IND	450	1310	596	3840	DW 15 L	DW 14 L
	16.9 - 24	TL	10	145 A8	IND	450	1310	590	3850	DW 15 L	DW 14 L
	16.9 - 24	TL	12	149 A8	IND	450	1310	590	3850	DW 15 L	DW 14 L
	17.5 L - 24	TL	8	139 A8	IND	445	1270	557	3825	DW 15 L	DW 14 L
	17.5 L - 24	TL	10	144 A8	IND	445	1270	557	3825	DW 15 L	DW 14 L
	17.5 L - 24	TL	12	148 A8	IND	445	1270	557	3825	DW 15 L	DW 14 L
	18.4 - 24	TL	12	155 A8	IND	472	1375	610	4114	DW 16 L	DW 15 L
	19.5 L - 24	TL	10	147 A8	IND	490	1333	585	4031	DW 16 L	-
	19.5 L - 24	TL	12	151 A8	IND	490	1333	585	4031	DW 16 L	-
	19.5 L - 24	TL	12	151 A8	IND SPL	490	1333	585	4031	DW 16 L	-
	21 L - 24	TL	14	157 A8	IND	533	1378	605	3995	DW 18 L	-
	21 L - 24	TL	12	155 A8	IND	533	1378	605	3995	DW 18 L	-

IND: Industrial - IND SPL: Industrial Special



	Tire size	Type	PR	LI/SS	Version	S.W.	O.D.	SLR	RC	RIM	
						(mm)	(mm)	(mm)	(mm)	Rec.	Alt.
Ø 26"	18.4 - 26	TL	12	156A8	IND	472	1425	628	4346	DW 16 L	DW 15 L
	18.4 - 26	TL	14	159A8	IND	472	1425	628	4346	DW 16 L	DW 15 L
	18.4 - 26	TL	16	162A8	IND	472	1425	628	4346	DW 16 L	DW 15 L
Ø 28"	16.9 - 28	TL	8	145A8	IND	440	1410	640	4145	DW 15 L	DW 14 L
	16.9 - 28	TL	10	148A8	IND	440	1410	640	4145	DW 15 L	DW 14 L
	16.9 - 28	TL	12	152A8	IND	445	1410	640	4272	DW 15 L	DW 14 L
	18.4 - 28	TL	12	157A8	IND	472	1475	664	4495	DW 16 L	DW 15 L
	21 L - 28	TL	12	157A8	IND	535	1480	-	-	DW 18 A	-
Ø 30"	16.9 - 30	TL	12	153A8	IND	440	1470	657	4484	DW 15 L	DW 14 L

IND: Industrial





Bias



A8



TR 461



TR 461 is a BKT pattern suitable for municipality and maintenance applications with tractors as well as for loading operations with telehandlers. The sidewall protection features particular resistance against cuts and bruises providing a longer life even on hard surfaces in addition to excellent stability.

Performance



Cut and Chip Resistance



Durability



Road Oriented



Stability

	Tire size	Type	PR	LI/SS		Version	S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	RIM	
				DW	FR						Rec.	Alt.
Ø 18"	12.5/80 - 18	TL	12	129 A8	142 A8	STD	305	987	435	2902	W 9	11
	12.5/80 - 18	TL	18	138 A8	150 A8	STD	305	987	435	2902	W 9	11
Ø 24"	16.9 - 24	TL	14	151 A8		STD	440	1280	566	3763	DW 15 L	DW 14 L
	19.5 L - 24	TL	12	151 A8		STD	505	1310	591	3908	DW 16 L	-
	19.5 L - 24	TL	14	154 A8		STD	490	1310	578	3851	DW 16 L	-
	21 L - 24	TL	14	157 A8		STD	540	1385	607	4072	DW 18 L	-
Ø 28"	16.9 - 28	TL	14	154 A8		STD	440	1390	620	4087	DW 15 L	DW 14 L
Ø 34"	620/60 B 34	TL	-	175 A8		HD	615	1629	750	4930	DW 20 B	-

STD: Standard - HD: Heavy Duty





TR 463

TR 463 has been specially designed for backhoe loaders and industrial tractors. Made of a superior tread compound and featuring a strong nylon casing, this tire stands for best results in industrial and OTR applications, and on construction sites. TR 463 provides excellent traction for drive wheels.



Bias



Performance



	Tire size	Type	PR	LI/SS	Version	S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	RIM	
										Rec.	Alt.
Ø 24"	16.9 - 24	TL	12	149A8	IND	445	1300	584	3877	DW 15 L	DW 14 L
	16.9 - 24	TL	14	152A8	IND	445	1300	584	3877	DW 15 L	DW 14 L
Ø 26"	18.4 - 26	TL	12	156A8	IND	480	1425	637	4215	DW 16 L	DW 15 L
	18.4 - 26	TL	14	158A8	IND	480	1425	637	4215	DW 16 L	DW 15 L
Ø 28"	16.9 - 28	TL	12	152A8	IND	450	1405	636	4190	DW 15 L	DW 14 L

IND: Industrial





Load index

The load index is a code that defines a tire's maximum weight capacity at the speed given by its speed index provided that the usage conditions recommended by the Manufacturer are fully complied with.

Corresponding values of load index (LI) and load capacity per wheel (kg / lbs)

LI	lbs	kg	LI	lbs	kg	LI	lbs	kg	LI	lbs	kg
50	420	190	85	1135	515	120	3085	1400	155	8540	3875
51	430	195	86	1170	530	121	3195	1450	156	8820	4000
52	440	200	87	1200	545	122	3305	1500	157	9095	4125
53	455	206	88	1235	560	123	3415	1550	158	9370	4250
54	465	212	89	1280	580	124	3525	1600	159	9645	4375
55	480	218	90	1325	600	125	3635	1650	160	9920	4500
56	495	224	91	1355	615	126	3750	1700	161	10195	4625
57	505	230	92	1390	630	127	3860	1750	162	10470	4750
58	520	236	93	1435	650	128	3970	1800	163	10745	4875
59	535	243	94	1475	670	129	4080	1850	164	11025	5000
60	550	250	95	1520	690	130	4190	1900	165	11355	5150
61	565	257	96	1565	710	131	4300	1950	166	11685	5300
62	585	265	97	1610	730	132	4410	2000	167	12015	5450
63	600	272	98	1655	750	133	4540	2060	168	12345	5600
64	615	280	99	1710	775	134	4675	2120	169	12785	5800
65	640	290	100	1765	800	135	4805	2180	170	13225	6000
66	660	300	101	1820	825	136	4940	2240	171	13560	6150
67	675	307	102	1875	850	137	5070	2300	172	13890	6300
68	695	315	103	1930	875	138	5205	2360	173	14330	6500
69	715	325	104	1985	900	139	5355	2430	174	14770	6700
70	740	335	105	2040	925	140	5510	2500	175	15210	6900
71	760	345	106	2095	950	141	5675	2575	176	15650	7100
72	785	355	107	2150	975	142	5840	2650	177	16095	7300
73	805	365	108	2205	1000	143	6005	2725	178	16535	7500
74	825	375	109	2270	1030	144	6175	2800	179	17085	7750
75	855	387	110	2335	1060	145	6395	2900	180	17635	8000
76	880	400	111	2405	1090	146	6615	3000	181	18185	8250
77	910	412	112	2470	1120	147	6780	3075	182	18740	8500
78	935	425	113	2535	1150	148	6945	3150	183	19290	8750
79	965	437	114	2600	1180	149	7165	3250	184	19840	9000
80	990	450	115	2680	1215	150	7385	3350	185	20390	9250
81	1020	462	116	2755	1250	151	7605	3450	186	20945	9500
82	1045	475	117	2835	1285	152	7825	3550	187	21495	9750
83	1075	487	118	2910	1320	153	8045	3650	188	22045	10000
84	1100	500	119	3000	1360	154	8265	3750	189	22705	10300

LI	lbs	kg	LI	lbs	kg	LI	lbs	kg
190	23370	10600	200	30865	14000	210	41885	19000
191	24030	10900	201	31965	14500	211	42990	19500
192	24690	11200	202	33070	15000	212	44090	20000
193	25350	11500	203	34170	15500	213	45415	20600
194	26015	11800	204	35270	16000	214	46735	21200
195	26785	12150	205	36375	16500	215	48060	21800
196	27555	12500	206	37475	17000	216	49380	22400
197	28330	12850	207	38580	17500	217	50705	23000
198	29100	13200	208	39680	18000	218	52025	23600
199	29980	13600	209	40785	18500	219	53570	24300

Speed index

The speed index is a value that indicates the maximum admitted speed at which the tire can carry the weight corresponding to its load index provided that the usage conditions recommended by the Manufacturer are fully complied with.

Speed index	A2	A4	A6	A8	B	C	D	E	F	G	J	K
km/h	10	20	30	40	50	60	65	70	80	90	100	110
mph	5	10	20	25	30	35	40	45	50	55	62	68



Corporate Office

Balkrishna Industries Ltd.

BKT HOUSE, C/15, Trade World, Kamala Mills Compound, Senapati Bapat Marg, Lower Parel, Mumbai - 400013, India
Tel: (+91) 22-6666 3800 - Fax: (+91) 22-6666 3898/99 - e-mail: info@bkt-tires.com - bkt-tires.com

BKT Europe srl

Viale Della Repubblica, 133
20831 Seregno (MB), Italy
Tel: (+39) 0362 33 03 28
(+39) 0362 32 51 07
Fax: (+39) 0362 23 24 72

BKT USA Inc.

202 Montrose West Ave. Suite 240
Copley, Ohio 44321
Office: (+1) 330 836 1090
Fax: (+1) 330 836 1091

BKT Tires (CANADA) Inc.

55 York Street, Suite 401
Toronto, Ontario M5J 1R7, Canada
Tel: AG/IND (+1) 514 792 9220
OTR (+1) 780 888 5667
Fax: (+1) 416 229 1711



bkt-tires.com