



**GROWING TOGETHER**

# ROW CROP

AGRICULTURAL TIRES





## AGRICULTURAL TIRES

# ROW

If you are looking for a tire that is suitable for row crops, BKT has the right answer for your needs. Specifically designed for the different types of land for vineyard and orchard crops, BKT offers an extensive range of highly performing tires. Available in a large number of sizes appropriate for the different types of machinery, these tires are your best ally for row crops. Distinguishing marks? High load capacity and improved traction as well as reduced soil compaction. BKT tires offer the perfect mix of performance, efficiency, durability and riding comfort.



*Radial*

Radial tires have steel cords that are arranged running radially from bead to bead around the tire. Sidewall and tread have independent functional features providing more flexibility, great performance, durability, and fuel economy.













*Bias*

Bias tires have cord plies that are arranged running diagonally from bead to bead across the tire. Layers overlap forming a crisscross pattern. This design features extraordinary sidewall resistance and puncture resistance.



# W CROP

## TECHNOLOGIES AND PERFORMANCE



# ROW CROP TIRES



**AGRIMAX RT 855**



[ p. 6 ]



**AGRIMAX SPARGO**



[ p. 13 ]



**AGRIMAX SPARGO SB**



[ p. 15 ]





**AGRIMAX RT 945**



[ p. 16 ]



**AGRIMAX RT 955**



[ p. 18 ]





Radial

R-1W

D

176

# AGRIMAX RT 855

RADIAL TRACTOR TIRES



AGRIMAX RT 855 provides excellent traction and comfort properties. Mainly designed for soil tillage and both field and road transport, some sizes are also suitable for spraying, and vineyard harvesting. AGRIMAX RT 855 has excellent self-cleaning features that allow for a quick change from field operations to road usage.

### Performance



Traction



Self-Cleaning



High Load Capacity





Handling and Comfort

Tire size	LI/SS		RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	SRI (index)	Version		
	DW	FR	Rec.	Alt.								
Ø 16"	180/95 R 16 (6.50 R 16)		105 A8/B		5.5 F	6.0 F	185	760	340	2265	350	STD
	210/95 R 16 (7.50 R 16)		-	116 A8	W 7	W 6 ; 6 LB	214	806	350	2353	370	IMP
	210/95 R 16 (7.50 R 16)		106 A8/B		W 7	W 6 ; 6 LB	214	806	360	2387	370	STD
Ø 18"	210/95 R 18 (7.50 R 18)		108 A8/B		W 7	W 6	214	855	385	2565	400	STD
	210/95 R 18 (7.50 R 18)		-	122 A8	W 7	W 6	214	855	378	2565	400	IMP
	250/80 R 18		125 A8/125 B		W 8	W 7 ; W 9	250	835	375	2539	410	STD
Ø 20"	210/90 R 20 (8.3 R 20)		110 A8/B		W 7	W 6	211	890	412	2681	425	STD
	210/95 R 20 (7.50 R 20)		110 A8/B		W 7	W 6	214	908	418	2749	425	STD
	250/85 R 20 (9.5 R 20)		116 A8/B		W 8	W 7 ; W 9	250	940	424	2812	450	STD
	280/85 R 20 (11.2 R 20)		112 A8/B		W 10	W 9	292	984	441	2952	475	STD
	280/85 R 20 (11.2 R 20)		122 A8/B		W 10	W 9	292	984	447	2977	475	STD
	320/85 R 20 (12.4 R 20)		119 A8/B		W 11	W 9 ; W 10	329	1052	467	3100	500	STD
Ø 22"	250/85 R 22 (9.5 R 22)		113 A8/B		W 8	W 7	251	985	453	2964	475	STD
	250/85 R 22		113 A8/B		W 8	W 7	251	985	453	2964	475	SPL
Ø 24"	250/85 R 24 (9.5 R 24)		109 A8/B		W 8	W 7 ; W 9	251	1036	475	3104	500	STD

STD: Standard - SPL: Special - IMP: Implement



	Tire size	LI/SS	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	SRI (index)	Version
			Rec.	Alt.						
										
Ø 24"	<b>250/85 R 24</b> (9.5 R 24)	109 A8/B	W 8	W 7 ; W 9	251	1036	475	3104	500	SPL
	<b>280/85 R 24</b> (11.2 R 24)	115 A8/B	W 10	W 9	292	1086	492	3224	525	STD
	<b>280/85 R 24</b> (11.2 R 24)	115 A8/B	W 10	W 9	292	1086	492	3224	525	SPL
	<b>320/85 R 24</b> (12.4 R 24)	122 A8/B	W 11	W 9 ; W 10	329	1154	519	3424	550	STD
	<b>320/85 R 24</b> (12.4 R 24)	122 A8/B	W 11	W 9 ; W 10	329	1154	519	3424	550	SPL
	<b>340/85 R 24</b> (13.6 R 24)	125 A8/B	W 12	W 11	353	1188	531	3540	575	STD
	<b>340/85 R 24</b> (13.6 R 24)	125 A8/B	W 12	W 11	353	1188	531	3540	575	SPL
	<b>380/85 R 24</b> (14.9 R 24)	131 A8/B	W 12	W 11 ; W 13	380	1256	554	3720	600	STD
	<b>380/85 R 24</b> (14.9 R 24)	131 A8/B	W 12	W 11 ; W 13	380	1256	554	3720	600	SPL
	<b>420/85 R 24</b> (16.9 R 24)	137 A8/B	W 15 L	W 14 L ; W 13	450	1324	582	3900	625	STD
	<b>420/85 R 24</b> (16.9 R 24)	137 A8/B	W 15 L	W 14 L ; W 13	450	1324	582	3900	625	SPL
Ø 28"	<b>250/85 R 28</b> (9.5 R 28)	112 A8/B	W 8	W 7 ; W 9	251	1137	519	3421	550	STD
	<b>250/85 R 28</b> (9.5 R 28)	112 A8/B	W 8	W 7 ; W 9	251	1137	519	3421	550	SPL
	<b>280/85 R 28</b> (11.2 R 28)	118 A8/B	W 10	W 9	292	1187	545	3558	575	STD
	<b>280/85 R 28</b> (11.2 R 28)	118 A8/B	W 10	W 9	292	1187	545	3558	575	SPL

STD: Standard - SPL: Special





Radial

R-1W

D

176

# AGRIMAX RT 855

RADIAL TRACTOR TIRES



AGRIMAX RT 855 provides excellent traction and comfort properties. Mainly designed for soil tillage and both field and road transport, some sizes are also suitable for spraying, and vineyard harvesting. AGRIMAX RT 855 has excellent self-cleaning features that allow for a quick change from field operations to road usage.

### Performance



Traction



Self-Cleaning



High Load Capacity





Handling and Comfort

	Tire size	LI/SS	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	SRI (index)	Version
			Rec.	Alt.						
Ø 28"	320/85 R 28 (12.4 R 28)	124 A8/B	W 11	W 9 ; W 10	329	1255	569	3743	600	STD
	320/85 R 28 (12.4 R 28)	124 A8/B	W 11	W 9 ; W 10	329	1255	569	3743	600	SPL
	340/85 R 28 (13.6 R 28)	127 A8/B	W 12	W 11	353	1289	588	3890	625	STD
	340/85 R 28 (13.6 R 28)	139 A8/B	W 12	W 11	353	1315	603	3963	625	STD
	340/85 R 28 (13.6 R 28)	127 A8/B	W 12	W 11	353	1289	588	3890	625	SPL
	380/85 R 28 (14.9 R 28)	133 A8/B	W 12	W 11 ; W 13	380	1357	606	4015	650	STD
	380/85 R 28 (14.9 R 28)	133 A8/B	W 12	W 11 ; W 13	380	1357	606	4015	650	SPL
	420/85 R 28 (16.9 R 28)	139 A8/B	W 15 L	W 13 ; W 14 L	438	1425	638	4241	675	STD
	420/85 R 28 (16.9 R 28)	139 A8/B	W 15 L	W 13 ; W 14 L	438	1425	638	4241	675	SPL
Ø 30"	380/85 R 30 (14.9 R 30)	135 A8/B	W 12	W 11 ; W 13	380	1408	633	4190	675	STD
	380/85 R 30 (14.9 R 30)	135 A8/B	W 12	W 11 ; W 13	380	1408	633	4190	675	SPL
	420/85 R 30 (16.9 R 30)	140 A8/B	W 15 L	W 13 ; W 14 L	438	1475	661	4421	700	STD
	420/85 R 30 (16.9 R 30)	140 A8/B	W 15 L	W 13 ; W 14 L	438	1475	661	4421	700	SPL
	460/85 R 30 (18.4 R 30)	145 A8/B	W 16 L	W 14 L ; W 15 L	475	1544	680	4562	725	STD
	460/85 R 30 (18.4 R 30)	156 A8/B	W 16 L	W 14 L ; W 15 L	475	1544	680	4562	725	STD

STD: Standard - SPL: Special



	Tire size	LI/SS	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	SRI (index)	Version
			Rec.	Alt.						
										
<b>Ø 30"</b>	<b>460/85 R 30 (18.4 R 30)</b>	145 A8/B	W 16 L	W 14 L; W 15 L	475	1544	680	4562	725	SPL
<b>Ø 32"</b>	<b>320/85 R 32 (12.4 R 32)</b>	126 A8/B	W 11	W 9; W 10	329	1357	621	4081	650	STD
	<b>320/85 R 32 (12.4 R 32)</b>	126 A8/B	W 11	W 9; W 10	329	1357	621	4081	650	SPL
<b>Ø 34"</b>	<b>320/85 R 34 (12.4 R 34)</b>	141 A8/B	W 11	W 9; W 10	329	1408	645	4280	675	STD
	<b>320/85 R 34 (12.4 R 34)</b>	141 A8/B	W 11	W 9; W 10	329	1408	645	4280	675	SPL
	<b>380/85 R 34 (14.9 R 34)</b>	137 A8/B	W 12	W 11; W 13	380	1509	682	4504	725	STD
	<b>380/85 R 34 (14.9 R 34)</b>	137 A8/B	W 12	W 11; W 13	380	1509	682	4504	725	SPL
	<b>420/85 R 34 (16.9 R 34)</b>	147 A8/B	W 15 L	W 13; W 14 L	438	1578	728	4782	750	STD
	<b>420/85 R 34 (16.9 R 34)</b>	142 A8/B	W 15 L	W 13; W 14 L	438	1578	709	4702	750	STD
	<b>420/85 R 34 (16.9 R 34)</b>	142 A8/B	W 15 L	W 13; W 14 L	438	1578	709	4702	750	SPL
	<b>460/85 R 34 (18.4 R 34)</b>	147 A8/B	W 16 L	W 14; W 15 L	475	1646	721	4865	775	STD
	<b>460/85 R 34 (18.4 R 34)</b>	158 A8/B	W 16 L	W 14 L; W 15 L	475	1646	721	4865	775	STD
	<b>460/85 R 34 (18.4 R 34)</b>	147 A8/B	W 16 L	W 14 L; W 15 L	475	1646	721	4865	775	SPL
<b>Ø 36"</b>	<b>320/85 R 36</b>	147 D/150 A8	W 11	W 9; W 10	329	1458	672	4404	700	STD
	<b>320/85 R 36 (12.4 R 36)</b>	128 A8/B	W 11	W 9; W 10	329	1458	672	4404	700	STD

STD: Standard - SPL: Special





Radial

R-1W

D

176

# AGRIMAX RT 855

RADIAL TRACTOR TIRES



AGRIMAX RT 855 provides excellent traction and comfort properties. Mainly designed for soil tillage and both field and road transport, some sizes are also suitable for spraying, and vineyard harvesting. AGRIMAX RT 855 has excellent self-cleaning features that allow for a quick change from field operations to road usage.

### Performance



Traction



Self-Cleaning



High Load Capacity





Handling and Comfort

	Tire size	LI/SS	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	SRI (index)	Version
			Rec.	Alt.						
Ø 36"	320/85 R 36 (12.4 R 36)	128 A8/B	W 11	W 9 ; W 10	329	1458	672	4404	700	SPL
	340/85 R 36 (13.6 R 36)	132 A8/B	W 12	W 11	353	1492	689	4507	725	STD
	340/85 R 36 (13.6 R 36)	132 A8/B	W 12	W 11	353	1492	689	4507	725	SPL
Ø 38"	320/85 R 38 (12.4 R 38)	143 A8/B	W 11	W 9 ; W 10 ; DW 10 ; DW 11	329	1509	700	4580	725	STD
	320/85 R 38 (12.4 R 38)	143 A8/B	W 11	W 9 ; W 10 ; DW 10	329	1509	700	4580	725	SPL
	340/85 R 38 (13.6 R 38)	133 A8/B	W 12	W 11	353	1543	712	4668	750	STD
	340/85 R 38 (13.6 R 38)	133 A8/B	W 12	W 11	353	1543	712	4668	750	SPL
	380/85 R 38 (14.9 R 38)	139 A8/B	W 12	W 11 ; W 13	380	1611	736	4842	775	STD
	380/85 R 38 (14.9 R 38)	139 A8/B	W 12	W 11 ; W 13	380	1611	736	4842	775	SPL
	420/85 R 38 (16.9 R 38)	144 A8/B	W 15 L	W 13 ; W 14 L	438	1679	763	5014	800	STD
	420/85 R 38 (16.9 R 38)	144 A8/B	W 15 L	W 13 ; W 14 L	438	1679	763	5014	800	SPL
	460/85 R 38 (18.4 R 38)	149 A8/B	W 16 L	W 14 L ; W 15 L	475	1747	785	5205	825	STD
	460/85 R 38 (18.4 R 38)	149 A8/B	W 16 L	W 14 L ; W 15 L	475	1747	785	5205	825	SPL
	480/80 R 38 (18.4 R 38)	149 A8/B	DW 16 L	W 14 L ; W 15 L	475	1747	785	5161	825	STD
	520/85 R 38 (20.8 R 38)	155 A8/B	DW 16 L	DW 18 L ; DD 16 L	516	1849	813	5466	875	STD

STD: Standard - SPL: Special



	Tire size	LI/SS	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	SRI (index)	Version
			Rec.	Alt.						
										
Ø 38"	520/85 R 38 (20.8 R 38)	170 A8/B	DW 16 L	DW 18 L ; DD 16 L	516	1849	847	5595	875	STD
	520/85 R 38 (20.8 R 38)	155 A8/B	DW 16 L	DW 18 L ; DD 16 L	516	1849	813	5466	875	SPL
	520/85 R 38	170 A8/B	DW 16 L	DW 18 L ; DD 16 L	516	1849	847	5595	875	SPL
Ø 42"	480/80 R 42 (18.4 R 42)	151 A8/B	W 16 A ; DD 16 ; DW 16 A	DD 16 L ; DW 16 L ; W 16 L	479	1835	835	5495	875	STD
	520/85 R 42 (20.8 R 42)	157 A8/B	DW 16 L ; W 16 A ; DD 16	DW 18 A ; DD 18 ; W 18 A ; DD 18 L	516	1951	858	5782	925	STD
	520/85 R 42 (20.8 R 42)	167 A8/B	DW 16 L ; W 16 A ; DD 16	DW 18 A ; DD 18 ; W 18 A ; DD 18 L	516	1951	858	5782	925	STD
	520/85 R 42 (20.8 R 42)	157 A8/B	DW 16 L ; W 16 A ; DD 16	DW 18 A ; DD 18 ; W 18 A ; DD 18 L	516	1951	858	5782	925	SPL
	520/85 R 42 (20.8 R 42)	167 A8/B	DW 16 L ; W 16 A ; DD 16	DW 18 A ; DD 18 ; W 18 A ; DD 18 L	516	1951	858	5782	925	SPL
Ø 46"	420/80 R 46 (16.9 R 46)	159 D/ 170 A2	W 13	W 12	418	1840	863	5641	900	STD
	420/80 R 46 (16.9 R 46)	151 D/ 162 A2	W 13	W 12	418	1840	863	5641	900	STD
	420/80 R 46 (16.9 R 46)	159 D/ 170 A2	W 13	W 12	418	1840	863	5641	900	SPL
	480/80 R 46 (18.4 R 46)	158 A8/B	DW 16 A ; W 16 A ; DD 16	W 16 L ; DD 16 L ; DW 16 L	479	1936	895	5871	925	STD
	480/80 R 46 (18.4 R 46)	164 A8/B	DW 16 A ; W 16 A ; DD 16	W 16 L ; DD 16 L ; DW 16 L	479	1936	895	5871	925	STD
	520/85 R 46 (20.8 R 46)	158 A8/B	DW 16 L ; W 16 A ; W 16 L ; DD 16	DW 18 L ; W 18 L ; W 18 A	516	2052	930	6157	975	STD
	520/85 R 46 (20.8 R 46)	173 A8/B	DW 16 L ; W 16 A ; W 16 L ; DD 16	DW 18 L ; W 18 L ; W 18 A	516	2075	964	6310	975	STD

STD: Standard - SPL: Special





Radial



# AGRIMAX RT 855

RADIAL TRACTOR TIRES



AGRIMAX RT 855 provides excellent traction and comfort properties. Mainly designed for soil tillage and both field and road transport, some sizes are also suitable for spraying, and vineyard harvesting. AGRIMAX RT 855 has excellent self-cleaning features that allow for a quick change from field operations to road usage.

### Performance



Traction



Self-Cleaning



High Load Capacity



Handling and Comfort

	Tire size	LI/SS	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	SRI (index)	Version
			Rec.	Alt.						
Ø 46"	520/85 R 46	158 A8/B	DW 16 L ; W 16 A ; W 16 L ; DD 16	DW 18 L ; W 18 L ; W 18 A	516	2052	930	6157	975	SPL
Ø 50"	420/80 R 50 (16.9 R 50)	165 A8/B	W 13	W 12	418	1951	915	5955	950	SB
	480/80 R 50 (18.4 R 50)	159 A8/B	DW 16 L	DW 15 L ; W 15 L	489	2036	941	6183	975	STD
	480/80 R 50 (18.4 R 50)	176 A8	DW 16 L	DW 15 L ; W 15 L	489	2036	945	6183	975	SB
	520/85 R 50 (20.8 R 50)	165 A8/B	DW 16 L	DW 18 L	516	2154	992	6472	1025	STD

STD: Standard - SB: Steel Belted - SPL: Special







# AGRIMAX SPARGO

RADIAL VF SPRAYER TIRES

AGRIMAX SPARGO is the special BKT tire for row crop applications. It has been designed for enhanced productivity in the fields and for preserving the soil in the long term. Thanks to VF technology, the tire provides higher load capacity at standard pressure. Thanks to a strong casing and an increased number of lugs, AGRIMAX SPARGO ensures outstanding durability along with strong stability both in the fields and during road transfers.

	Tire size	LI/SS	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	SRI (index)	Version
			Rec.	Alt.						
										
Ø 34"	VF 380/85 R 34	160 D	W 13 A	W 12	380	1500	678	4514	725	STD
Ø 38"	VF 380/85 R 38	161 D	W 13 A	W 12	380	1602	730	4830	775	STD
Ø 42"	VF 320/90 R 42	163 D	W 11	W 10 ; DW 10 ; W 10 L ; DW 11	323	1642	764	4995	775	STD
	VF 480/80 R 42	176 D	DW 16 L	DW 15 L	479	1835	838	5572	875	STD
Ø 46"	VF 320/90 R 46	165 D	W 11	W 10 ; DW 10 ; W 10 L ; DW 11	323	1743	810	5316	825	STD
	VF 380/90 R 46	173 D	DW 13 A	W 13 A ; DW 12	390	1852	846	5611	875	STD
	VF 380/90 R 46	175 D	DW 13 A	W 13 A ; DW 12	390	1852	848	5582	875	STD
	VF 480/80 R 46	177 D	DW 16 L	DW 15 L	479	1936	892	5907	925	STD
	VF 750/60 R 46	189 D	DW 27 B	-	755	2086	940	6337	1000	SB
Ø 50"	VF 320/90 R 50	169 D	W 11	W 10 ; DW 10 ; W 10 L ; DW 11	323	1846	865	5650	875	STD
	VF 380/90 R 50	175 D	W 13 B	W 12 B	390	1950	893	5950	925	STD
	VF 380/105 R 50	179 D	W 13 A	W 12 ; DW 12 ; DW 13 ; DW 13 L	400	2050	934	6211	975	STD
	VF 420/95 R 50	177 D	DW 14	DW 13 ; W 13 ; W 14	419	2068	943	6210	975	STD

STD: Standard - SB: Steel Belted



Radial



### Technologies



VF Technology



Strong Casing



More Lugs

### Performance



High Load Capacity



Durability



Stability





Radial

R-1

D

189



# AGRIMAX SPARGO

RADIAL VF SPRAYER TIRES

AGRIMAX SPARGO is the special BKT tire for row crop applications. It has been designed for enhanced productivity in the fields and for preserving the soil in the long term. Thanks to VF technology, the tire provides higher load capacity at standard pressure. Thanks to a strong casing and an increased number of lugs, AGRIMAX SPARGO ensures outstanding durability along with strong stability both in the fields and during road transfers.

### Technologies



VF Technology



Strong Casing



More Lugs

### Performance



High Load Capacity



Durability



Stability

	Tire size	LI/SS	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	SRI (index)	Version
			Rec.	Alt.						
Ø 50"	VF 480/80 R 50	179 D	DW 16 L	DW 15 L	479	2038	947	6224	975	STD
	VF 480/95 R 50	181 D	DW 16 L	DW 15 L	479	2182	991	6606	1025	STD
Ø 54"	VF 320/90 R 54 CFO	168 D	W 11	W 10 ; DW 10 ; W 10 L ; DW 11	323	1948	910	5946	925	STD
	VF 380/90 R 54	176 D	W 13	DW 13 ; DW 12 ; W 12	383	2056	948	6232	975	STD
	VF 380/105 R 54	180 D	W 13 A	W 12 ; DW 12 ; DW 13 ; DW 13 L	400	2140	984	6503	1025	STD
	VF 480/95 R 54 CFO	180 D	DW 16 L	DW 15 L	509	2300	1033	6956	1075	STD

STD: Standard







# AGRIMAX SPARGO SB

RADIAL VF SPRAYER TIRES

AGRIMAX SPARGO SB is a special row crop tire that is particularly suitable for tractors and sprayers in open-field spraying and row crop applications, or for specialized tractors in orchards and vineyards. Thanks to its advanced VF-technology (Very Increased Flexion), the tire is able to carry 40% heavier load compared to a standard tire of the same size at the same inflation pressure. The wide footprint ensures uniform weight distribution as well as low soil compaction in the fields. AGRIMAX SPARGO SB stands for excellent performance and high speed-efficiency both on and off the road, up to 65 km/h. Moreover, the robust polyester casing provides improved durability, better handling and dimensional stability as well as enhanced equipment stability and control both in the fields and on the road, thus avoiding the risk of tire slippage and reducing fuel consumption. AGRIMAX SPARGO SB features a special sidewall design that provides tire flexibility and reduces vibrations - essential for operations with precision sprayers. Finally, the steel-belted construction guarantees excellent puncture resistance plus outstanding support of heavy loads, while the extraordinarily strong lug design stands for improved traction. The combination of all these features results in a lower economic and environmental impact, increasing productivity and operator comfort at the same time.

Ø	Tire size	LI/SS	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	SRI (index)	Version
			Rec.	Alt.						
										
32"	VF 270/95 R 32	148 D	W 9	-	280	1339	617	4080	650	SB
34"	VF 420/85 R 34	165 D	DW 15 L	DW 14 L	429	1578	716	4779	750	SB
36"	VF 270/95 R 36	150 D	W 9	-	280	1441	664	4397	700	SB
38"	VF 270/95 R 38	151 D	W 9	-	280	1491	692	4546	725	SB
	VF 380/95 R 38	165 D	W 13	W 12	395	1690	767	5116	800	SB
46"	VF 380/90 R 46 CFO	173 D	W 13	W 12; DW 13	400	1852	856	5668	875	SB
48"	VF 270/95 R 48	155 D	W 9	-	280	1745	815	5373	850	SB
50"	VF 380/90 R 50 CFO	175 D	W 13	W 12; DW 13	400	1954	903	5986	925	SB
54"	VF 270/95 R 54	157 D	W 9	-	280	1900	895	5843	900	SB
	VF 320/90 R 54	168 D	W 11	W 10; DW 10 A; DW 11	323	1960	918	6031	925	SB
	VF 380/90 R 54	176 D	W 13	W 12; DW 12; W 13 A; DW 13; DW 13 A	395	2060	957	6310	975	SB

SB: Steel Belted



Radial



176

### Technologies





Radial

R-1W

D

160

Technologies



Strong Casing

Performance



High Load Capacity



Durability



Stability



Self-Cleaning



Traction



# AGRIMAX RT 945

RADIAL TRACTOR TIRES

AGRIMAX RT 945 is specially designed for row crops: it does not damage the crops and preserves the yield. Excellent self-cleaning features allow for a quick change from field operations to road usage, where AGRIMAX RT 945 shows brilliant performance. Its strong carcass gives the tire excellent stability, outstanding traction, and exceptional durability.

	Tire size	LI/SS	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	SRI (index)	Version
			Rec.	Alt.						
Ø 30"	420/90 R 30	147 A8/B	DW 13	W 14 L	418	1518	684	4571	700	STD
Ø 42"	320/90 R 42 (12.4 R 42)	139 A8/B	W 10	W 9 ; W 11	319	1643	760	4944	775	STD
Ø 46"	320/90 R 46 (12.4 R 46)	146 A8/B	W 10	W 9 ; W 11	319	1744	810	5232	825	STD
	320/90 R 46 (12.4 R 46)	148 D/151 A8	W 10	W 9 ; W 11	319	1744	810	5232	825	STD
	380/90 R 46 (14.9 R 46)	155 A8/B	W 12	W 11 ; W 13	380	1852	866	5648	875	STD
Ø 50"	380/90 R 46 (14.9 R 46)	159 A8/B	W 12	W 11 ; W 13	380	1852	859	5699	875	STD
	320/90 R 50 (12.4 R 50)	150 A8/B	W 10	W 9 ; W 11	319	1846	873	5618	875	STD
	380/90 R 50 (14.9 R 50)	151 A8/B	W 12	W 11 ; W 13	380	1954	906	5900	925	STD
Ø 54"	380/90 R 50 (14.9 R 50)	160 A8/B	W 12	W 11 ; W 13	390	1954	921	5958	925	STD
	320/90 R 54 (12.4 R 54)	156 A8/B	W 10	W 9 ; W 11	319	1948	930	6021	925	STD
	380/90 R 54 (14.9 R 54)	158 A8/B	W 12	W 11 ; W 13	380	2056	962	6232	975	STD

STD: Standard





Radial

R-1

D

154

Technologies



Strong Casing

Performance



High Load Capacity



Durability



Stability



Self-Cleaning



Traction



# AGRIMAX RT 955



RADIAL TRACTOR TIRES

AGRIMAX RT 955 is a BKT radial tire for row crop applications, while some sizes are also suitable for spraying and vineyards. The special tread design with a rounded shoulder provides excellent traction performance, stability and self-cleaning properties. Thanks to its strong casing, AGRIMAX RT 955 has a high load capacity.

	Tire size	LI/SS	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	SRI (index)	Version
			Rec.	Alt.						
Ø 24"	210/90 R 24 (8.3 R 24)	107 A8/B	W 7	W 6	214	1010	462	3027	475	STD
Ø 28"	210/95 R 28 (8.3 R 28)	116 A8/B	W 7	W 6	214	1111	513	3364	525	STD
Ø 32"	210/95 R 32 (8.3 R 32)	120 A8/B	W 7	W 6	214	1213	571	3703	575	STD
	230/95 R 32 (9.5 R 32)	128 A8/B	W 7	W 8	228	1251	585	3810	600	STD
	270/95 R 32 (11.2 R 32)	136 A8/B	W 9	W 8 ; W 10	275	1327	614	4076	625	STD
Ø 36"	230/95 R 36 (9.5 R 36)	130 A8/B	W 7	W 8	228	1352	639	4112	650	STD
	270/80 R 36	134 A8/B	W 9	W 8 ; W 10	275	1346	629	4090	650	STD
	270/95 R 36 (11.2 R 36)	139 A8/B	W 9	W 8 ; W 10	275	1428	665	4335	675	STD
Ø 38"	270/95 R 38 (11.2 R 38)	140 A8/B	W 9	W 8 ; W 10	275	1479	697	4510	700	STD
Ø 40"	230/95 R 40 (9.5 R 40)	132 A8/B	W 7	W 8	228	1454	690	4445	700	STD
Ø 42"	230/95 R 42 (9.5 R 42)	133 A8/B	W 7	W 8	228	1506	714	4595	725	STD
	300/85 R 42 (11.2 R 42)	144 A8/B	W 9	W 10 ; W 11	295	1577	745	4850	750	STD
Ø 44"	210/95 R 44 (8.3 R 44)	120 A8/B	W 7	W 6	214	1518	721	4653	725	STD

STD: Standard



	Tire size	LI/SS	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	SRI (index)	Version
			Rec.	Alt.						
										
Ø 44"	<b>230/95 R 44</b> (9.5 R 44)	134 A8/B	W 7	W 8	228	1556	739	4788	750	STD
	<b>270/95 R 44</b> (11.2 R 44)	142 A8/B	W 9	W 8 ; W 10	275	1632	764	4983	775	STD
Ø 46"	<b>270/95 R 46</b> (11.2 R 46)	143 A8/B	W 9	W 8 ; W 10	275	1683	792	5169	800	STD
	<b>300/95 R 46</b> (12.4 R 46)	148 A8/B	W 9	W 10 ; W 11 ; DW 10 ; DW 11	295	1738	812	5318	825	STD
	<b>300/95 R 46</b> (12.4 R 46)	148 D/ 151 A8	W 9	W 10 ; W 11 ; DW 10 ; DW 11	295	1738	812	5318	825	STD
	<b>340/85 R 46</b> (13.6 R 46)	150 A8/B	W 12	W 11	353	1746	826	5346	850	STD
Ø 48"	<b>230/95 R 48</b> (9.5 R 48)	136 A8/B	W 7	W 8	228	1656	792	5085	800	STD
	<b>230/95 R 48</b> (9.5 R 48)	136 D/ 139 A8	W 7	W 8	228	1656	792	5085	800	STD
	<b>270/95 R 48</b> (11.2 R 48)	144 A8/B	W 9	W 8 ; W 10	275	1733	820	5351	825	STD
	<b>340/85 R 48</b> (13.6 R 48)	152 A8/B	W 12	W 11	353	1797	855	5572	875	STD
	<b>340/85 R 48</b> (13.6 R 48)	151 D/ 154 A8	W 12	W 11	353	1797	855	5572	875	STD
Ø 52"	<b>300/95 R 52</b> (12.4 R 52)	151 A8/B	W 9	W 10 ; W 11 ; DW 10 ; DW 11	295	1891	889	5774	900	STD
Ø 54"	<b>270/95 R 54</b> (11.2 R 54)	146 A8/B	W 9	W 8 ; W 10	275	1885	894	5815	900	STD

STD: Standard



# Load index

The load index is a code that defines a tire's maximum weight capacity at the speed given by its speed index provided that the usage conditions recommended by the Manufacturer are fully complied with.

## Corresponding values of load index (LI) and load capacity per wheel (kg / lbs)

LI	lbs	kg	LI	lbs	kg	LI	lbs	kg	LI	lbs	kg
50	420	190	85	1135	515	120	3085	1400	155	8540	3875
51	430	195	86	1170	530	121	3195	1450	156	8820	4000
52	440	200	87	1200	545	122	3305	1500	157	9095	4125
53	455	206	88	1235	560	123	3415	1550	158	9370	4250
54	465	212	89	1280	580	124	3525	1600	159	9645	4375
55	480	218	90	1325	600	125	3635	1650	160	9920	4500
56	495	224	91	1355	615	126	3750	1700	161	10195	4625
57	505	230	92	1390	630	127	3860	1750	162	10470	4750
58	520	236	93	1435	650	128	3970	1800	163	10745	4875
59	535	243	94	1475	670	129	4080	1850	164	11025	5000
60	550	250	95	1520	690	130	4190	1900	165	11355	5150
61	565	257	96	1565	710	131	4300	1950	166	11685	5300
62	585	265	97	1610	730	132	4410	2000	167	12015	5450
63	600	272	98	1655	750	133	4540	2060	168	12345	5600
64	615	280	99	1710	775	134	4675	2120	169	12785	5800
65	640	290	100	1765	800	135	4805	2180	170	13225	6000
66	660	300	101	1820	825	136	4940	2240	171	13560	6150
67	675	307	102	1875	850	137	5070	2300	172	13890	6300
68	695	315	103	1930	875	138	5205	2360	173	14330	6500
69	715	325	104	1985	900	139	5355	2430	174	14770	6700
70	740	335	105	2040	925	140	5510	2500	175	15210	6900
71	760	345	106	2095	950	141	5675	2575	176	15650	7100
72	785	355	107	2150	975	142	5840	2650	177	16095	7300
73	805	365	108	2205	1000	143	6005	2725	178	16535	7500
74	825	375	109	2270	1030	144	6175	2800	179	17085	7750
75	855	387	110	2335	1060	145	6395	2900	180	17635	8000
76	880	400	111	2405	1090	146	6615	3000	181	18185	8250
77	910	412	112	2470	1120	147	6780	3075	182	18740	8500
78	935	425	113	2535	1150	148	6945	3150	183	19290	8750
79	965	437	114	2600	1180	149	7165	3250	184	19840	9000
80	990	450	115	2680	1215	150	7385	3350	185	20390	9250
81	1020	462	116	2755	1250	151	7605	3450	186	20945	9500
82	1045	475	117	2835	1285	152	7825	3550	187	21495	9750
83	1075	487	118	2910	1320	153	8045	3650	188	22045	10000
84	1100	500	119	3000	1360	154	8265	3750	189	22705	10300

LI	lbs	kg	LI	lbs	kg	LI	lbs	kg
190	23370	10600	200	30865	14000	210	41885	19000
191	24030	10900	201	31965	14500	211	42990	19500
192	24690	11200	202	33070	15000	212	44090	20000
193	25350	11500	203	34170	15500	213	45415	20600
194	26015	11800	204	35270	16000	214	46735	21200
195	26785	12150	205	36375	16500	215	48060	21800
196	27555	12500	206	37475	17000	216	49380	22400
197	28330	12850	207	38580	17500	217	50705	23000
198	29100	13200	208	39680	18000	218	52025	23600
199	29980	13600	209	40785	18500	219	53570	24300

## Speed index

The speed index is a value that indicates the maximum admitted speed at which the tire can carry the weight corresponding to its load index provided that the usage conditions recommended by the Manufacturer are fully complied with.

Speed index	A2	A4	A6	A8	B	C	D	E	F	G	J	K
km/h	10	20	30	40	50	60	65	70	80	90	100	110
mph	5	10	20	25	30	35	40	45	50	55	62	68







## Corporate Office

**Balkrishna Industries Ltd.**

BKT HOUSE, C/15, Trade World, Kamala Mills Compound, Senapati Bapat Marg, Lower Parel, Mumbai - 400013, India  
Tel: (+91) 22-6666 3800 - Fax: (+91) 22-6666 3898/99 - e-mail: info@bkt-tires.com - bkt-tires.com

### **BKT Europe srl**

Viale Della Repubblica,133  
20831 Seregno (MB), Italy  
Tel: (+39) 0362 33 03 28  
(+39) 0362 32 51 07  
Fax: (+39) 0362 23 24 72

### **BKT USA Inc.**

202 Montrose West Ave. Suite 240  
Copley, Ohio 44321  
Office: (+1) 330 836 1090  
Fax: (+1) 330 836 1091

### **BKT Tires (CANADA) Inc.**

55 York Street, Suite 401  
Toronto, Ontario M5J 1R7, Canada  
Tel: AG/IND (+1) 514 792 9220  
OTR (+1) 780 888 5667  
Fax: (+1) 416 229 1711



**bkt-tires.com**