



GROWING TOGETHER

TRACTOR & HARVESTER

BIAS AGRICULTURAL TIRES





TRACTOR HARVEST

BIAS AGRICULTURAL TIRES

Have you got a small lot of land or wide fields stretching over several hectares? BKT has the perfect tire that suits your needs. BKT has had a focus on research and development of tires for tractors and harvesters ever since creating specialist product ranges for any specific need.

As these types of agricultural machinery are essential for every farming business, do not ignore the key role of tires! It is important to choose products that care for the most delicate soils ensuring at the same time high load capacity as well as operators' comfort without forgetting reduced operating costs. All this even under extreme conditions. Find out which BKT product is perfect to fit your needs!



TRACTOR & HARVESTERS



Radial

Radial tires have steel cords that are arranged running radially from bead to bead around the tire. Sidewall and tread have independent functional features providing more flexibility, great performance, durability, and fuel economy.



Bias







Bias tires have cord plies that are arranged running diagonally from bead to bead across the tire. Layers overlap forming a crisscross pattern. This design features extraordinary sidewall resistance and puncture resistance.



TRACTOR TIRES

BIAS AGRICULTURAL TIRES

TECHNOLOGIES



FOR & VESTER



PERFORMANCE



Comfort



Cut and Chip
Resistance



Durability



For muddy ground



Handling and Comfort



Hard Surfaces



High Load Capacity



High Puncture
Resistance



Ideal for grassland



Self-Cleaning



Stability



Steering Control



Stubble Resistance



Traction

BIAS TRACTOR & HARVESTER TIRES



TR 126



[p. 10]



TR 128



[p. 11]



TR 133



[p. 12]



TR 135



[p. 13]



TR 136



[p. 28]



TR 144



[p. 29]



TR 145



[p. 31]



TR 171



[p. 32]



TR 173



[p. 37]



FARM 2000



[p. 38]



FARM 2000 PLUS



[p. 41]



FARM SPECIAL



[p. 42]



AS 2001



[p. 43]



TRAC FARM



[p. 44]



TRAC FARM PLUS



[p. 45]



COMMANDER (R)



[p. 46]



TR 270



[p. 48]



TR 273



[p. 50]



PUDDLE SPECIAL (A)



[p. 52]



PUDDLE SPECIAL (B)



[p. 53]



TR 318



[p. 54]



AT 316



[p. 55]



AT 523



[p. 56]



STAR TRAC



[p. 57]



BIAS TRACTOR & HARVESTER TIRES



HARVESTER SPECIAL



[p. 58]



TR 137



[p. 59]



TR 360



[p. 60]



TR 882



[p. 61]



FLOTATION 558



[p. 62]



BK 308



[p. 63]



TF 8181



[p. 64]



TF 9393



[p. 67]



TF 9090



[p. 68]



TF 9292



[p. 71]



COMMANDER (F)



[p. 72]



COMMANDER TWIN RIB



[p. 73]



COMMANDER 3 RIB



[p. 74]



POWER RIB F2



[p. 75]



PRO RIB F2M



[p. 76]



RIB F3



[p. 77]



STEER FARM



[p. 78]



Bias



Performance



High Load Capacity



Traction



TR 126

TR 126 is designed to fit small tractors in soil tillage operations. The deep lugs and the tread pattern provide excellent traction and outstanding load capacity features providing best tire performance in all operating conditions.

	Tire size	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS
		Rec.	Alt.								
Ø 14"	6 - 14	5 JA ; 5 KB	-	157	655	305	1978	STD	4	TT	66 A6
	6 - 14	5 JA ; 5 KB	-	157	655	305	1978	STD	4	TL	66 A6
	6 - 14	5 JA ; 5 KB	-	157	655	305	1978	HD	8	TT	80 A6
	7 - 14	5 JA ; 5 KB	-	170	690	320	2070	STD	4	TT	72 A6
	7 - 14	5 JA ; 5 KB	-	170	690	320	2070	STD	4	TL	72 A6
	7 - 14	5 JA ; 5 KB	-	170	690	320	2070	STD	8	TT	95 A6

STD: Standard - HD: Heavy Duty





TR 128

TR 128 has been specially designed for utility tractors and rototillers. The wide and deep lug design and the special cut-and-chip resistance compound provide an extended tire service life. TR 128 features maximum traction on wet soil.

	Tire size	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS
		Rec.	Alt.								
Ø 12"	5 - 12	4 JA	-	127	554	262	1700	STD	4	TT	-
	5 - 12	4 JA	-	127	554	262	1700	STD	6	TT	64 A6
	6.00 - 12	4.00 E	4.00 E DT	160	635	296	1926	STD	4	TT	69 A6
	6.00 - 12	4.00 E	4.00 E DT	160	635	296	1926	STD	6	TT	76 A6
	6.00 - 12	4.00 E	4.00 E DT	160	635	296	1926	STD	8	TT	82 A6
	180/85 D 12	5 JA	-	165	612	295	1847	STD	4	TT	63 A6
	180/85 D 12	5 JA	-	165	612	288	1847	STD	6	TT	76 A6
Ø 14"	7 - 14	5 JA	5 J	173	690	323	2086	STD	8	TT	95 A6

STD: Standard



Bias



95

Performance





Bias



R-1



A6



136

Technologies



More Lugs

Performance



Durability



High Load Capacity



Self-Cleaning



Traction



TR 133

TR 133 has been specially designed for tractors in soil tillage applications. Thanks to the increased number of lugs, this tire features excellent traction as well as enhanced self-cleaning properties. TR 133 provides an extended tire life-cycle.

	Tire size	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS
		Rec.	Alt.								
Ø 38"	13.6 - 38 (14.00 - 38)	W 12	W 11	350	1580	735	4843	STD	10	TT	136 A6

STD: Standard





TR 135

TR 135 is best suitable for tractors in soil tillage applications. Its reinforced casing and the special cut-and-chip resistance compound provide an extended tire life-cycle. Traction, self-cleaning properties and load capacity are key features which make the TR 135 tire the ideal partner even on the most difficult ground conditions.

	Tire size	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS
		Rec.	Alt.								
Ø 16"	12.4 - 16	W 11	W 9; 9; W 10	326	960	431	2852	STD	4	TT	97 A6
	12.4 - 16	W 11	W 9; 9; W 10	326	960	431	2852	STD	8	TT	111 A6
Ø 20"	8.00 - 20	5.50 F	-	225	965	448	2837	STD	6	TT	105 A6
	8.00 - 20	5.50 F	-	225	965	448	2837	STD	8	TT	111 A6
	9.5 - 20	W 8	W 7	240	955	454	2888	STD	6	TT	102 A6
	9.5 - 20	W 8	W 7	240	955	444	2881	HD	8	TT	107 A6
	9.5 - 20	W 8	W 7	240	955	454	2888	STD	8	TT	107 A6
	10.00 - 20	7.5	-	280	1075	495	3160	STD	10	TT	152 A2
	11.2 - 20	W 10	W 9; 9	292	1020	466	3077	STD	8	TT	111 A6
	12.4 - 20	W 11	W 9; 9; W 10; 11	325	1075	500	3160	HD	8	TT	116 A6
	12.4 - 20	W 11	W 9; 9; W 10; 11	325	1075	500	3160	STD	8	TT	116 A6
	Ø 24"	8.3 - 24	W 7	W 6	211	995	469	2985	STD	6	TT
8.3 - 24		W 7	W 6	211	995	469	2985	HD	8	TT	105 A6
8.3 - 24		W 7	W 6	211	995	475	3076	STD	8	TT	105 A6

STD: Standard - HD: Heavy Duty



Bias



R-1



A6



168

Technologies



Special Compound



Reinforced Carcass

Performance



Traction



High Load Capacity



Self-Cleaning



Durability



Cut and Chip Resistance





Bias



Technologies



Special Compound



Reinforced Carcass

Performance



Traction



High Load Capacity



Self-Cleaning



Durability



Cut and Chip Resistance





TR 135

TR 135 is best suitable for tractors in soil tillage applications. Its reinforced casing and the special cut-and-chip resistance compound provide an extended tire life-cycle. Traction, self-cleaning properties and load capacity are key features which make the TR 135 tire the ideal partner even on the most difficult ground conditions.

	Tire size	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS
		Rec.	Alt.								
Ø 24"	8.3 - 24	W 7	W 6	211	995	469	2985	HD	10	TT	111 A6
	9.5 - 24	W 8	W 7	241	1060	502	3234	STD	6	TT	106 A6
	9.5 - 24	W 8	W 7	241	1060	502	3234	HD	8	TT	112 A6
	9.5 - 24	W 8	W 7	241	1060	502	3234	STD	8	TT	112 A6
	9.5 - 24	W 8	W 7	241	1060	502	3234	HD	10	TT	116 A6
	9.5 - 24	W 8	W 7	241	1060	502	3234	STD	10	TT	116 A6
	11.2 - 24	W 10	W 9	284	1105	517	3399	STD	6	TT	110 A6
	11.2 - 24	W 10	W 9	284	1105	507	3303	HD	8	TT	116 A6
	11.2 - 24	W 10	W 9	284	1105	517	3399	STD	8	TT	116 A6
	11.2 - 24	W 10	W 9	284	1105	517	3399	STD	8	TL	116 A6
	11.2 - 24	W 10	W 9	284	1105	517	3399	HD	10	TL	120 A6
	11.2 - 24	W 10	W 9	284	1105	517	3399	HD	10	TT	120 A6
	12.4 - 24	W 11	W 9; W 10	315	1160	543	3573	STD	6	TT	115 A6
	12.4 - 24	W 11	W 9; W 10	315	1160	531	3477	HD	8	TT	121 A6

STD: Standard - HD: Heavy Duty



	Tire size	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS
		Rec.	Alt.								
											
Ø 24"	12.4 - 24	W 11	W 9; W 10	315	1160	531	3477	HD	8	TL	121 A6
	12.4 - 24	W 11	W 9; W 10	315	1160	543	3573	STD	8	TT	121 A6
	12.4 - 24	W 11	W 9; W 10	315	1160	543	3573	STD	8	TL	121 A6
	12.4 - 24	W 11	W 9; W 10	315	1160	543	3573	STD	10	TT	125 A6
	12.4 - 24	W 11	W 9; W 10	315	1160	543	3573	SPL	12	TT	128 A6
	12.4 - 24	W 11	W 9; W 10	315	1160	543	3573	STD	12	TT	128 A6
	12.4 - 24	W 11	W 9; W 10	315	1160	543	3573	STD	12	TL	128 A6
	13.6 - 24	W 12	W 11	355	1220	562	3698	HD	8	TT	123 A6
	13.6 - 24	W 12	W 11	355	1220	562	3698	STD	8	TT	123 A6
	13.6 - 24	W 12	W 11	355	1220	562	3698	STD	8	TL	123 A6
	13.6 - 24	W 12	W 11	355	1220	562	3698	HD	12	TT	130 A6
	13.6 - 24	W 12	W 11	355	1220	562	3698	STD	12	TT	130 A6
	14.9 - 24	W 13	W 11; W 12	378	1265	570	3769	HD	8	TT	128 A6
	14.9 - 24	W 13	W 11; W 12	378	1265	570	3769	HD	8	TL	128 A6

STD: Standard - HD: Heavy Duty - SPL: Special





Bias



TR 135

TR 135 is best suitable for tractors in soil tillage applications. Its reinforced casing and the special cut-and-chip resistance compound provide an extended tire life-cycle. Traction, self-cleaning properties and load capacity are key features which make the TR 135 tire the ideal partner even on the most difficult ground conditions.

Technologies



Special Compound



Reinforced Carcass

Performance



Traction



High Load Capacity



Self-Cleaning



Durability





Cut and Chip Resistance

	Tire size	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS
		Rec.	Alt.								
Ø 24"	14.9 - 24	W 13	W 11; W 12	378	1265	576	3837	STD	8	TT	128 A6
	14.9 - 24	W 13	W 11; W 12	378	1265	576	3837	STD	8	TL	128 A6
	14.9 - 24	W 13	W 11; W 12	378	1265	576	3837	HD	10	TL	132 A6
	14.9 - 24	W 13	W 11; W 12	378	1265	576	3837	HD	12	TT	135 A6
	14.9 - 24	W 13	W 11; W 12	378	1265	576	3837	STD	12	TT	135 A6
	14.9 - 24	W 13	W 11; W 12	378	1265	576	3837	STD	12	TL	135 A6
	16.9 - 24	W 15 L	W 14 L	429	1335	613	3925	HD	8	TT	133 A6
	16.9 - 24	W 15 L	W 14 L	429	1335	613	3925	STD	8	TL	133 A6
	16.9 - 24	W 15 L	W 14 L	429	1335	613	3925	STD	8	TT	133 A6
	16.9 - 24	W 15 L	W 14 L	429	1335	613	3925	STD	10	TL	136 A6
	16.9 - 24	W 15 L	W 14 L	429	1335	613	3925	STD	10	TT	136 A6
	16.9 - 24	W 15 L	W 14 L	429	1335	613	3925	HD	12	TT	140 A6
Ø 26"	14.9 - 26	W 13	W 11; W 12	375	1315	599	3947	HD	8	TT	129 A6
	14.9 - 26	W 13	W 11; W 12	375	1315	599	3947	STD	8	TT	129 A6

STD: Standard - HD: Heavy Duty



	Tire size	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS
		Rec.	Alt.								
											
Ø 26"	14.9 - 26	W 13	W 11; W 12	375	1315	599	3947	STD	12	TT	136A6
	16.9 - 26	W 15 L	W 14 L	430	1380	625	4183	STD	10	TT	137A6
	16.9 - 26	W 15 L	W 14 L	430	1380	625	4183	STD	10	TL	137A6
	16.9 - 26	W 15 L	W 14 L	430	1380	625	4183	STD	12	TT	140A6
	23.1 - 26	DW 20 B ; DW 20 A	-	587	1585	700	4615	DB	12	TL	153A6
	23.1 - 26	DW 20 B ; DW 20 A	-	587	1585	700	4615	DB	12	TT	153A6
	23.1 - 26	DW 20 B ; DW 20 A	-	587	1585	700	4615	STD	12	TL	153A6
	23.1 - 26	DW 20 B ; DW 20 A	-	587	1585	700	4615	STD	12	TT	153A6
	23.1 - 26	DW 20 B ; DW 20 A	-	587	1585	700	4615	STD	14	TL	156A6
	23.1 - 26	DW 20 B ; DW 20 A	-	587	1585	700	4615	DB	16	TL	159A6
	23.1 - 26	DW 20 B ; DW 20 A	-	587	1585	700	4615	DB HD	16	TL	159A6
	23.1 - 26	DW 20 B ; DW 20 A	-	587	1585	700	4615	HD	16	TT	159A6
	23.1 - 26	DW 20 B ; DW 20 A	-	587	1585	700	4615	STD	16	TL	159A6
	23.1 - 26	DW 20 B ; DW 20 A	-	587	1585	700	4615	STD	16	TT	159A6

STD: Standard - DB: Dual Bead - HD: Heavy Duty - DB HD: Dual Bead Heavy Duty





Bias



TR 135



TR 135 is best suitable for tractors in soil tillage applications. Its reinforced casing and the special cut-and-chip resistance compound provide an extended tire life-cycle. Traction, self-cleaning properties and load capacity are key features which make the TR 135 tire the ideal partner even on the most difficult ground conditions.

Technologies



Special Compound



Reinforced Carcass

Performance



Traction



High Load Capacity



Self-Cleaning



Durability





Cut and Chip Resistance

	Tire size	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS
		Rec.	Alt.								
Ø 26"	23.1 - 26	DW 20 B ; DW 20 A	-	587	1585	700	4615	DB	18	TL	161 A6
Ø 28"	8.3 - 28	W 7	W 6	213	1104	519	3347	STD	6	TT	103 A6
	8.3 - 28	W 7	W 6	213	1104	519	3347	STD	8	TT	108 A6
	9.5 - 28	W 8	W 7	235	1155	548	3557	STD	6	TT	108 A6
	9.5 - 28	W 8	W 7	235	1155	548	3557	STD	8	TT	114 A6
	11.2 - 28	W 10	W 9	284	1205	565	3543	HD	8	TT	118 A6
	11.2 - 28	W 10	W 9	284	1205	565	3543	STD	8	TT	118 A6
	11.2 - 28	W 10	W 9	284	1205	565	3543	STD	10	TT	122 A6
	12.4 - 28	W 11	W 9 ; W 10	325	1260	584	3876	STD	6	TT	117 A6
	12.4 - 28	W 11	W 9 ; W 10	325	1260	584	3876	HD	8	TT	123 A6
	12.4 - 28	W 11	W 9 ; W 10	325	1260	584	3876	STD	8	TT	123 A6
	12.4 - 28	W 11	W 9 ; W 10	325	1260	584	3876	STD	10	TT	127 A6
	12.4 - 28	W 11	W 9 ; W 10	325	1260	584	3876	STD	12	TT	131 A6
13.6 - 28	W 12	W 11	345	1310	607	4023	HD	8	TT	125 A6	

STD: Standard - DB: Dual Bead - HD: Heavy Duty



	Tire size	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS
		Rec.	Alt.								
											
Ø 28"	13.6 - 28	W 12	W 11	345	1310	606	3908	STD	8	TT	125 A6
	13.6 - 28	W 12	W 11	345	1310	606	3908	STD	12	TT	134 A6
	13.6 - 28	W 12	W 11	345	1310	606	3908	STD	14	TT	137 A6
	14.9 - 28	W 13	W 11; W 12	378	1365	634	4170	STD	6	TT	125 A6
	14.9 - 28	W 13	W 11; W 12	378	1365	634	4170	HD	8	TT	130 A6
	14.9 - 28	W 13	W 11; W 12	378	1365	634	4170	STD	8	TT	130 A6
	14.9 - 28 (28)	W 13	W 11; W 12	378	1365	634	4170	STD	8	TL	130 A6
	14.9 - 28	W 13	W 11; W 12	378	1365	634	4170	HD	12	TT	137 A6
	14.9 - 28	W 13	W 11; W 12	378	1365	634	4170	STD	12	TT	137 A6
	14.9 - 28	W 13	W 11; W 12	378	1365	634	4170	STD	14	TT	139 A6
	18.4 - 28	W 16 L	W 15 L	467	1501	691	4413	STD	8	TL	138 A6
	18.4 - 28	W 16 L	W 15 L	467	1501	691	4413	STD	12	TL	147 A6
Ø 30"	7.2 - 30	W 6	-	185	1095	523	3219	STD	6	TT	95 A6
	9.5 - 30	W 8	W 7	241	1200	567	3528	STD	6	TT	109 A6

STD: Standard - HD: Heavy Duty





Bias



A6



TR 135



TR 135 is best suitable for tractors in soil tillage applications. Its reinforced casing and the special cut-and-chip resistance compound provide an extended tire life-cycle. Traction, self-cleaning properties and load capacity are key features which make the TR 135 tire the ideal partner even on the most difficult ground conditions.

Technologies



Special Compound



Reinforced Carcass

Performance



Traction



High Load Capacity



Self-Cleaning



Durability





Cut and Chip Resistance

	Tire size	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS
		Rec.	Alt.								
Ø 30"	9.5 - 30	W 8	W 7	241	1200	567	3528	STD	8	TT	115 A6
	14.9 - 30	W 13	W 11 ; W 12	378	1415	659	4316	STD	8	TT	131 A6
	15 - 30 (18.4 - 30)	W 16 L	W 15 L	460	1545	714	4542	STD	12	TT	149 A6
	15 - 30 (18.4 - 30)	W 16 L	W 15 L	460	1545	714	4542	STD	14	TT	151 A6
	16.9 - 30	W 15 L	W 14 L	429	1485	678	4535	STD	8	TT	137 A6
	16.9 - 30	W 15 L	W 14 L	429	1485	678	4535	STD	10	TT	139 A6
	16.9 - 30 (14 - 30)	W 15 L	W 14 L	429	1485	678	4535	STD	14	TT	146 A6
	16.9 - 30 (14 - 30)	W 15 L	W 14 L	429	1485	678	4535	STD	16	TT	149 A6
	18.4 - 30	W 16 L	W 15 L	460	1545	697	4712	HD	8	TT	139 A6
	18.4 - 30	W 16 L	W 15 L	460	1545	697	4712	STD	8	TT	139 A6
	18.4 - 30	W 16 L	W 15 L	460	1545	697	4712	HD	10	TT	145 A6
	18.4 - 30	W 16 L	W 15 L	460	1545	697	4712	HD	10	TL	145 A6
	18.4 - 30	W 16 L	W 15 L	460	1545	697	4712	STD	10	TT	145 A6
	18.4 - 30	W 16 L	W 15 L	460	1545	697	4712	HD	12	TT	149 A6

STD: Standard - HD: Heavy Duty



	Tire size	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS
		Rec.	Alt.								
											
Ø 30"	18.4 - 30	W 16 L	W 15 L	460	1545	697	4712	STD	12	TL	149A6
	18.4 - 30	W 16 L	W 15 L	460	1545	697	4712	STD	12	TT	149A6
	18.4 - 30	W 16 L	W 15 L	460	1545	697	4712	STD	14	TT	151A6
	18.4 - 30	W 16 L	W 15 L	460	1545	697	4712	STD	16	TT	154A6
	23.1 - 30	DW 20 B ; DW 20 A	-	600	1700	773	5217	STD	8	TT	146A6
	23.1 - 30	DW 20 B ; DW 20 A	-	600	1700	773	5217	STD	8	TL	146A6
	23.1 - 30	DW 20 B ; DW 20 A	-	600	1700	773	5217	DB	12	TT	155A6
	23.1 - 30	DW 20 B ; DW 20 A	-	600	1700	773	5217	STD	12	TL	155A6
	23.1 - 30	DW 20 B ; DW 20 A	-	600	1700	773	5217	STD	12	TT	155A6
	23.1 - 30	DW 20 B ; DW 20 A	-	600	1700	773	5217	DB	18	TT	164A6
	23.1 - 30	DW 20 B ; DW 20 A	-	600	1700	773	5217	DB	18	TL	164A6
Ø 32"	8.3 - 32	W 7	W 6	211	1195	572	3585	STD	6	TT	105A6
	8.3 - 32	W 7	W 6	211	1195	572	3585	STD	8	TT	111A6
	9.5 - 32	W 8	W 7	235	1255	594	3686	STD	6	TT	110A6

STD: Standard - DB: Dual Bead





Bias



TR 135



TR 135 is best suitable for tractors in soil tillage applications. Its reinforced casing and the special cut-and-chip resistance compound provide an extended tire life-cycle. Traction, self-cleaning properties and load capacity are key features which make the TR 135 tire the ideal partner even on the most difficult ground conditions.

Technologies



Special Compound



Reinforced Carcass

Performance



Traction



High Load Capacity



Self-Cleaning



Durability





Cut and Chip Resistance

	Tire size	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS
		Rec.	Alt.								
Ø 32"	11.2 - 32	W 10	W 9	287	1310	615	4007	HD	8	TL	120 A6
	12.4 - 32	W 11	W 9; W 10	325	1360	639	3998	STD	6	TT	119 A6
	12.4 - 32	W 11	W 9; W 10	325	1360	639	3998	HD	8	TT	124 A6
	12.4 - 32	W 11	W 9; W 10	325	1360	639	3998	STD	8	TT	124 A6
	12.4 - 32	W 11	W 9; W 10	325	1360	639	3998	HD	10	TT	128 A6
Ø 34"	16.9 - 34	W 15 L	W 14 L	429	1585	728	4794	HD	8	TT	139 A6
	16.9 - 34	W 15 L	W 14 L	429	1585	728	4794	STD	8	TT	139 A6
	16.9 - 34	W 15 L	W 14 L	429	1585	728	4794	HD	10	TT	142 A6
	16.9 - 34	W 15 L	W 14 L	429	1585	728	4794	STD	10	TT	142 A6
	16.9 - 34	W 15 L	W 14 L	429	1585	728	4794	HD	12	TT	144 A6
	16.9 - 34	W 15 L	W 14 L	429	1585	728	4794	STD	12	TT	144 A6
	16.9 - 34	W 15 L	W 14 L	429	1585	728	4794	HD	14	TT	142 A6
	18.4 - 34	W 16 L	W 15 L	467	1650	751	5009	STD	6	TT	137 A6
	18.4 - 34	W 16 L	W 15 L	467	1650	751	5009	HD	8	TT	142 A6

STD: Standard - HD: Heavy Duty



	Tire size	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS
		Rec.	Alt.								
											
Ø 34"	18.4 - 34	W 16 L	W 15 L	467	1650	751	5009	STD	8	TT	142 A6
	18.4 - 34	W 16 L	W 15 L	467	1650	751	5009	HD	10	TT	146 A6
	18.4 - 34	W 16 L	W 15 L	467	1650	751	5009	STD	10	TT	146 A6
	18.4 - 34	W 16 L	W 15 L	467	1650	751	5009	HD	12	TT	151 A6
	18.4 - 34	W 16 L	W 15 L	467	1650	751	5009	HD SPL	12	TT	151 A6
	18.4 - 34	W 16 L	W 15 L	467	1650	751	5009	STD	12	TT	151 A6
	18.4 - 34	W 16 L	W 15 L	467	1650	751	5009	HD	14	TT	154 A6
	18.4 - 34	W 16 L	W 15 L	467	1650	751	5009	STD	14	TT	154 A6
	23.1 - 34	DW 20 B ; DW 20 A	-	585	1810	834	5321	STD	10	TT	153 A6
	23.1 - 34	DW 20 B ; DW 20 A	-	585	1810	834	5321	STD	10	TL	153 A6
Ø 36"	8.3 - 36	W 7	W 6	211	1295	628	4028	STD	6	TT	107 A6
	8.3 - 36	W 7	W 6	211	1295	628	4028	STD	8	TT	113 A6
	9.5 - 36	W 8	W 7	235	1360	646	4000	STD	10	TT	122 A6
	12.4 - 36	W 11	W 9 ; W 10	325	1465	696	4546	HD	8	TT	126 A6

STD: Standard - HD: Heavy Duty - HD SPL: Heavy Duty Special





Bias



Technologies



Special Compound



Reinforced Carcass

Performance



Traction



High Load Capacity



Self-Cleaning



Durability



Cut and Chip Resistance





TR 135

TR 135 is best suitable for tractors in soil tillage applications. Its reinforced casing and the special cut-and-chip resistance compound provide an extended tire life-cycle. Traction, self-cleaning properties and load capacity are key features which make the TR 135 tire the ideal partner even on the most difficult ground conditions.

	Tire size	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS
		Rec.	Alt.								
Ø 36"	12.4 - 36	W 11	W 9; W 10	325	1465	696	4546	STD	8	TT	126 A6
	12.4 - 36	W 11	W 9; W 10	325	1465	696	4546	HD	10	TT	131 A6
	12.4 - 36	W 11	W 9; W 10	325	1465	696	4546	STD	10	TT	131 A6
	12.4 - 36	W 11	W 9; W 10	325	1465	696	4546	HD	12	TT	135 A6
	12.4 - 36	W 11	W 9; W 10	325	1465	696	4546	STD	12	TT	135 A6
	12.4 - 36	W 11	W 9; W 10	325	1465	696	4546	HD	14	TL	139 A6
	12.4 - 36	W 11	W 9; W 10	325	1465	696	4546	HD	14	TT	139 A6
	12.4 - 36	W 11	W 9; W 10	325	1465	696	4546	STD	14	TT	139 A6
	13.6 - 36	W 12	W 11	345	1515	713	4687	STD	6	TT	125 A6
	13.6 - 36	W 12	W 11	345	1515	712	4687	STD	8	TT	129 A6
	13.6 - 36	W 12	W 11	345	1515	713	4687	HD	10	TT	134 A6
	13.6 - 36	W 12	W 11	345	1515	713	4687	STD	10	TT	134 A6
Ø 38"	11.2 - 38	W 10	W 9	284	1460	-	-	STD	6	TL	117 A6
	12.4 - 38	W 11	W 9; W 10	325	1525	718	4670	STD	8	TT	127 A6

STD: Standard - HD: Heavy Duty



	Tire size	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS
		Rec.	Alt.								
											
Ø 38"	12.4 - 38	W 11	W 9; W 10	325	1525	718	4670	STD	14	TT	138 A6
	12.4 - 38	W 11	W 9; W 10	325	1525	718	4670	STD	14	TL	138 A6
	13.6 - 38 (14.00 - 38)	W 12	W 11	345	1565	735	4832	HD	8	TT	131 A6
	13.6 - 38 (14.00 - 38)	W 12	W 11	345	1565	735	4832	STD	8	TT	131 A6
	13.6 - 38 (14.00 - 38)	W 12	W 11	345	1565	735	4832	HD	12	TT	139 A6
	13.6 - 38 (14.00 - 38)	W 12	W 11	355	1565	735	4832	STD	12	TT	139 A6
	13.6 - 38 (14.00 - 38)	W 12	W 11	345	1565	735	4832	STD	14	TT	142 A6
	14.00 - 38 (13.6 - 38)	W 12	W 11	345	1565	735	4832	STD	8	TT	131 A6
	14.00 - 38 (13.6 - 38)	W 12	W 11	345	1565	735	4832	SPL	12	TT	139 A6
	15.5 - 38	W 14 L	-	395	1585	746	4660	HD	8	TT	133 A6
	15.5 - 38	W 14 L	-	395	1585	746	4660	HD	8	TL	133 A6
	15.5 - 38	W 14 L	-	395	1585	746	4660	STD	8	TT	133 A6
	15.5 - 38	W 14 L	-	395	1585	746	4760	HD	10	TT	138 A6
	15.5 - 38	W 14 L	-	395	1585	746	4660	STD	10	TT	138 A6

STD: Standard - HD: Heavy Duty - SPL: Special





Bias



TR 135



TR 135 is best suitable for tractors in soil tillage applications. Its reinforced casing and the special cut-and-chip resistance compound provide an extended tire life-cycle. Traction, self-cleaning properties and load capacity are key features which make the TR 135 tire the ideal partner even on the most difficult ground conditions.

Technologies



Special Compound



Reinforced Carcass

Performance



Traction



High Load Capacity



Self-Cleaning



Durability





Cut and Chip Resistance

	Tire size	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS
		Rec.	Alt.								
Ø 38"	15.5 - 38	W 14 L	-	395	1585	746	4660	STD	12	TT	141 A6
	16.9 - 38	W 15 L	W 14 L	429	1685	788	4954	HD	8	TT	141 A6
	16.9 - 38	W 15 L	W 14 L	429	1685	788	4954	STD	8	TT	141 A6
	16.9 - 38	W 15 L	W 14 L	429	1685	788	4954	HD	10	TT	143 A6
	16.9 - 38	W 15 L	W 14 L	429	1685	788	4954	STD	10	TT	143 A6
	16.9 - 38	W 15 L	W 14 L	429	1685	788	4954	STD	12	TT	146 A6
	18.4 - 38	W 16 L	W 15 L	467	1750	794	5366	HD	8	TT	143 A6
	18.4 - 38	W 16 L	W 15 L	467	1750	794	5366	STD	8	TT	143 A6
	18.4 - 38	W 16 L	W 15 L	467	1750	794	5366	HD	10	TT	148 A6
	18.4 - 38	W 16 L	W 15 L	467	1750	794	5366	HD	10	TL	148 A6
	18.4 - 38	W 16 L	W 15 L	467	1750	794	5366	HD	12	TT	153 A6
	18.4 - 38	W 16 L	W 15 L	467	1750	794	5366	STD	12	TT	153 A6
	18.4 - 38	W 16 L	W 15 L	467	1750	794	5366	STD	12	TL	153 A6
	18.4 - 38	W 16 L	W 15 L	467	1750	794	5366	STD	14	TT	155 A6

STD: Standard - HD: Heavy Duty



	Tire size	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS
		Rec.	Alt.								
											
Ø 38"	20.8 - 38	W 18 L	W 16 L	530	1835	846	5684	STD	8	TT	148 A6
	20.8 - 38	W 18 L	W 16 L	530	1835	846	5684	HD	12	TT	156 A6
	20.8 - 38	W 18 L	W 16 L	530	1835	846	5684	STD	12	TT	156 A6
	20.8 - 38	W 18 L	W 16 L	530	1835	846	5684	STD	12	TL	156 A6
	20.8 - 38	W 18 L	W 16 L	530	1835	846	5684	STD	14	TT	160 A6
	20.8 - 38	W 18 L	W 16 L	530	1835	846	5684	DB HD	16	TT	163 A6
	20.8 - 38	W 18 L	W 16 L	530	1835	846	5684	DB HD	18	TT	166 A6
	20.8 - 38	W 18 L	W 16 L	530	1835	846	5684	DB HD	18	TL	166 A6
Ø 42"	9.5 - 42	W 8	W 7	246	1510	721	4663	STD	10	TT	125 A6
	12.4 - 42	W 10 ; W 10 A	-	322	1630	770	5011	STD	10	TL	134 A6
	20.8 - 42 (42)	W 18 L	W 16 L	535	1950	909	5733	STD	12	TL	158 A6
	20.8 - 42	W 18 L	W 16 L	535	1950	909	5733	STD	12	TT	158 A6
	20.8 - 42	W 18 L	W 16 L	535	1950	909	5733	STD	16	TL	165 A6
	20.8 - 42	W 18 L	W 16 L	535	1950	909	5733	DB HD	18	TL	168 A6

STD: Standard - HD: Heavy Duty - DB HD: Dual Bead Heavy Duty



Bias

R-1

A6

151



TR 136

TR 136 has been developed by BKT to equip tractors and trailers in soil tillage and haulage operations. This tire provides improved traction in all working conditions along with best cut and chip resistance to reduce machine downtime and increase your productivity. Thanks to the increased number of lugs, TR 136 provides outstanding traction even at high loads.

Technologies



Special Compound



More Lugs

Performance



Cut and Chip Resistance



Durability



High Load Capacity



Traction

	Tire size	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS
		Rec.	Alt.								
Ø 26"	18.4 - 26	W 16 L	W 15 L	480	1450	646	4205	SPL	12	TL	146 A6
	18.4 - 26	W 16 L	W 15 L	480	1450	646	4205	STD	14	TL	150 A6
	18.4 - 26	W 16 L	W 15 L	480	1450	646	4205	STD	12	TL	146 A6
	18.4 - 26	W 16 L	W 15 L	480	1450	646	4205	STD	12	TT	146 A6
Ø 28"	12.4 - 28	W 11	W 9; W 10	315	1275	595	3749	STD	8	TT	123 A6
Ø 30"	16.9 - 30	W 15 L	W 14 L	429	1485	677	4455	HD	8	TT	137 A6
	16.9 - 30	W 15 L	W 14 L	429	1485	687	4523	SPL	12	TT	143 A6
	16.9 - 30	W 15 L	W 14 L	429	1485	677	4455	SPL	8	TT	137 A6
	16.9 - 30	W 15 L	W 14 L	429	1485	687	4523	SPL	12	TL	143 A6
	16.9 - 30 (14 - 30)	W 15 L	W 14 L	429	1485	677	4455	STD	14	TT	146 A6
	16.9 - 30	W 15 L	W 14 L	429	1485	677	4455	STD	8	TT	137 A6
	16.9 - 30	W 15 L	W 14 L	429	1485	677	4455	STD	10	TT	139 A6
	16.9 - 30	W 15 L	W 14 L	429	1485	687	4523	STD	12	TT	143 A6
	18.4 - 30	W 16 L	W 15 L	467	1550	712	4719	HD	8	TT	139 A6
	18.4 - 30	W 16 L	W 15 L	467	1550	712	4719	HD	12	TT	149 A6
	18.4 - 30	W 16 L	W 15 L	467	1550	712	4719	HD	14	TT	151 A6
	18.4 - 30	W 16 L	W 15 L	467	1550	712	4719	SPL	12	TT	149 A6
	18.4 - 30	W 16 L	W 15 L	467	1550	712	4719	STD	8	TT	139 A6

SPL: Special - STD: Standard - HD: Heavy Duty



TR 144

TR 144 is suitable to equip small tractors to be used in soil tillage operations. TR 144 ensures outstanding performance in all operating conditions which require excellent traction with high loads. It is also available in a "special" version, which is best suitable for heavy-duty service.

	Tire size	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS
		Rec.	Alt.								
Ø 16"	7 - 16	6 L ; 6 LB ; 6.00 F	-	183	740	344	2223	STD	4	TT	75 A6
	7 - 16	6 L ; 6 LB ; 6.00 F	-	183	740	344	2223	STD	4	TL	75 A6
	7 - 16	6 L ; 6 LB ; 6.00 F	-	183	740	347	2253	STD	6	TT	84 A6
	8 - 16	6 L ; 6 LB ; 6.00 F	-	200	785	358	2342	STD	4	TT	83 A6
	8 - 16	6 L ; 6 LB ; 6.00 F	-	200	785	358	2342	HD	6	TT	91 A6
	8 - 16	6 L ; 6 LB ; 6.00 F	-	200	785	358	2342	STD	6	TT	91 A6
	8 - 16	6 L ; 6 LB ; 6.00 F	-	200	785	358	2342	STD	6	TL	91 A6
	8 - 16	6 L ; 6 LB ; 6.00 F	-	200	785	358	2342	SPL	6	TT	91 A6
	8 - 16	6 L ; 6 LB ; 6.00 F	-	200	785	358	2342	STD	8	TT	98 A6
	9.5 - 16	W 8 L	8 LB	245	850	388	2558	STD	6	TT	96 A6
	9.5 - 16	W 8 L	8 LB	245	850	388	2558	STD	6	TL	96 A6
	9.5 - 16	W 8 L	8 LB	245	850	388	2558	STD	8	TT	102 A6
9.5 - 16	W 8 L	8 LB	245	850	388	2558	STD	8	TL	102 A6	

STD: Standard - SPL: Special - HD: Heavy Duty



Bias



Performance



High Load Capacity



Traction





Bias



Performance



High Load Capacity



Traction



TR 144

TR 144 is suitable to equip small tractors to be used in soil tillage operations. TR 144 ensures outstanding performance in all operating conditions which require excellent traction with high loads. It is also available in a "special" version, which is best suitable for heavy-duty service.

	Tire size	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS
		Rec.	Alt.								
Ø 18"	8 - 18	W 6	W 7 ; 5,50 F	195	840	385	2509	STD	4	TT	85 A6
	8 - 18	W 6	W 7 ; 5,50 F	195	840	385	2509	STD	6	TT	94 A6
	8 - 18	W 6	W 7 ; 5,50 F	195	840	391	2535	SPL	6	TT	94 A6
	8 - 18	W 6	W 7 ; 5,50 F	195	840	385	2509	STD	8	TT	100 A6
	8 - 18	W 6	W 7 ; 5,50 F	195	840	391	2535	SPL	8	TT	100 A6
Ø 20"	8.3 - 20	W 7	W 6	211	890	414	2670	STD	6	TT	96 A6
	8.3 - 20	W 7	W 6	211	890	414	2670	HD	6	TT	96 A6
Ø 22"	9.5 - 22	W 8	W 7	235	1000	464	3008	STD	6	TT	104 A6

STD: Standard - SPL: Special - HD: Heavy Duty





TR 145

TR 145 has been specifically designed for small tractors. The special tread pattern provides excellent traction and outstanding self-cleaning properties. The wide and deep lug design ensures an extended tire service life. The TR 145 tire has a large contact area which offers excellent driving comfort and high directional stability.

	Tire size	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS
		Rec.	Alt.								
Ø 12"	160/90 - 12	4.00	-	160	631	294	1969	STD	6	TT	76 A6

STD: Standard



Bias



Performance



Durability



Self-Cleaning



Traction





Bias



Technologies



Special Compound



Extra Deep Tread

Performance



Traction



High Load Capacity



Self-Cleaning



Durability





TR 171

TR 171 is a deep tread tire suitable for tractors in soil tillage operations. Thanks to its outstanding self-cleaning properties, it is ideal for wet and moist soil. Designed with a special compound, TR 171 provides excellent traction and extraordinary durability also in the harshest operating conditions.

	Tire size	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS
		Rec.	Alt.								
Ø 12"	5.00 - 12	3.00 D DT ; 3.00 D	4 JA ; 3.50 B	130	580	272	1750	STD	4	TT	61 A6
	5.00 - 12	3.00 D DT ; 3.00 D	4 JA ; 3.50 B	130	580	272	1750	STD	6	TT	67 A6
	6.00 - 12	4.00 E DT ; 4.00 E	4 JA	160	635	298	1953	STD	6	TT	76 A6
Ø 16"	9.5 - 16	W 8 L	8 LB	241	845	395	2607	STD	6	TT	96 A6
Ø 18"	8.00 - 18	W 6	W 7 ; 5.50 F	190	845	391	2617	STD	4	TT	85 A6
	8.00 - 18	W 6	W 7 ; 5.50 F	190	845	391	2579	STD	6	TT	94 A6
	8.00 - 18	W 6	W 7 ; 5.50 F	190	845	391	2617	STD	8	TT	100 A6
	9.5 - 18	W 8	-	241	900	423	2790	STD	8	TT	105 A6
Ø 20"	8.3 - 20	W 7	W 6	210	900	423	2704	STD	6	TT	96 A6
	8.3 - 20	W 7	W 6	210	900	422	2788	HD	6	TT	96 A6
	8.3 - 20	W 7	W 6	210	900	422	2806	STD	8	TT	101 A6
	8.3 - 20	W 7	W 6	210	900	424	2785	HD	8	TT	101 A6
	9.5 - 20	W 8	W 7	241	955	449	2942	STD	6	TT	101 A6
	9.5 - 20	W 8	W 7	241	955	449	2942	STD	8	TT	107 A6

STD: Standard - HD: Heavy Duty



	Tire size	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS
		Rec.	Alt.								
											
Ø 20"	9.5 - 20	W 8	W 7	241	955	449	2942	HD	8	TT	107A6
	11.2 - 20	W 10	W 9;9	285	1005	471	3101	STD	8	TT	113A6
Ø 22"	8.3 - 22	W 7	W 6	205	945	444	2778	STD	8	TT	104A6
	9.5 - 22	W 8	W 7	244	1005	472	3107	STD	8	TT	110A6
Ø 24"	8.3 - 24	W 7	W 6	210	1005	474	3014	STD	6	TT	100A6
	8.3 - 24	W 7	W 6	210	1005	474	3153	STD	8	TT	105A6
	8.3 - 24	W 7	W 6	210	1005	474	3153	HD	8	TT	105A6
	9.5 - 24	W 8	W 7	240	1066	500	3260	STD	6	TT	106A6
	9.5 - 24	W 8	W 7	240	1066	496	3263	STD	8	TT	111A6
	11.2 - 24	W 10	W 9	285	1105	519	3388	STD	6	TT	110A6
	11.2 - 24	W 10	W 9	285	1105	517	3403	STD	8	TT	116A6
	11.2 - 24	W 10	W 9	285	1105	517	3403	STD	10	TT	120A6
	12.4 - 24	W 11	W 9;W 10	315	1165	544	3557	STD	4	TT	106A6
	12.4 - 24	W 11	W 9;W 10	315	1165	544	3557	STD	6	TT	115A6

STD: Standard - HD: Heavy Duty





Bias

R-1W

A6

148

Technologies



Special Compound



Extra Deep Tread

Performance



Traction



High Load Capacity



Self-Cleaning



Durability





TR 171

TR 171 is a deep tread tire suitable for tractors in soil tillage operations. Thanks to its outstanding self-cleaning properties, it is ideal for wet and moist soil. Designed with a special compound, TR 171 provides excellent traction and extraordinary durability also in the harshest operating conditions.

	Tire size	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS
		Rec.	Alt.								
Ø 24"	12.4 - 24	W 11	W 9; W 10	315	1165	544	3557	STD	8	TT	120 A6
	12.4 - 24	W 11	W 9; W 10	315	1165	544	3557	HD	8	TT	120 A6
	13.6 - 24	W 12	W 11	355	1210	562	3674	STD	6	TT	119 A6
	13.6 - 24	W 12	W 11	355	1210	562	3674	STD	8	TT	123 A6
	14.9 - 24	W 13	W 11; W 12	391	1265	575	3792	STD	6	TT	123 A6
	14.9 - 24	W 13	W 11; W 12	391	1265	575	3792	STD	8	TT	128 A6
Ø 26"	11.2 - 26	W 10	W 9	284	1155	541	3461	STD	8	TT	117 A6
	12.4 - 26	W 11	W 10; W 9	315	1210	573	3727	STD	8	TT	121 A6
	13.6 - 26	W 12	W 11	340	1270	580	3774	STD	4	TT	110 A6
	13.6 - 26	W 12	W 11	340	1270	582	3815	STD	6	TT	120 A6
	13.6 - 26	W 12	W 11	340	1270	587	3835	STD	8	TT	126 A6
	13.6 - 26	W 12	W 11	340	1270	589	3774	HD	12	TT	135 A6
Ø 28"	12.4 - 28	W 11	W 9; W 10	315	1260	589	3860	STD	6	TT	117 A6
	12.4 - 28	W 11	W 9; W 10	315	1260	589	3860	STD	8	TT	123 A6

STD: Standard - HD: Heavy Duty



	Tire size	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS
		Rec.	Alt.								
											
Ø 28"	12.4 - 28	W 11	W 9 ; W 10	315	1260	589	3860	STD	12	TT	131 A6
	13.6 - 28	W 12	W 11	350	1325	614	4013	STD	4	TT	112 A6
	13.6 - 28	W 12	W 11	350	1325	614	4013	STD	6	TT	121 A6
	13.6 - 28	W 12	W 11	350	1325	614	4013	STD	8	TT	125 A6
	13.6 - 28	W 12	W 11	350	1325	616	4007	HD	8	TT	125 A6
	13.6 - 28	W 12	W 11	350	1325	614	4013	STD	12	TT	134 A6
	13.6 - 28	W 12	W 11	350	1325	614	4013	HD	12	TT	134 A6
	14.9 - 28	W 13	W 11 ; W 12	388	1370	636	4246	STD	8	TT	130 A6
	14.9 - 28	W 13	W 11 ; W 12	388	1370	635	4176	HD	8	TT	130 A6
	14.9 - 28	W 13	W 11 ; W 12	388	1370	636	4246	STD	12	TT	137 A6
	14.9 - 28	W 13	W 11 ; W 12	388	1370	636	4246	HD	12	TT	137 A6
	15.9 - 28	W 13	W 11 ; W 12	410	1420	356	4357	STD	12	TT	140 A6
	16.9 - 28	W 15 L	W 14 L	435	1440	674	4496	STD	8	TT	135 A6
	16.9 - 28	W 15 L	W 14 L	435	1440	674	4496	STD	12	TT	143 A6

STD: Standard - HD: Heavy Duty





Bias



Technologies



Special Compound



Extra Deep Tread

Performance



Traction



High Load Capacity



Self-Cleaning



Durability



TR 171

TR 171 is a deep tread tire suitable for tractors in soil tillage operations. Thanks to its outstanding self-cleaning properties, it is ideal for wet and moist soil. Designed with a special compound, TR 171 provides excellent traction and extraordinary durability also in the harshest operating conditions.

	Tire size	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS
		Rec.	Alt.								
Ø 30"	14.9 - 30	W 13	W 11 ; W 12	380	1415	658	4282	STD	8	TT	131 A6
	16.9 - 30	W 15 L	W 14 L	430	1490	687	4535	STD	8	TT	137 A6
	16.9 - 30	W 15 L	W 14 L	430	1490	687	4605	STD	12	TT	143 A6
	18.4 - 30	W 16 L	W 15 L	470	1550	710	4706	STD	10	TT	145 A6
Ø 32"	12.4 - 32	W 11	W 9 ; W 10	315	1370	643	4232	STD	8	TT	124 A6
Ø 34"	16.9 - 34	W 15 L	W 14 L	429	1585	736	4838	STD	8	TT	139 A6
	18.4 - 34	W 16 L	W 15 L	470	1655	768	4866	STD	10	TT	146 A6
Ø 36"	12.4 - 36	W 11	W 9 ; W 10	315	1470	691	4332	STD	8	TT	126 A6
	13.6 - 36	W 12	W 11	345	1520	717	4647	STD	8	TT	129 A6
Ø 38"	13.6 - 38	W 12	W 11	345	1565	729	4818	STD	8	TT	131 A6
	16.9 - 38	W 15 L	W 14 L	429	1685	788	4954	STD	8	TT	141 A6
	18.4 - 38	W 16 L	W 15 L	470	1760	815	5364	STD	10	TT	148 A6

STD: Standard



TR 173

TR 173 is a tractor tire suitable for wet conditions and paddy fields. The special tread pattern provides outstanding self-cleaning properties in addition to reduced soil compaction thanks to a large contact area.

	Tire size	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS
		Rec.	Alt.								
Ø 18"	8 - 18	W 6	W 7 ; 5.50 F	200	841	392	2525	STD	6	TT	94A6
Ø 20"	8.3 - 20	W 7	W 6	211	890	418	2713	STD	6	TT	96A6
Ø 22"	8.3 - 22	W 7	W 6	211	940	443	2869	STD	6	TT	98A6
	9.5 - 22	W 8	W 7	241	997	472	3045	STD	6	TT	104A6
Ø 24"	8.3 - 24	W 7	W 6	211	995	467	3009	STD	6	TT	100A6
	9.5 - 24	W 8	W 7	241	1047	493	3238	STD	6	TT	106A6
	12.4 - 24	W 11	W 9 ; W 10	315	1160	541	3509	STD	6	TT	115A6
Ø 26"	13.6 - 26	W 12	W 11	345	1255	586	3786	STD	6	TT	120A6
Ø 28"	14.9 - 28	W 13	W 11 ; W 12	385	1367	631	4215	STD	8	TT	130A6
	14.9 - 28	W 13	W 11 ; W 12	385	1367	631	4215	HD	12	TT	137A6
	16.9 - 28	W 15 L	W 14 L	445	1450	669	4454	STD	6	TT	129A6

STD: Standard - HD: Heavy Duty



Bias



A6



130

Technologies



Extra Deep Tread



Heavy Duty



Strong Casing

Performance



Traction



Self-Cleaning



Durability



For muddy ground



Bias



FARM 2000



The FARM 2000 tire is suitable on tractors for soil tillage applications. It has been designed with a special cut-and-chip resistant compound to ensure better durability. Thanks to its strong casing, FARM 2000 offers high load capacity. It also provides great traction and self-cleaning properties.

Technologies



Reinforced Carcass



Special Compound

Performance



Durability



Traction



Cut and Chip Resistance



Self-Cleaning









High Load Capacity

Ø	Tire size	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS	
		Rec.	Alt.								DW	FR
15.3"	260/70 - 15.3	9.00	-	265	775	349	2294	STD	-	TL	114A8	126A8
	300/80 - 15.3	9.00	-	300	890	388	2608	STD	-	TL	120A8	132A8
16"	250/80 - 16	W 8	W 7 ; W 9 ; W 8 L	240	820	369	2429	STD	-	TT	113A8	125A8
	250/80 - 16	W 8	W 7 ; W 9 ; W 8 L	240	820	369	2429	STD	-	TL	113A8	125A8
18"	8 - 18	W 6	-	195	840	390	2458	STD	4	TT	85A6	
	8 - 18	W 6	-	195	840	393	2539	STD	6	TT	94A6	
	9.5 - 18	W 8	W 7	241	900	419	2751	STD	8	TT	105A6	
	250/80 - 18	W 8	W 7 ; W 9	240	870	394	2679	STD	-	TT	115A8	127A8
	250/80 - 18	W 8	W 7 ; W 9	240	870	394	2679	STD	-	TL	115A8	127A8
20"	8.3 - 20	W 7	-	210	895	431	2714	STD	4	TT	-	
	8.3 - 20	W 7	-	210	895	431	2714	STD	6	TT	-	
	9.5 - 20	W 8	W 7	241	945	445	2911	STD	8	TT	107A6	
22"	9.5 - 22	W 8	W 7	243	1007	470	3074	STD	8	TT	110A6	

STD: Standard



	Tire size	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS
		Rec.	Alt.								
											
Ø 24"	8.3 - 24	W 7	W 6	211	995	473	3032	STD	6	TT	-
	8.3 - 24	W 7	W 6	211	995	473	3032	STD	8	TT	105A6
Ø 28"	12.4 - 28	W 11	W 9; W 10	320	1288	603	3969	STD	8	TT	123A6
	12.4 - 28	W 11	W 9; W 10	320	1288	603	3969	STD	10	TT	124A6
	12.4 - 28	W 11	W 9; W 10	320	1288	603	3969	STD	12	TT	125A6
	12.4 - 28	W 11	W 9; W 10	320	1288	603	3969	SPL	12	TT	125A6
	13.6 - 28	W 12	W 11	345	1335	622	4080	STD	8	TT	125A6
	13.6 - 28	W 12	W 11	345	1335	622	4080	STD	10	TT	127A6
	13.6 - 28	W 12	W 11	345	1335	622	4080	STD	12	TT	128A6
	13.6 - 28	W 12	W 11	345	1335	622	4080	SPL	12	TT	128A6
	14.9 - 28	W 13	W 11; W 12	385	1375	636	4194	STD	8	TT	130A6
	14.9 - 28	W 13	W 11; W 12	385	1375	636	4194	STD	10	TT	132A6
	14.9 - 28	W 13	W 11; W 12	385	1375	636	4194	STD	12	TT	134A6
	14.9 - 28	W 13	W 11; W 12	385	1375	636	4194	SPL	12	TT	134A6

STD: Standard - SPL: Special





Bias



FARM 2000

The FARM 2000 tire is suitable on tractors for soil tillage applications. It has been designed with a special cut-and-chip resistant compound to ensure better durability. Thanks to its strong casing, FARM 2000 offers high load capacity. It also provides great traction and self-cleaning properties.

Technologies



Reinforced Carcass



Special Compound

Performance



Durability



Traction



Cut and Chip Resistance



Self-Cleaning



High Load Capacity

	Tire size	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS
		Rec.	Alt.								
Ø 28"	14.9 - 28	W 13	W 11 ; W 12	385	1375	636	4194	STD	14	TT	136A6
	16.9 - 28	W 15 L	W 14 L	429	1420	657	4351	STD	12	TT	143A6
	16.9 - 28	W 15 L	W 14 L	429	1420	657	4351	HD	8	TT	135A6
Ø 30"	18.4 - 30	W 16 L	-	470	1560	716	4776	STD	14	TT	151A6



STD: Standard - HD: Heavy Duty





FARM 2000 PLUS

FARM 2000 PLUS is an agriculture tire featuring a higher number of lugs for better performance in the fields. The deep tread provides an extended tire life and great traction, whereas the superior tread compound ensures better cut and chip resistance. FARM 2000 PLUS shows excellent self-cleaning features and specially designed lug angles making the tire particularly suitable for field and haulage applications.

Tire size	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS	
	Rec.	Alt.									
											
Ø 28"	16.9 - 28	W 15 L	W 14 L	440	1435	657	4311	SPL	12	TT	143A6
	16.9 - 28	W 15 L	W 14 L	440	1435	657	4311	STD	12	TT	143A6

SPL: Special - STD: Standard



Bias



R-1



A6



143

Technologies



More Lugs



Deep Tread

Performance



Cut and Chip Resistance



Durability



High Load Capacity



Self-Cleaning



Traction



Bias



R-1



A6



139

Technologies



Reinforced Carcass

Performance



Self-Cleaning



Traction



High Load Capacity



Cut and Chip Resistance



Durability



FARM SPECIAL

FARM SPECIAL is a tractor tire suitable for soil tillage operations. The strong casing provides a high level of puncture resistance and a longer service life, whilst the rounded shoulders prevent soil damages ensuring the protection of the valuable crops. FARM SPECIAL features a unique tread design with special mud breakers for best self-cleaning properties. In addition, dual angled lugs provide excellent traction and reduced slippage.



	Tire size	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS
		Rec.	Alt.								
Ø 24"	9.5 - 24	W 8	W 7	240	1050	491	3194	STD	8	TT	112 A6
	11.2 - 24	W 10	W 9	285	1095	509	3283	STD	8	TT	116 A6
	12.4 - 24	W 11	W 9; W 10	320	1155	534	3504	STD	8	TT	121 A6
	13.6 - 24	W 12	W 11	350	1205	554	3635	STD	8	TT	123 A6
	14.9 - 24	W 13	W 11; W 12	378	1255	572	3775	STD	8	TT	128 A6
Ø 28"	11.2 - 28	W 10	W 9	285	1205	563	3694	STD	8	TT	118 A6
	12.4 - 28	W 11	W 9; W 10	315	1265	589	3853	STD	8	TT	123 A6
	13.6 - 28	W 12	W 11	350	1310	610	3985	STD	8	TT	125 A6
	14.9 - 28	W 13	W 11; W 12	375	1355	620	4105	STD	8	TT	130 A6
Ø 30"	16.9 - 30	W 15 L	W 14 L	431	1469	671	4456	STD	8	TT	137 A6
	18.4 - 30	W 16 L	W 15 L	451	1533	689	4599	STD	8	TT	139 A6
Ø 32"	12.4 - 32	W 11	W 9; W 10	320	1360	634	4137	STD	8	TT	124 A6
Ø 36"	13.6 - 36	W 12	W 11	345	1515	704	4591	STD	8	TT	129 A6
Ø 38"	13.6 - 38 (14.00 - 38)	W 12	W 11	345	1565	736	4874	STD	8	TT	131 A6
	14.00 - 38 (13.6 - 38)	W 12	W 11	345	1565	736	4874	STD	8	TT	131 A6
	15.5 - 38	W 14 L	-	394	1575	731	4813	STD	8	TT	133 A6

STD: Standard



AS 2001

AS 2001 is a bias cross-ply tire which best suits tractors in soil tillage operations. Its design provides excellent traction and self-cleaning properties. AS 2001 is made of a special cut-and-chip resistant compound that also ensures great load capacity.

	Tire size	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS
		Rec.	Alt.								
											
Ø 22"	9.5 - 22	W 8	W 7	243	1007	470	3074	STD	8	TT	110 A6
Ø 26"	18.4 - 26	W 16 L	W 15 L	467	1475	650	4250	STD	10	TT	142 A6
	18.4 - 26	W 16 L	W 15 L	467	1475	650	4250	STD	10	TL	142 A6
	18.4 - 26	W 16 L	W 15 L	467	1475	650	4250	STD	12	TT	146 A6
	18.4 - 26	W 16 L	W 15 L	467	1475	650	4250	STD	12	TL	146 A6
	18.4 - 26	W 16 L	W 15 L	467	1475	650	4250	STD	14	TT	149 A6
Ø 28"	16.9 - 28	W 15 L	W 14 L	429	1420	651	4319	STD	8	TT	135 A6
	16.9 - 28	W 15 L	W 14 L	429	1420	651	4319	STD	10	TT	139 A6
	16.9 - 28	W 15 L	W 14 L	429	1420	651	4319	STD	12	TT	143 A6
	16.9 - 28	W 15 L	W 14 L	429	1420	651	4319	STD	12	TL	143 A6
	16.9 - 28	W 15 L	W 14 L	429	1420	651	4319	SPL	12	TT	143 A6

STD: Standard - SPL: Special



Bias



R-1



A6



149

Technologies



Special Compound

Performance



Traction



High Load Capacity



Self-Cleaning



Cut and Chip Resistance



Bias



R-1



A6



151

Technologies



More Lugs



Extra Deep Tread

Performance



Durability



Self-Cleaning



Traction



High Load Capacity



Cut and Chip Resistance



TRAC FARM

TRAC FARM is a heavy-duty tire specifically designed for tractors in soil tillage and haulage applications. Its deep tread and the special cut-and-chip-resistant compound make the tire suitable for the most difficult operating conditions, ensuring the best return on investment during the entire product life-cycle. TRAC FARM has been designed with more lugs providing extraordinary traction and self-cleaning properties.

	Tire size	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS
		Rec.	Alt.								
Ø 20"	11.2 - 20	W 10	W 9	290	1000	463	2940	STD	8	TT	111 A6
Ø 28"	12.4 - 28	W 11	W 9; W 10	320	1295	602	3890	STD	10	TT	124 A6
	12.4 - 28	W 11	W 9; W 10	320	1295	602	3890	STD	12	TT	125 A6
	13.6 - 28	W 12	W 11	365	1345	625	4034	STD	12	TT	128 A6
	16.9 - 28	W 15 L	W 14 L	440	1435	663	4219	STD	12	TT	143 A6
Ø 30"	18.4 - 30	W 16 L	W 15 L	467	1550	716	4557	STD	12	TT	149 A6
	18.4 - 30	W 16 L	W 15 L	470	1565	716	4557	STD	14	TT	151 A6
	18.4 - 30	W 16 L	W 15 L	470	1565	716	4557	HD	14	TT	151 A6

STD: Standard - HD: Heavy Duty





TRAC FARM PLUS

TRAC FARM PLUS is a rear tractor tire specifically designed for soil tillage and haulage applications. The tire features a deeper tread with dual angle lugs to ensure both excellent traction and a comfortable ride on the road. The special tread design provides more contact for better stability and great self-cleaning properties. TRAC FARM PLUS ensures a longer tire life-cycle.

	Tire size	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS
		Rec.	Alt.								
Ø 28"	12.4 - 28	W 11	W 9; W 10	320	1295	603	3899	STD	12	TT	125 A6
	13.6 - 28	W 12	W 11	365	1345	621	4088	STD	12	TT	128 A6
	14.9 - 28	W 13	W 12; W 11	390	1380	642	4179	STD	12	TT	134 A6
	16.9 - 28	W 15 L	W 14 L	440	1435	660	4298	STD	12	TT	143 A6
Ø 30"	16.9 - 30	W 15 L	W 14 L	440	1475	679	4466	STD	12	TT	144 A6

STD: Standard



Bias



R-1



A6



144

Technologies



Larger Footprint

Performance



Durability



Handling and Comfort



High Load Capacity



Self-Cleaning



Traction



Bias



A6



Technologies



Extra Deep Tread

Performance



Cut and Chip Resistance



Durability



High Load Capacity



Self-Cleaning



Traction





COMMANDER (R)

COMMANDER (R) is an agricultural tire featuring a deep tread with strong lug bases for a longer tire life-cycle. The special dual-angle lug design provides excellent traction in the fields and top self-cleaning properties. The strong casing is made of a cut-and-chip-resistant compound providing better puncture resistance together with high load capacity. COMMANDER (R) is the perfect tire for soil tillage, haulage and harvesting operations.

	Tire size	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS
		Rec.	Alt.								
Ø 20"	9.5 - 20	W 8	W 7	245	970	456	2949	STD	12	TT	109 A6
	Ø 24"	9.5 - 24	W 8	W 7	245	1065	507	3308	STD	12	TT
	11.2 - 24	W 10	W 9	295	1125	533	3483	STD	12	TT	123 A6
	12.4 - 24	W 11	W 10	328	1180	569	3669	STD	12	TT	128 A6
	12.4 - 24	W 11	W 10	328	1180	569	3669	STD	8	TT	121 A6
Ø 28"	12.4 - 28	W 11	W 9 ; W 10	320	1285	600	3946	STD	12	TT	125 A6
	13.6 - 28	W 12	W 11	360	1345	623	4068	STD	12	TT	128 A6
	14.9 - 28	W 13	W 11 ; W 12	388	1380	642	4176	STD	12	TT	134 A6
	15.9 - 28	W 13	W 11 ; W 12	405	1410	-	-	STD	12	TT	140 A6
	16.9 - 28	W 15 L	W 14 L	440	1435	663	4274	STD	12	TT	143 A6
	16.9 - 28 (21L)	W 15 L	W 14 L	440	1435	-	-	STD	12	TT	143 A6
	17.9 - 28	W 15 L	W 14 L	458	1515	-	-	STD	12	TT	144 A6
	Ø 30"	16.9 - 30	W 15 L	W 14 L	440	1480	689	4537	STD	12	TT
18.4 - 30		W 16 L	-	472	1565	734	4834	STD	14	TT	151 A6

STD: Standard



	Tire size	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS
		Rec.	Alt.								
											
Ø 30"	18.4 - 30	W 16 L	-	472	1565	734	4834	STD	18	TL	155 A6
	18.4 - 30	W 16 L	-	472	1565	734	4834	STD	18	TT	155 A6
	18.4 - 30	W 16 L	-	472	1565	734	4834	STD	8	TT	139 A6
Ø 36"	9.5 - 36	W 8	W 7	246	1376	-	-	STD	12	TT	126 A6

STD: Standard





Bias

R-2

A6

160

Technologies



Extra Deep Tread

Performance



Cut and Chip Resistance



Durability



For muddy ground



Self-Cleaning



Traction



TR 270

TR 270 is a tractor tire suitable for soil tillage applications. It is specially designed for providing maximum performance on wet and moist soil. In these soil conditions, a tire is required to offer superior grip and enhanced self-cleaning features. TR 270 perfectly meets all these characteristics.

	Tire size	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS
		Rec.	Alt.								
Ø 26"	23.1 - 26	DW 20 A ; DW 20 B	-	590	1646	739	4922	STD	8	TT	145 A6
	23.1 - 26	DW 20 A ; DW 20 B	-	590	1646	739	4922	STD	10	TT	149 A6
	23.1 - 26	DW 20 A ; DW 20 B	-	590	1646	739	4922	STD	12	TL	153 A6
	23.1 - 26	DW 20 A ; DW 20 B	-	590	1646	739	4922	STD	12	TT	153 A6
	23.1 - 26	DW 20 A ; DW 20 B	-	590	1646	739	4922	STD	14	TT	156 A6
Ø 30"	18.4 - 30	DW 16 L ; DW 16 A	W 15 L ; DW 15 A	465	1580	720	4787	STD	8	TL	139 A6
	18.4 - 30	DW 16 L ; DW 16 A	W 15 L ; DW 15 A	465	1580	720	4787	STD	8	TT	139 A6
	18.4 - 30	DW 16 L ; DW 16 A	W 15 L ; DW 15 A	465	1580	720	4787	STD	12	TT	149 A6
	23.1 - 30	DW 20 A ; DW 20 B	-	590	1748	790	5227	STD	8	TT	146 A6
	23.1 - 30	DW 20 A ; DW 20 B	-	590	1748	790	5227	STD	10	TT	151 A6
	23.1 - 30	DW 20 A ; DW 20 B	-	590	1748	790	5227	STD	12	TT	155 A6
Ø 34"	18.4 - 34	DW 16 A ; W 16 L	W 15 L	465	1682	771	5029	STD	8	TT	142 A6
	18.4 - 34	DW 16 A ; W 16 L	W 15 L	465	1682	771	5029	STD	12	TT	150 A6
	23.1 - 34	DW 20 A ; DW 20 B	-	590	1850	841	5532	STD	8	TT	148 A6

STD: Standard



	Tire size	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS
		Rec.	Alt.								
Ø 34"	23.1 - 34	DW 20 A ; DW 20 B	-	590	1850	841	5532	STD	10	TT	153 A6
	23.1 - 34	DW 20 A ; DW 20 B	-	590	1850	841	5532	STD	12	TT	156 A6
	23.1 - 34	DW 20 A ; DW 20 B	-	590	1850	841	5532	STD	14	TL	160 A6
Ø 38"	13.6 - 38	W12	DW 12 A ; W 11	345	1600	-	4828	STD	6	TT	122 A6
	18.4 - 38	W 16 A ; W 16 L	W 15 L ; DD 16	465	1784	822	5334	STD	8	TT	143 A6
	18.4 - 38	W 16 A ; W 16 L	W 15 L ; DD 16	465	1784	822	5334	STD	12	TT	153 A6
	20.8 - 38	W 18 A ; W 18 L	DD 18 ; DW 18 A	530	1875	861	5695	STD	8	TT	148 A6
	20.8 - 38	W 18 A ; W 18 L	DD 18 ; DW 18 A	530	1875	861	5695	STD	10	TT	151 A6
	20.8 - 38	W 18 A ; W 18 L	DD 18 ; DW 18 A	530	1875	861	5695	STD	12	TT	156 A6
Ø 46"	13.6 - 46	W 12	W 12 A	345	1804	-	5440	STD	6	TT	125 A6

STD: Standard





Bias



Technologies



Extra Deep Tread

Performance



Traction



For muddy ground



Self-Cleaning



Durability



Cut and Chip Resistance





TR 273

TR 273 is a tractor tire suitable for soil tillage and specifically designed to provide maximum performance on wet and moist soil. In these soil conditions, a tire is required to offer superior grip and enhanced self-cleaning properties. TR 273 perfectly meets all these characteristics.

	Tire size	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS
		Rec.	Alt.								
Ø 24"	12.4 - 24	W 11	W 10	315	1195	550	3722	STD	8	TT	121 A6
	13.6 - 24	W 12	W 11	350	1240	570	3795	STD	8	TT	123 A6
	14.9 - 24	W 13	W 12	380	1310	595	4044	STD	8	TT	128 A6
	14.9 - 24	W 13	W 12	380	1310	595	4044	STD	10	TT	132 A6
Ø 26"	18.4 - 26	W 16	W 15	470	1490	673	4534	STD	12	TT	146 A6
	23.1 - 26	DW 20 A ; DW 20 B	-	590	1655	737	5053	STD	10	TT	149 A6
	23.1 - 26	DW 20 A ; DW 20 B	-	590	1655	737	5053	STD	12	TT	153 A6
	23.1 - 26	DW 20 A ; DW 20 B	-	590	1655	737	5053	STD	14	TT	156 A6
	28 L - 26	DW 25 B	DW 23 B	714	1673	765	4861	DB	16	TL	160 A6
Ø 28"	14.9 - 28	W 13	W 12	385	1410	651	4368	STD	8	TT	130 A6
Ø 30"	16.9 - 30	W 15 L	W 14 L	435	1530	706	4800	STD	12	TT	143 A6
	18.4 - 30	W 16 L	W 15 L	465	1585	723	4924	STD	12	TT	149 A6
	23.1 - 30	DW 20 A ; DW 20 B	-	590	1748	794	5356	STD	10	TT	151 A6
	23.1 - 30	DW 20 A ; DW 20 B	-	590	1748	794	5356	STD	14	TT	157 A6

STD: Standard - DB: Dual Bead



	Tire size	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS
		Rec.	Alt.								
											
Ø 32"	30.5 L - 32	DH 27 B	DW 27 B	765	1865	-	-	STD	14	TL	164A6
Ø 34"	18.4 - 34	DW 16 A	W 16 L ; W 15 L DW 15 L	475	1701	775	5253	STD	12	TT	150A6
	23.1 - 34	DW 20 A ; DW 20 B	-	590	1850	833	5634	STD	10	TT	153A6
	23.1 - 34	DW 20 A ; DW 20 B	-	590	1850	831	5674	STD	14	TT	160A6
Ø 38"	18.4 - 38	W 16	W 15	465	1800	822	5579	STD	12	TT	152A6
	20.8 - 38	W 18 A ; W 18 L	DD 18 ; DW 18 A	533	1886	-	-	STD	12	TT	156A6

STD: Standard





Bias



PUDDLE SPECIAL (A)

PUDDLE SPECIAL is a R-2 agricultural tire specifically designed for operations in paddy fields. The extra deep tread design along with the special lug pattern provides best grip and excellent traction even on wet and soft soil. The wide center bar provides better adaptability for road applications and provides extraordinary service performance. In addition, PUDDLE SPECIAL shows superior self-cleaning features and excellent durability.

Technologies



Extra Deep Tread



More Lugs

Performance



Durability



Self-Cleaning



Traction

	Tire size	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS
		Rec.	Alt.								
Ø 28"	12.4 - 28	W 11	W 10	325	1385	649	4067	STD	12	TT	137 A2
Ø 32"	11-32	W 10	W 9	305	1465	702	4384	STD	6	TL	111 A2
	11-32	W 10	W 9	305	1465	702	4384	STD	6	TT	111 A2



STD: Standard





PUDDLE SPECIAL (B)

PUDDLE SPECIAL is a R-2 agricultural tire specifically designed for operations in paddy fields. The extra deep tread design along with the special lug pattern provides best grip and excellent traction even on wet and soft soil. The wide center bar provides better adaptability for road applications and provides extraordinary service performance. In addition, PUDDLE SPECIAL shows superior self-cleaning features and excellent durability.

Tire size	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS	
	Rec.	Alt.									
											
Ø 26"	120/90 - 26	4 JA	-	127	940	448	2847	STD	6	TL	90A2
	120/90 - 26	4 JA	-	127	940	448	2847	STD	6	TT	90A2

STD: Standard



Bias



A2



90

Technologies



Extra Deep Tread

Performance



Durability



Self-Cleaning



Traction



Bias



TR 318

TR 318 is specifically designed for sprayers and implement machinery. Its dual-angled lugs provide excellent traction and outstanding driving comfort. TR 318 also features extraordinary self-cleaning properties.

Performance



Self-Cleaning



Stability



Traction

	Tire size	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS
		Rec.	Alt.								
Ø 12"	23 X 9.00 - 12	7.0	-	220	585	-	-	STD	6	TT	93A3
	23 X 9.00 - 12	7.0	-	220	585	-	-	STD	6	TL	93A3
	26 X 10.00 - 12	8.5	-	265	675	-	-	STD	8	TT	107A3






STD: Standard





AT 316

AT 316 is suitable for compact utility tractors in municipality and maintenance applications. The special tread design provides excellent traction without compromising field protection - an essential feature for this kind of application. AT 316 is also available as "aramid-belted" version to provide increased puncture resistance.

	Tire size	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS
		Rec.	Alt.								
											
Ø 12"	24 X 12.00 - 12	10.50 I - 55 ; I - 70 ; I - 90	-	315	610	271	1769	STD	4	TL	-
	24 X 12.00 - 12	10.50 I - 55 ; I - 70 ; I - 90	-	315	610	271	1769	AB	6	TL	-

STD: Standard - AB: Aramid Belted



Bias

Performance



Self-Cleaning



Traction





Bias



AT 523

BKT's AT 523 is a multifunctional tire designed to provide reliable performance in agricultural, turf, and industrial applications. Its tread design ensures excellent traction and self-cleaning capabilities, which are key features for tackling a variety of surfaces: from rammed earth and turf to hard surfaces typical of industrial settings. The flatter profile and enlarged center block, combined with the R-1 and R-4 type design, provide greater stability on the road, while the rounded shoulders protect the turf, preserving its integrity even under intensive operating conditions. The strong carcass and a cut-resistant tread compound make AT 523 particularly durable. This combination of ruggedness, versatility and ease of use makes AT 523 the ideal solution for those who need a single tire that can cope with a variety of situations: from soil preparation and lawn operations to industrial use.

Technologies



Strong Casing



Rounded Shoulder Technology

Performance



Traction



Self-Cleaning



Hard Surfaces



Ideal for grassland



Stability

	Tire size	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS
		Rec.	Alt.								
Ø 12"	26 X 12.00 - 12	10.50 I - 55 ; I - 70 ; I - 90	10½ JA ; 8½ JA	300	650	300	1898	STD	6	TL	107 A8

STD: Standard





STAR TRAC

STAR TRAC is the BKT tire for harvesters at cotton farms, which is able to support heavy loads. Thanks to its particularly deep tread design, it ensures both excellent traction in the fields and excellent performance during road transfers. On cotton plantations showing the typical middle-sized shrubs, harvesting demands tire features like excellent flotation and reduced soil compaction. Moreover, the tire is made of a special compound providing high resistance against cuts and typical damages of this application.

	Tire size	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS
		Rec.	Alt.								
Ø 32"	DW 500/95 D 32	13.00 DW	-	500	1836	809	5324	STD	-	TL	162 A8/ 169 A5
	VA 500/95 D 32	13.00 VA	-	500	1836	809	5324	STD	-	TL	179 A8/ 186 A5

STD: Standard



Bias



A8



186

Performance



High Load Capacity



High Puncture Resistance



Bias



HARVESTER SPECIAL

HARVESTER SPECIAL has been specifically designed for harvesters. Its dual –angled lugs provide excellent traction in the fields and a comfortable ride on the road. The special tread design provides a large contact area for extraordinary stability. HARVESTER SPECIAL features a strong casing and a particularly cut-and-chip resistant compound ensuring a longer tire life-cycle.

Performance



Comfort



Cut and Chip Resistance



Stability



Traction

	Tire size	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS
		Rec.	Alt.								
Ø 25"	23.5 - 25	-	19.50/2.5	-	615	1665	715	5058	20	DB	191 A2
Ø 26"	23.1 - 26	-	DW 20 B ; DW 20 A	-	587	1585	720	4806	16	DB	159 A6

DB: Dual Bead





TR 137

TR 137 is BKT's most suitable tire for all harvesting operations. It ensures excellent traction in the fields even with high loads. The tire is available in different versions: the "aramid-belted" version provides better puncture resistance and protection against all typical damages of this application; the "HD" version provides extraordinary cut and chip resistance, and an extended tire life-cycle.

	Tire size	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS
		Rec.	Alt.								
Ø 32"	24.5 - 32	DW 21 B	DW 20 B	622	1805	807	5343	STD	12	TL	159 A6
	24.5 - 32	DW 21 B	DW 20 B	622	1805	807	5343	STD	14	TL	163 A6
	30.5 L - 32	DH 27 B	DW 27 B	770	1865	831	5520	STD	12	TL	162 A6
	30.5 L - 32	DH 27 B	DW 27 B	770	1865	831	5520	STD	14	TL	164 A6
	30.5 L - 32	DH 27 B	DW 27 B	770	1865	831	5520	STD	16	TL	167 A6
	30.5 L - 32	DH 27 B	DW 27 B	770	1865	831	5520	AB	18	TL	170 A6
	30.5 L - 32	DH 27 B	DW 27 B	770	1865	831	5520	HD	18	TL	170 A6

STD: Standard - AB: Aramid Belted - HD: Heavy Duty



Bias



R-1



A6



170

Technologies



Aramid Belted



Heavy Duty

Performance



High Load Capacity



Traction



Durability



Self-Cleaning



Stubble Resistance



Cut and Chip Resistance



Bias



A8



115

Performance



Durability



TR 360

TR 360 is suitable for implement machinery in on-and-off-the-road transport as well as lawn and garden applications. The particular tread design along with the casing structure ensures a long tire life-cycle.

	Tire size	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS
		Rec.	Alt.								
Ø 8"	18 X 7 - 8	5.5	-	180	460	202	1334	STD	6	TL	-
Ø 15"	240/70 - 15 (28 X 9.00 - 15)	7.00 I	6½ K	235	740	-	-	STD	8	TL	115A8

STD: Standard





TR 882

TR 882 is a very versatile tire suitable for several applications and vehicles. It has been designed to fit implement machinery, hay harvesters/balers and sugar cane machinery. Engineered with a special compound to reduce damage, this tire features also great durability and traction in every field condition. TR 882 is also available as "aramid-belted", "HD" and "special" versions to meet specific end user requirements.

	Tire size	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS	
		Rec.	Alt.								DW	FR
Ø 15.5"	400/60 - 15.5	AG 13.00	-	400	875	378	2605	AB	14	TL	132 A8	145 A8
	400/60 - 15.5	AG 13.00	-	400	875	378	2605	AB HD	18	TL	137 A8	149 A8
	400/60 - 15.5	AG 13.00	-	400	875	378	2605	HD	14	TL	132 A8	145 A8
	400/60 - 15.5	AG 13.00	-	400	875	378	2605	HD	18	TL	137 A8	149 A8
	400/60 - 15.5	AG 13.00	-	400	875	378	2605	SPL	14	TL	132 A8	145 A8
	400/60 - 15.5	AG 13.00	-	400	875	378	2605	SPL	18	TL	137 A8	149 A8
	400/60 - 15.5	AG 13.00	-	400	875	378	2605	STD	8	TL	122 A8	134 A8
	400/60 - 15.5	AG 13.00	-	400	875	378	2605	STD	14	TL	132 A8	145 A8
	400/60 - 15.5	AG 13.00	-	400	875	378	2605	STD	18	TL	137 A8	149 A8

AB: Aramid Belted - AB HD: Aramid Belted Heavy Duty - HD: Heavy Duty - SPL: Special - STD: Standard



Bias



A8



149

Technologies



Heavy Duty



Special Compound



Aramid Belted

Performance



Cut and Chip Resistance



Durability



Stubble Resistance



Traction



Bias



158



FLOTATION 558

FLOTATION 558 is a cross-ply flotation tire suitable for hay harvesters/balers, tankers and trailers both on and off the road. It is particularly recommended whenever traction is essential for good soil tillage in addition to high load capacity.

Performance



High Load Capacity



Durability



Traction

Ø 22.5"	Tire size	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS	
		Rec.	Alt.								DW	FR
Ø 22.5"	400/55 - 22.5	AG 11.75	12.25; 13.00; AG 13.00	405	1020	445	3084	STD	14	TL	138 A8/ 134 B	150 A8/ 146 B
	400/55 - 22.5	AG 11.75	12.25; 13.00; AG 13.00	405	1020	445	3084	STD	16	TL	140 A8/ 136 B	152 A8/ 148 B
	400/55 - 22.5	AG 11.75	12.25; 13.00; AG 13.00	405	1020	445	3084	AB HD	16	TL	140 A8/ 136 B	152 A8/ 148 B
	400/55 - 22.5	AG 11.75	12.25; 13.00; AG 13.00	405	1020	445	3084	STD	20	TL	144 A8/ 140 B	156 A8/ 152 B
	500/45 - 22.5	AG 16.00	-	500	1045	471	3167	STD	12	TL	136 A8/ 132 B	148 A8/ 144 B
	500/45 - 22.5	AG 16.00	-	500	1045	471	3167	STD	16	TL	142 A8/ 138 B	154 A8/ 150 B
	500/45 - 22.5	AG 16.00	-	500	1045	471	3167	AB HD	16	TL	142 A8/ 138 B	154 A8/ 150 B
	500/45 - 22.5	AG 16.00	-	500	1045	471	3167	STD	20	TL	146 A8/ 142 B	158 A8/ 154 B

STD: Standard - AB HD: Aramid Belted Heavy Duty





BK 308

BK 308 has been specially designed for trailers and utility tractors. It features excellent traction on all surfaces and tread tie bars to reduce tread groove cracking. The strong casing provides excellent durability and puncture resistance whereas the special tread compound ensures a longer service life.

	Tire size	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS
		Rec.	Alt.								
∅ 20"	6.50 - 20	5.50 F	4.00 E ; 5.00 F	190	865	-	-	STD	10	TT	112 A6

STD: Standard



Bias



A6



112

Performance



Durability



High Puncture Resistance



Traction





Bias



Performance



Steering Control





TF 8181

TF 8181 is a field and road tire designed for 2WD tractors in soil tillage and haulage applications. This tire provides excellent steering performance.

	Tire size	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS
		Rec.	Alt.								
Ø 15"	4.00 - 15	3.00 D	4 J	112	605	287	1834	STD	4	TT	66 A6
	5.00 - 15	4.00 E	3.00 D; 4 J; 4½ J	142	655	307	1951	SPL	6	TT	82 A6
	5.00 - 15	4.00 E	3.00 D; 4 J; 4½ J	142	655	307	1951	STD	4	TT	73 A6
	5.00 - 15	4.00 E	3.00 D; 4 J; 4½ J	142	655	307	1951	STD	6	TT	82 A6
Ø 16"	4.00 - 16	3.00 D	-	112	630	301	1877	STD	4	TT	69 A6
	4.50 - 16	3.00 D	-	122	655	311	1952	STD	4	TT	73 A6
	5.00 - 16	4.00 E	3.00 D; 4 J; 4½ J	140	680	322	2025	STD	4	TT	76 A6
	5.00 - 16	4.00 E	3.00 D; 4 J; 4½ J	140	680	322	2025	SPL	6	TT	84 A6
	5.00 - 16	4.00 E	3.00 D; 4 J; 4½ J	140	680	322	2025	STD	6	TT	84 A6
	5.50 - 16	4.00 E	3.50 D; 4.50 E	158	720	340	2145	SPL	6	TT	86 A6
	5.50 - 16	4.00 E	3.50 D; 4.50 E	158	720	340	2145	STD	6	TT	86 A6
	6.00 - 16	4.50 E	4.00 E; 5 K; 5.00 F	173	745	350	2220	SPL	6	TT	88 A6
	6.00 - 16	4.50 E	4.00 E; 5 K; 5.00 F	173	745	350	2220	STD	6	TT	88 A6
	6.00 - 16	4.50 E	4.00 E; 5 K; 5.00 F	173	745	350	2220	SPL	8	TT	94 A6
6.00 - 16	4.50 E	4.00 E; 5 K; 5.00 F	173	745	350	2220	STD	8	TT	94 A6	

STD: Standard - SPL: Special



	Tire size	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS
		Rec.	Alt.								
											
Ø 16"	6.50 - 16	4.50 E	4.00 E; 5 K; 5.00 F; 5.50 F	180	770	361	2295	SPL	6	TT	91 A6
	6.50 - 16	4.50 E	4.00 E; 5 K; 5.00 F; 5.50 F	180	770	361	2295	STD	6	TT	91 A6
	6.50 - 16	4.50 E	4.00 E; 5 K; 5.00 F; 5.50 F	180	770	361	2295	HD	8	TT	98 A6
	6.50 - 16	4.50 E	4.00 E; 5 K; 5.00 F; 5.50 F	180	770	361	2295	SPL	10	TT	102 A6
	7.50 - 16	5.50 F	5.00 F; 5 K; 6.00 F	205	820	383	2445	SPL	6	TT	98 A6
	7.50 - 16	5.50 F	5.00 F; 5 K; 6.00 F	205	820	383	2445	STD	6	TT	98 A6
	7.50 - 16	5.50 F	5.00 F; 5 K; 6.00 F	205	820	383	2445	SPL	8	TT	103 A6
	7.50 - 16	5.50 F	5.00 F; 5 K; 6.00 F	205	820	383	2445	STD	8	TT	103 A6
	7.50 - 16	5.50 F	5.00 F; 5 K; 6.00 F	205	820	383	2445	STD	10	TT	109 A6
	7.50 - 16	5.50 F	5.00 F; 5 K; 6.00 F	205	820	383	2445	IMP	14	TT	-
	9.00 - 16	W 8	6.00 F; W 7; W 8 L	234	855	-	-	STD	8	TT	111 A6
	10.00 - 16	W 8	W 8 L	273	895	411	2667	STD	8	TT	115 A6
11.00 - 16	W 10 L	W 8; W 8 L	326	970	447	2920	STD	8	TT	118 A6	
Ø 18"	6.00 - 18	4.50 E	4.00 E; 5.00 F	172	800	374	2410	STD	8	TT	101 A6
	7.50 - 18	5.50 F	-	208	875	410	2605	SPL	6	TT	101 A6

STD: Standard - SPL: Special - HD: Heavy Duty - IMP: Implement





Bias



Performance



Steering Control



TF 8181

TF 8181 is a field and road tire designed for 2WD tractors in soil tillage and haulage applications. This tire provides excellent steering performance.


	Tire size	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS
		Rec.	Alt.								
Ø 18"	7.50 - 18	5.50 F	-	208	875	410	2605	STD	6	TT	101 A6
	7.50 - 18	5.50 F	-	208	875	410	2605	HD	8	TT	106 A6
	7.50 - 18	5.50 F	-	208	875	410	2605	SPL	8	TT	106 A6
	7.50 - 18	5.50 F	-	208	875	410	2605	STD	8	TT	106 A6
Ø 19"	6.00 - 19	4.50 E	4.00 E ; 5.00 F	174	830	385	2425	STD	6	TT	93 A6
Ø 20"	6.50 - 20	5.00 F	4.00 E ; 5.50 F	180	865	409	2578	STD	6	TT	97 A6
	6.50 - 20	5.00 F	4.00 E ; 5.50 F	180	865	409	2578	SPL	8	TT	101 A6
	6.50 - 20	5.00 F	4.00 E ; 5.50 F	180	865	409	2578	STD	8	TT	101 A6
	7.50 - 20	5.50 F	5.00 F	205	915	431	2725	HD	6	TT	103 A6
	7.50 - 20	5.50 F	5.00 F	205	915	431	2725	STD	6	TT	103 A6
	7.50 - 20	5.50 F	5.00 F	205	915	431	2725	HD	8	TT	109 A6
	7.50 - 20	5.50 F	5.00 F	205	915	431	2725	SPL	8	TT	109 A6
	7.50 - 20	5.50 F	5.00 F	205	915	431	2725	STD	8	TT	109 A6

STD: Standard - SPL: Special - HD: Heavy Duty



TF 9393

TF 9393 is an agricultural front tire specifically designed for small tractors in soils tillage applications and it is particularly suitable on loose soils. Its tread shows a wide center part and shoulder ribs. The special tread design provides excellent steering performance on all surfaces.

Tire size	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS	
	Rec.	Alt.									
											
Ø 16"	7.50 - 16	5.50 F	5.00 F; 6.00 F	210	810	-	-	STD	8	TT	103A6

STD: Standard



Bias



Performance



Steering Control



Bias



Performance



Steering Control





TF 9090

TF 9090 is a tire designed for small tractors in soil tillage operations. The special tread design provides excellent steering performance on loose soil.

	Tire size	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS
		Rec.	Alt.								
Ø 12"	4.00 - 12	3.00 D	2.50 C	112	530	255	1573	STD	4	TT	60 A6
	4.00 - 12	3.00 D	2.50 C	112	530	255	1573	STD	6	TT	68 A6
Ø 15"	5.00 - 15	4.00 E	3.00 D; 4 J; 4½ J	140	655	307	1951	STD	4	TT	73 A6
	5.00 - 15	4.00 E	3.00 D; 4 J; 4½ J	140	655	307	1951	STD	6	TT	82 A6
Ø 16"	4.00 - 16	3.00 D	-	112	630	301	1877	STD	4	TT	69 A6
	5.50 - 16	4.00 E	3.50 D; 4.50 E	150	710	332	2116	STD	6	TT	86 A6
	6.00 - 16	4.50 E	4.00 E; 5 K; 5.00 F	170	735	346	2190	SPL	6	TT	88 A6
	6.00 - 16	4.50 E	4.00 E; 5 K; 5.00 F	170	735	346	2190	STD	6	TT	88 A6
	6.00 - 16	4.50 E	4.00 E; 5 K; 5.00 F	170	735	346	2190	SPL	8	TT	94 A6
	6.00 - 16	4.50 E	4.00 E; 5 K; 5.00 F	170	735	346	2190	STD	8	TT	94 A6
	6.50 - 16	4.50 E	4.00 E; 5 K; 5.00 F; 5.50 F	180	765	359	2280	STD	6	TT	91 A6
	6.50 - 16	4.50 E	4.00 E; 5 K; 5.00 F; 5.50 F	180	765	359	2280	STD	8	TT	98 A6
	7.50 - 16	5.50 F	5.00 F; 5 K; 6.00 F	207	810	379	2414	SPL	6	TT	98 A6
	7.50 - 16	5.50 F	5.00 F; 5 K; 6.00 F	207	810	379	2414	STD	6	TT	98 A6
7.50 - 16	5.50 F	5.00 F; 5 K; 6.00 F	207	810	379	2414	SPL	8	TT	103 A6	

STD: Standard - SPL: Special



	Tire size	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS
		Rec.	Alt.								
											
Ø 16"	7.50 - 16	5.50 F	5.00 F; 5 K; 6.00 F	207	810	379	2414	STD	8	TT	103 A6
	7.50 - 16	5.50 F	5.00 F; 5 K; 6.00 F	207	810	379	2414	STD	10	TT	109 A6
	9.00 - 16	W 8	6.00 F; W 7; W 8 L	257	855	398	2548	STD	8	TT	111 A6
	9.00 - 16	W 8	6.00 F; W 7; W 8 L	257	855	398	2548	SPL	10	TT	116 A6
	9.00 - 16	W 8	6.00 F; W 7; W 8 L	257	855	398	2548	STD	10	TT	116 A6
	10.00 - 16	W 8	W 8 L	275	900	409	2714	SPL	8	TT	115 A6
	10.00 - 16	W 8	W 8 L	275	900	409	2714	SPL	10	TT	119 A6
	10.00 - 16	W 8	W 8 L	275	900	409	2714	STD	8	TT	115 A6
	10.00 - 16	W 8	W 8 L	275	900	409	2714	STD	10	TT	119 A6
	11.00 - 16	W 10 L	W 8; W 8 L	320	970	448	2890	SPL	8	TT	118 A6
	11.00 - 16	W 10 L	W 8; W 8 L	320	970	448	2890	STD	8	TL	118 A6
	11.00 - 16	W 10 L	W 8; W 8 L	320	970	448	2890	STD	8	TT	118 A6
Ø 18"	7.50 - 18	5.50 F	-	207	860	404	2562	SPL	6	TT	101 A6
	7.50 - 18	5.50 F	-	207	860	404	2562	STD	6	TT	101 A6
	7.50 - 18	5.50 F	-	207	860	404	2562	SPL	8	TT	106 A6

STD: Standard - SPL: Special





Bias



Performance



Steering Control



TF 9090

TF 9090 is a tire designed for small tractors in soil tillage operations. The special tread design provides excellent steering performance on loose soil.


	Tire size	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS
		Rec.	Alt.								
Ø 18"	7.50 - 18	5.50 F	-	207	860	404	2562	STD	8	TT	106 A6
	7.50 - 18	5.50 F	-	207	860	404	2562	STD	10	TT	113 A6
Ø 19"	4.00 - 19	3.00 D	-	115	715	343	2145	STD	4	TT	72 A6
	6.00 - 19	4.50 E	4.00 E; 5.00 F	167	815	386	2445	STD	6	TT	93 A6
Ø 20"	7.50 - 20	5.50 F	5.00 F	205	915	431	2725	SPL	6	TT	103 A6
	7.50 - 20	5.50 F	5.00 F	205	915	431	2725	STD	6	TT	103 A6
	7.50 - 20	5.50 F	5.00 F	205	915	431	2725	SPL	8	TT	109 A6
	7.50 - 20	5.50 F	5.00 F	205	915	431	2725	STD	8	TT	109 A6




STD: Standard - SPL: Special





TF 9292

 TF 9292 is an agricultural front tire specifically designed for tractors engaged in soil tillage and haulage operations. TF 9292 is a 3-Rib pattern: its unique center rib design provides moderate traction while the shoulder notches ensure excellent grip and steering performance on different types of terrains. High load capacity is granted by the wide center as shoulder ribs protect the tire to guarantee long durability.

	Tire size	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS
		Rec.	Alt.								
											
 20"	7.50 - 20	5.50 F	5.00 F	207	915	430	2799	STD	12	TT	116A6

STD: Standard



Bias



F-2



A6



116

Technologies



Strong Casing

Performance



Traction



Durability



High Load Capacity





Bias



Technologies



Deep Tread

Performance



Durability



High Load Capacity



Cut and Chip Resistance



COMMANDER (F)

COMMANDER (F) is a front 3-rib pattern tire - perfect for soil tillage and haulage applications. Its deep tread made of a cut-and-chip resistant compound ensures a longer tire life, together with high load capacity.

	Tire size	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS
		Rec.	Alt.								
Ø 16"	5.50 - 16	4.00 E	3.50 D ; 4.50 E	155	720	340	2145	STD	6	TT	86 A6
	6.00 - 16	4.50 E	4.00 E ; 5.00 F	175	750	357	2308	STD	8	TT	94 A6
	6.50 - 16	4.50 E	4.00 E ; 5.00 F ; 5.50 F	183	770	362	2332	STD	8	TT	98 A6
	6.50 - 16	4.50 E	4.00 E ; 5.00 F ; 5.50 F	183	770	362	2332	STD	10	TT	102 A6
	7.50 - 16	5.50 F	5.00 F ; 5 K ; 6.00 F	210	810	381	2477	STD	8	TT	103 A6

STD: Standard



COMMANDER TWIN RIB

COMMANDER TWIN RIB is a 4-rib pattern tire with shoulder notches providing excellent grip. Its wider tread profile ensures good weight distribution. The strong casing along with a superior tread compound provide a longer tire life. COMMANDER TWIN RIB is perfect for soil tillage and haulage applications.

	Tire size	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS
		Rec.	Alt.								
∅ 15"	5.00 - 15	4.00 E	-	145	665	-	-	STD	6	TT	82 A6
∅ 16"	6.00 - 16	4.50 E	4.00 E ; 5.00 F	170	750	-	-	STD	8	TT	94 A6
	6.50 - 16	4.50 E	4.00 E ; 5.00 F ; 5.50 F	180	761	-	-	STD	8	TT	98 A6
	7.50 - 16	5.50 F	5.00 F ; 5 K ; 6.00 F	210	810	-	-	STD	8	TT	103 A6
∅ 20"	6.50 - 20	5.00 F	4.00 E ; 5.50 F	190	875	-	-	STD	8	TT	101 A6

STD: Standard



Bias



Technologies



Deep Tread

Performance



Cut and Chip Resistance



Durability



High Load Capacity



Bias



A6



Technologies



Deep Tread

Performance



Cut and Chip Resistance



Durability



High Load Capacity



COMMANDER 3 RIB

COMMANDER 3 RIB is a 3-rib pattern front tire designed for soil tillage and haulage operations. It provides excellent durability and load capacity thanks to the optimized weight distribution on center and shoulder ribs. The strong casing along with the cut-and-chip resistant compound ensure outstanding puncture resistance.

	Tire size	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS
		Rec.	Alt.								
Ø 16"	6.00 - 16	4.50 E	4.00 E ; 5.00 F	175	740	-	-	STD	8	TT	94A6
	6.00 - 16	4.50 E	4.00 E ; 5.00 F ; 5.50 F	183	765	-	-	STD	8	TT	98A6
	7.50 - 16	5.50 F	5.00 F ; 5 K ; 6.00 F	212	810	-	-	STD	8	TT	-



STD: Standard





POWER RIB F2

POWER RIB F2 has been specially designed for 2WD tractors in soil tillage applications. This field-oriented tire is particularly suitable for all operations where excellent steering performance is required.

Tire size	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS	
	Rec.	Alt.									
											
Ø 15"	11 L - 15 SL	8 LB	10 LB	279	813	374	2423	STD	8	TL	110A6

STD: Standard



Bias



Performance



Steering Control



Bias



Performance



Steering Control



PRO RIB F2M

PRO RIB F2M is an agricultural tire for 2WD tractors in soil tillage applications. It is particularly suitable for all operations requiring a high level of handling.

	Tire size	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS
		Rec.	Alt.								
Ø 15"	9.5 L - 15 SL	7.00	8 LB	240	780	364	2325	STD	8	TL	102A8
	11 L - 15 SL	8 LB	10 LB	280	795	370	2370	STD	8	TL	106A8
Ø 16"	10.00 - 16 SL	8 LB	W 8 L	275	894	409	2620	IND	8	TT	110A8
	10.00 - 16 SL	8 LB	W 8 L	275	894	409	2620	STD	8	TL	110A8
	10.00 - 16 SL	8 LB	W 8 L	275	894	409	2620	STD	8	TT	110A8
	11.00 - 16 SL	10 LB	W 8 L; 8 LB	335	950	440	2830	STD	8	TL	114A8
	11.00 - 16 SL	10 LB	W 8 L; 8 LB	335	950	440	2830	IND	8	TT	114A8
	11.00 - 16 SL	10 LB	W 8 L; 8 LB	335	950	440	2830	STD	8	TT	114A8
Ø 16.1"	14 L - 16.1 SL	W 11 C	-	355	980	453	2920	STD	12	TL	127A8
	16.5 L - 16.1 SL	W 14 C	W 14 CH	430	1072	-	-	STD	10	TL	129A8

STD: Standard - IND: Industrial





RIB F3

RIB F3 is a field-oriented tire designed for 2WD tractors in soil tillage and haulage operations. Some sizes are suitable for transport applications using trailers. The RIB F3 tire is the ideal partner for all operations that require a high level of handling. It has been designed with a hard compound to ensure great durability and stubble resistance.

	Tire size	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS
		Rec.	Alt.								
											
Ø 16"	9.00 - 16	W 8	6.00 F; W 7;W 8 L	245	878	387	2573	HD	12	TT	120 A6/ 112 A8
	9.00 - 16	W 8	6.00 F; W 7;W 8 L	245	878	387	2573	STD	12	TT	120 A6/ 112 A8
	9.00 - 16	W 8	6.00 F; W 7;W 8 L	245	878	387	2573	STD	12	TL	120 A6/ 112 A8

HD: Heavy Duty - STD: Standard



Bias



Technologies



Hard Compound

Performance



Durability



Steering Control



Stubble Resistance



Bias



Performance



Steering Control



STEER FARM

STEER FARM has been designed for 2WD tractors in soil tillage applications, providing excellent steering performance.

	Tire size	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS
		Rec.	Alt.								
Ø 14"	5.20 - 14	3.50 D	4.00 E	135	625	296	1837	STD	6	TT	75 A6
Ø 16"	6.00 - 16	4.50 E	4.00 E ; 5 K ; 5.00 F	170	740	353	2279	STD	8	TT	94 A6
	6.50 - 16	4.50 E	4.00 E ; 5.00 F ; 5.50 F	185	770	-	-	STD	8	TT	98 A6
	7.50 - 16	5.50 F	5.00 F ; 5 K ; 6.00 F	205	805	378	2451	STD	8	TT	103 A6
	7.50 - 16	5.50 F	5.00 F ; 5 K ; 6.00 F	205	805	378	2451	STD	10	TT	109 A6
Ø 20"	6.50 - 20	5.50 F	4.00 E ; 5.00 F	196	878	418	2701	STD	8	TT	101 A6

STD: Standard





Load index

The load index is a code that defines a tire's maximum weight capacity at the speed given by its speed index provided that the usage conditions recommended by the Manufacturer are fully complied with.

Corresponding values of load index (LI) and load capacity per wheel (kg / lbs)

LI	lbs	kg	LI	lbs	kg	LI	lbs	kg	LI	lbs	kg
50	420	190	85	1135	515	120	3085	1400	155	8540	3875
51	430	195	86	1170	530	121	3195	1450	156	8820	4000
52	440	200	87	1200	545	122	3305	1500	157	9095	4125
53	455	206	88	1235	560	123	3415	1550	158	9370	4250
54	465	212	89	1280	580	124	3525	1600	159	9645	4375
55	480	218	90	1325	600	125	3635	1650	160	9920	4500
56	495	224	91	1355	615	126	3750	1700	161	10195	4625
57	505	230	92	1390	630	127	3860	1750	162	10470	4750
58	520	236	93	1435	650	128	3970	1800	163	10745	4875
59	535	243	94	1475	670	129	4080	1850	164	11025	5000
60	550	250	95	1520	690	130	4190	1900	165	11355	5150
61	565	257	96	1565	710	131	4300	1950	166	11685	5300
62	585	265	97	1610	730	132	4410	2000	167	12015	5450
63	600	272	98	1655	750	133	4540	2060	168	12345	5600
64	615	280	99	1710	775	134	4675	2120	169	12785	5800
65	640	290	100	1765	800	135	4805	2180	170	13225	6000
66	660	300	101	1820	825	136	4940	2240	171	13560	6150
67	675	307	102	1875	850	137	5070	2300	172	13890	6300
68	695	315	103	1930	875	138	5205	2360	173	14330	6500
69	715	325	104	1985	900	139	5355	2430	174	14770	6700
70	740	335	105	2040	925	140	5510	2500	175	15210	6900
71	760	345	106	2095	950	141	5675	2575	176	15650	7100
72	785	355	107	2150	975	142	5840	2650	177	16095	7300
73	805	365	108	2205	1000	143	6005	2725	178	16535	7500
74	825	375	109	2270	1030	144	6175	2800	179	17085	7750
75	855	387	110	2335	1060	145	6395	2900	180	17635	8000
76	880	400	111	2405	1090	146	6615	3000	181	18185	8250
77	910	412	112	2470	1120	147	6780	3075	182	18740	8500
78	935	425	113	2535	1150	148	6945	3150	183	19290	8750
79	965	437	114	2600	1180	149	7165	3250	184	19840	9000
80	990	450	115	2680	1215	150	7385	3350	185	20390	9250
81	1020	462	116	2755	1250	151	7605	3450	186	20945	9500
82	1045	475	117	2835	1285	152	7825	3550	187	21495	9750
83	1075	487	118	2910	1320	153	8045	3650	188	22045	10000
84	1100	500	119	3000	1360	154	8265	3750	189	22705	10300

LI	lbs	kg	LI	lbs	kg	LI	lbs	kg
190	23370	10600	200	30865	14000	210	41885	19000
191	24030	10900	201	31965	14500	211	42990	19500
192	24690	11200	202	33070	15000	212	44090	20000
193	25350	11500	203	34170	15500	213	45415	20600
194	26015	11800	204	35270	16000	214	46735	21200
195	26785	12150	205	36375	16500	215	48060	21800
196	27555	12500	206	37475	17000	216	49380	22400
197	28330	12850	207	38580	17500	217	50705	23000
198	29100	13200	208	39680	18000	218	52025	23600
199	29980	13600	209	40785	18500	219	53570	24300

Speed index

The speed index is a value that indicates the maximum admitted speed at which the tire can carry the weight corresponding to its load index provided that the usage conditions recommended by the Manufacturer are fully complied with.

Speed index	A2	A4	A6	A8	B	C	D	E	F	G	J	K
km/h	10	20	30	40	50	60	65	70	80	90	100	110
mph	5	10	20	25	30	35	40	45	50	55	62	68



Corporate Office

Balkrishna Industries Ltd.

BKT HOUSE, C/15, Trade World, Kamala Mills Compound, Senapati Bapat Marg, Lower Parel, Mumbai - 400013, India
Tel: (+91) 22-6666 3800 - Fax: (+91) 22-6666 3898/99 - e-mail: info@bkt-tires.com - bkt-tires.com

BKT Europe srl

Viale Della Repubblica,133
20831 Seregno (MB), Italy
Tel: (+39) 0362 33 03 28
(+39) 0362 32 51 07
Fax: (+39) 0362 23 24 72

BKT USA Inc.

202 Montrose West Ave. Suite 240
Copley, Ohio 44321
Office: (+1) 330 836 1090
Fax: (+1) 330 836 1091

BKT Tires (CANADA) Inc.

55 York Street, Suite 401
Toronto, Ontario M5J 1R7, Canada
Tel: AG/IND (+1) 514 792 9220
OTR (+1) 780 888 5667
Fax: (+1) 416 229 1711



bkt-tires.com